

Official Journal

of the European Communities

ISSN 0378 – 6978

L 358

Volume 30

19 December 1987

English edition

Legislation

Contents

I *Acts whose publication is obligatory*

- ★ Council Regulation (EEC) No 3747/87 of 8 December 1987 temporarily suspending the autonomous Common Customs Tariff duties on a number of industrial products 1

I

(Acts whose publication is obligatory)

COUNCIL REGULATION (EEC) No 3734/87

of 8 December 1987

temporarily suspending the autonomous Common Customs Tariff duty on certain industrial products

THE COUNCIL OF THE EUROPEAN COMMUNITIES,

Having regard to the Treaty establishing the European Economic Community, and in particular Article 28 thereof,

Having regard to the Act of Accession of Spain and Portugal, and in particular Article 32 thereof,

Having regard to the proposal from the Commission,

Whereas production of the products referred to in this Regulation is at present inadequate or non-existent within the Community and producers are thus unable to meet the needs of user industries in the Community;

Whereas it is in the Community's interest in certain cases to suspend the autonomous Common Customs Tariff duties only partially, particularly because of the existence of Community production, and in other cases to suspend them completely;

Whereas, taking account of the difficulties involved in accurately assessing the development of the economic situation in the sectors concerned in the near future, these suspension measures should be taken only temporarily, by fixing their period of validity by reference to the interests of Community production;

Whereas, on account of the suspensions concerned, there is a need to take the measures necessary to maintain Community preference, pursuant to Article 32 of the Act of Accession; whereas, in consequence, the duties under suspension should be considered as basic duties within the meaning of Article 30 (1) of the said Act,

HAS ADOPTED THIS REGULATION:

Article 1

The autonomous Common Customs Tariff duties for the products listed in the Annexes shall be suspended at the level indicated in respect of each of them:

- from 1 January to 31 March 1988 for the products listed in Annex I,
- from 1 January to 30 June 1988 for the products listed in Annex II.

Article 2

The duties under suspension referred to in Article 1, reduced by 60 %, constitute the basic duties on which the Community of Ten applies the successive reductions provided for in Article 31 of the Act of Accession to products which are in free circulation in Spain.

Article 3

This Regulation shall enter into force on 1 January 1988.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 8 December 1987.

For the Council

The President

N. WILHELM

ANNEX I

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 3920 10 11 ex 3920 10 19	Film of a copolymer of ethylene with methyl acrylate, having a thickness of not more than 0,05 mm, for the manufacture of disposable medical gloves (a)	0
ex 8473 30 00	Thin film magnetic heads for disc file peripherals, as well as carrying arms equipped with such magnetic heads, capable of recording to a density of not less than 10 tracks per millimetre	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

ANNEX II

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 1302 14 00	Extract of dewaxed pyrethrum	0
ex 2712 20 00	Synthetic paraffin wax having a molecular weight of not less than 460 and not more than 1 560	0
ex 2904 10 00	Sodium prop-2-ene-1-sulphonate with a purity of not less than 93 % by weight in a powder form for the manufacture of acrylic fibres (a)	0
ex 2917 19 90	Dodecanedioic acid	4
ex 2917 20 00	Cyclohex-1,2-ene-1,2-dicarboxylic anhydride	0
ex 2918 19 90	Dinoprost (INN) for the manufacture of human medical products falling within heading No 3004 (a)	0
ex 2921 29 00	Tetramethylenediamine in aqueous solution, having in the water-free material: — a purity of not less than 99,9 % by weight — a pyrrolidine content of not more than 0,03 % by weight — an aminobutyronitrile content of not more than 0,02 % by weight	0
ex 2922 19 00	Tulobuterol hydrochloride (INNM)	0
ex 2922 50 00	Methyldopa (INN)	0
ex 2925 11 00	Saccharin and its sodium salt	0
ex 2926 90 90	Isophthalonitrile	6
ex 2932 13 00	Tetrahydrofurfuryl alcohol	0
ex 2932 19 00	5-Nitrofurfurylidene di(acetate)	0
ex 2932 19 00	Furan	0
ex 2932 29 90	3'-Chloro-6'-cyclohexylaminospiro[isobenzofuran-1(3H), 9'-xanthen]-3-one	0
ex 2932 29 90	6'-(N-Ethyl- <i>p</i> -toluidino)-2'-(N-methylanilino)spiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0
ex 2932 29 90	6'-(<i>H</i> -Ethyl- <i>p</i> -toluidino)-2'-methylspiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0
ex 2932 29 90	2'-Anilino-6'-(N-ethyl- <i>p</i> -toluidino)-3'-methylspiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0
ex 2932 90 90	2,3-Dihydro-2,2-dimethylbenzofuran-7-ol with a purity of not less than 99,5 % by weight	0
ex 2933 39 90	2-Butoxyethyl (3,5,6-trichloro-2-pyridyloxy)acetate	0
ex 2933 39 90	3,5-Dichloro-2,4,6-trifluoropyridine	0
ex 2941 90 00	Kanamycin sulphate (INNM)	0
ex 3002 39 00	Vaccine consisting of a bacterium obtained by isolating R-980 from <i>Mycoplasma gallisepticum</i> in an oil-based emulsion	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 3504 00 00	Crude proteinaceous material, containing interferon α -2b, obtained from genetically manipulated <i>Escherichia coli</i> for further purification to human interferon α -2b (a)	3
ex 3802 90 00	Acid-activated montmorillonite for the manufacture of self-copy paper (a)	0
ex 3811 21 00	Salts of dinonylnaphthalenesulphonic/acid, dissolved in mineral oils	0
ex 3815 19 00	Catalysts consisting of chromium oxides and titanium dioxide fixed on a support of silicon dioxide, aluminium oxide/or aluminium phosphate	0
ex 3815 90 00	Catalysts, consisting of a mixture of titanium, magnesium and aluminium compounds, in the form of a suspension in hexane, containing by weight: — not less than 3 % and not more than 6 % titanium — not less than 1,5 % and not more than 3 % magnesium — not less than 0,3 and not more than 0,5 % aluminium for use in the production of polyethylene with a density of at least 0,930 g/cm ³ (a)	0
ex 3815 90 00	Catalysts in the form of rodlets, consisting of an acid aluminosilicate (zeolite) with a mole ratio of silicon dioxide: dialuminium trioxide of not less than 500:1 and containing by weight not less than 0,2 % and not more than 0,8 % of platinum	0
ex 3817 10 90	Monoalkylbenzenes, obtained by the alkylation of benzene with polyalkenes/and having an average molecular weight of not less than 680 and not more than 820	0
ex 3818 00 10	Doped silicon wafers, of Czochralski technology, with a diameter of 70 mm or more, unpolished and with an oxygen content of not less than 5×10^{17} atoms per cm ³	0
ex 3823 90 99	Preparation consisting essentially of alkaline asphalt sulphonate having a density of not less than 1,2 and not more than 1,5 g/cm ³ and a solubility in water of not less than 70 % by weight	0
ex 3823 90 99	Anti-corrosion preparations consisting of salts of dinonylnaphthalene sulphonic acid, either on a carrier of mineral wax or dissolved in an organic solvent	0
ex 3901 20 00	Polyethylene, in one of the forms mentioned in note 6 (b) to Chapter 39, having a density of not less than 0,958 g/cm ³ at 23 °C and containing by weight not more than: — 50 ppm aluminium — 2 ppm calcium — 2 ppm chromium — 2 ppm of iron — 2 ppm of nickel — 2 ppm of titanium — 8 ppm vanadium for the manufacture of chlorosulphonated polyethylene (a)	0
ex 3901 20 00	Polyethylene, in one of the forms mentioned in note 6 (b) to Chapter 39, having a density of not less than 0,945 and not more than 0,985 g/cm ³ for the manufacture of typewriter ribbon or similar ribbon (a)	0
ex 3901 90 00	Ionomer resin consisting of a salt of a copolymer of ethylene and methacrylic acid	0
ex 3901 90 00	Ionomer resin consisting of a salt of a terpolymer of ethylene, isobutyl acrylate and methacrylic acid	0
ex 3904 40 00	Copolymers of vinyl chloride with vinyl acetate and vinyl alcohol, containing by weight not less than 87 % and not more than 92 % of vinyl chloride, not less than 2 % and not more than 9 % of vinyl acetate and not less than 1 % and not more than 8 % of vinyl alcohol, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 3906 90 00	Polymerization products of acrylic acid with small quantities of a polyunsaturated monomer, for use as a stabilizer in emulsions or dispersions with a pH of more than 13 (a)	6
ex 3907 20 90	<i>Alpha</i> -4-Hydroxybutyl- <i>omega</i> -hydroxypoly(oxytetramethylene) with a halogen or metal content each of less than 1 mg/kg and a colour of not more than 20 units on the Hazen scale	0
ex 3907 20 90	Liquid poly(oxypropylene) with 3-(3-[2-(2-mercaptoethoxy)ethoxy]ethy[thio]-propoxycarbonylamino)- <i>p</i> -tolylcarbamoxyloxy as the end group	0
ex 3912 11 00	Non-plasticized cellulose triacetate in the form of flakes, for the manufacture of cellulose triacetate yarn (a)	0
ex 3912 39 90	Hydroxypropylcellulose	0
ex 3919 90 31 ex 3920 62 00 ex 3921 90 19	Reflecting laminated sheeting, metallized, consisting of one sheet of polyester and at least another sheet of polyester or other plastic material and coated on one side with an adhesive, whether or not protected by a release sheet	0
ex 3919 90 31 ex 3920 62 00 ex 3920 63 00 ex 3920 69 00 ex 3921 90 19	Reflecting polyester sheeting in which microspheres are embedded	0
ex 3919 90 39 ex 3920 99 19 ex 3921 90 50	Reflecting polyurethane sheeting	0
ex 3919 90 50	Polyvinyl chloride sheeting, of a thickness of less than 1 mm, coated with an adhesive in which are embedded hollow glass balls having a diameter of not more than 100 micrometres	0
ex 3919 90 50 ex 3920 59 00 ex 3921 90 60	Laminated reflecting film of acrylic polymers and isocyanate cross-linking agents, containing embedded glass microspheres metallized with aluminium, which reflect light back to the source of incident light (retro-reflecting), coated on one side with an adhesive	0
ex 3919 90 50 ex 3920 59 00 ex 3921 90 60	Reflecting sheeting of an acrylic polymer modified by melamine-formaldehyde, containing glass microspheres	0
ex 3919 90 50 ex 3920 59 00 ex 3921 90 60	Reflecting polyacrylic sheeting in which microspheres are embedded	0
ex 3919 90 50 ex 3920 59 00 ex 3921 90 60	Laminated reflecting film of acrylic polymer, one layer of which is embossed with a prismatic pattern which reflects light back to the source of incident light (retro-reflecting), coated on one side with an adhesive	0
ex 3920 10 11	Polyethylene film of a thickness of not less than 20 and not more than 40 micrometres, for the production of photo-resist film used in the manufacture of semiconductors (a)	0
ex 3920 10 11	Laminated plastic sheet or strip, either: — having a width of not less than 190 mm, and consisting of one layer of biaxially orientated polyamide film coated on one side with polyvinylidene chloride and on the other side with a layer of polyethylene film or — having a width of not more than 15 mm, and consisting of one layer of biaxially orientated polyamide film and two layers of polyethylene film	0
ex 3920 42 10	Reflecting polyvinyl chloride sheeting, wholly embossed on one side in a regular pyramidal pattern	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 3920 62 00 ex 3920 63 00 ex 3920 69 00	Reflecting polyester sheeting embossed in a regular pyramidal pattern	0
ex 3920 99 50	Microporous polytetrafluoroethylene film, coated on one side with a polymer permeable to water vapour, not less than 30 cm in width and weighing not more than 50 g/m ²	0
ex 3920 99 50	Microporous polytetrafluoroethylene film of a width of not more than 30 cm and weighing not more than 22,4 g/m ²	0
ex 3920 99 50	Films of a thickness of not more than 1 mm, entirely of polyvinyl alcohol, containing not more than 2 % by weight of unhydrolyzed acetate groups expressed as vinyl acetate and not less than 5 % and not more than 15 % by weight of glycerol as a plasticizer, not soluble in water at temperatures below 85 °C	0
ex 3920 99 50	Polyvinyl alcohol film coated on both sides having a total thickness of less than 1 mm and with an extension at break (longitudinal or transversal) of not less than 65 %	0
ex 3920 99 50	Polyvinyl alcohol film containing not less than 99 % by weight of polyvinyl alcohol, uncoated, with a thickness of not more than 1 mm	0
ex 3920 99 50	Film of a mixture of polyvinylidene fluoride and of an acrylic polymer having a thickness not less than 40 micrometres and not more than 60 micrometres	0
4502 00 00	Natural cork, debarked or roughly squared, or in rectangular (including square) blocks, plates, sheets or strip (including sharp-edged blanks for corks or stoppers)	4
ex 7011 20 00	Face plates made wholly of glass, having a diagonal dimension of not more than 61 cm and a raised edge intended for use in the manufacture of monochrome cathode ray tubes (a)	0
ex 7011 20 00	Glass cones with a shaped edge and having a diagonal dimension of not more than 61 cm intended for use in the manufacture of monochrome cathode ray tubes (a)	0
ex 8401 30 00	Nuclear fuel cartridges, consisting of mixed oxides of gadolinium and uranium enriched in U 235 contained in a 'barrier'-type metal cladding of zirconium alloy (Zircaloy)	0
ex 8419 89 90	Immersion tube (coils) bundles consisting of an assembly of plastic tubes terminating at each end in a honeycomb structure (end fitting) surrounded by a pipe connector	0
ex 8471 99 90	Optical reader for reading dot-matrix printing characters and converting them into electrical signals, comprising a read head containing an optical detector, an amplifier, a focusing lens and two lamps, linked by one or two flat cables to a central module of which the dimensions do not exceed 200 × 220 mm, comprising a printed circuit board on which are mounted a microprocessor, an image recognition circuit and an analog/digital converter	0
ex 8473 10 00	Integrated memory unit for electronic typewriters, comprising a printed circuit with two or four static read-write random-access memories each with 8 K × 8 bit capacity, electronic control components and memory back-up-batteries, containing in a cartridge fitted with connectors, of external dimensions not exceeding 11 × 40 × 90 mm, and bearing an identification mark consisting of or including the following combination of letters: MEMOCART or other identification markings relating to integrated memory units complying with the abovementioned description	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Combined Nomenclature code	Description	Rate of autonomous duty (%)									
ex 8473 10 00 ex 8473 30 00	Dot-matrix displays consisting of a layer of liquid crystal between two glass sheets or plates with a maximum of 15 360 dots (arranged in 64 lines and 240 columns), complete with an interface electronics board in C-MOS technology whose exterior dimensions do not exceed 186 × 75 × 15 mm, with not more than 544 contact areas	0									
ex 8473 10 00 ex 8473 30 00	Dot-matrix displays, whose external dimensions do not exceed 15 × 90 × 280 mm excluding cables and connectors consisting of a layer of liquid crystals between two glass sheets or plates with 30 720 dots (arranged in 64 lines and 480 columns), mounted on a printed-circuit board comprising electronic components providing drive functions, with or without cable and connector	0									
ex 8473 10 00 ex 8473 30 00	Dot-matrix displays, whose external dimensions do not exceed 15 × 62 × 276 mm excluding cables and connectors consisting of a layer of liquid crystals between two glass sheets or plates with 32 768 dots (arranged in 64 lines and 512 columns), mounted on a printed-circuit board comprising electronic components providing drive and control functions, with or without cable and connector	0									
ex 8473 10 00 ex 8473 30 00	Displays unit with maximum dimensions, excluding cables and connectors, of 15 × 115 × 290 mm, comprising two layers or sheets of glass enclosing 128 000 liquid-crystal dots (arranged in 200 rows and 640 columns), fixed to a printed circuit fitted with electronic components performing control functions, with or without cables and connectors	0									
ex 8473 30 00	Ferrite magnetic heads of Winchester technology for disc file peripherals, as well as carrying arms equipped with such magnetic heads, capable of recording to a density of not less than 10 tracks per millimetre	0									
ex 8473 30 00	Magnetic bubble memories with a storage capacity of not more than four megabits contained in a housing the exterior dimensions of which do not exceed 43 × 44 mm, with not more than 42 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: <table><tr><td>BDL 0133</td><td>MBM 2011</td><td>FBM 64 DA</td></tr><tr><td>BDL 0134</td><td>MBM 2256</td><td>7110</td></tr><tr><td>BDN 0151</td><td>FBM 54 DB</td><td>7114-1</td></tr></table> or — other identification markings relating to magnetic bubble memories complying with the abovementioned description	BDL 0133	MBM 2011	FBM 64 DA	BDL 0134	MBM 2256	7110	BDN 0151	FBM 54 DB	7114-1	0
BDL 0133	MBM 2011	FBM 64 DA									
BDL 0134	MBM 2256	7110									
BDN 0151	FBM 54 DB	7114-1									
ex 8473 30 00	Component forming the arithmetic/logic element of a central processing unit, comprising not more than nine printed circuit boards, the dimensions of which do not exceed 290 × 310 mm on each of which are mounted not more than 121 ECL gate arrays or ECL random access memories (ECL-RAMs) and combinations thereof contained in a framework the dimensions of which do not exceed 611 × 501 × 596 mm which serves as a housing and interconnector for the printed circuit boards, which bear: — an identification marking consisting of or including one of the following combinations of figures and letters: <table><tr><td>CO1B 2675 E 500</td></tr><tr><td>CO1B 2675 H 500</td></tr><tr><td>CO1B 2675 H 501</td></tr><tr><td>CO1B 2675 H 502</td></tr><tr><td>CO1B 2675 H 503</td></tr><tr><td>CO1B 2675 H 504</td></tr></table> or — other identification markings relating to components complying with the abovementioned description	CO1B 2675 E 500	CO1B 2675 H 500	CO1B 2675 H 501	CO1B 2675 H 502	CO1B 2675 H 503	CO1B 2675 H 504	0			
CO1B 2675 E 500											
CO1B 2675 H 500											
CO1B 2675 H 501											
CO1B 2675 H 502											
CO1B 2675 H 503											
CO1B 2675 H 504											

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8473 30 00	Assemblies for automatic data-processing machines, consisting of two stacked substrate layers with one or two static random access memories of bipolar technology (bipolar S-RAMs) in the form of monolithic integrated circuits, each with a storage capacity of 1 K bit and with a maximum storage capacity of 4 K bits, contained in a housing the exterior dimensions of which do not exceed 13 × 13 mm, with not more than 23 connecting pins and bearing: — an identification marking, either consisting of or including one of the following combinations of figures: 770965 4599497 7379442 or — other identification markings relating to assemblies complying with the abovementioned description	0
ex 8501 10 99	DC electric motor, brushless, with a maximum torque of 0,20 N m, with an incorporated electronic control plate, outside rotor with circular cross-section and maximum diameter of 95 mm, aluminium precision-made hub with inside diameter of 28,6 mm, speed of 300 or 360 rpm, supply voltage of 12 V ± 10 %	0
ex 8501 10 99	DC electric motor, brushless, with a maximum torque of not more than 0,20 N m, with or without an outside rotor, with a coupling flange of a diameter of 75 mm, a spindle of a diameter of 25 mm, rated speed of 3 600 rpm, supply voltage of 12 V ± 10 % with cables and connectors	0
ex 8501 10 99	DC electric motor, brushless, with a maximum torque of 0,20 N m, with outside rotor of a maximum diameter of 55 mm, coupling flange of a diameter of 77 mm and precision-made chuck of a diameter of 44 mm, four-phase winding, rated speed of 3 600 rpm, supply voltage of 12 V ± 10 % and fitted with wires and connectors	0
ex 8501 10 99	DC electric motor, brushless, with a torque of not more than 0,2 N m, with a coupling flange of a diameter of 74 mm, a spindle of a diameter of 40 mm, rated speed of 3 600 rpm, supply voltage of 12 V ± 10 %, with cables and connectors	0
ex 8501 10 99	Two or three-phase DC electric motor, brushless, with a maximum torque of 0,20 N m, with an external rotor of 62 mm maximum diameter and incorporating an electronic control panel, maximum dimensions 85 × 85 × 20 mm, including the shaft, nominal operating voltage of 12 V ± 10 % and a rate of rotation of 300 rpm	0
ex 8501 10 99	DC electric motor, brushless, with a maximum torque of 0,05 N m an outside rotor of a maximum diameter of 92 mm, aluminium precision-made hub with an outside diameter of 40 mm, 2-phase winding, rated speed of 3 600 rpm, supply voltage of 12 V ± 10 %	0
ex 8501 10 99	Hybrid stepping motor with an angle of step 0,9°, 400 steps per revolution, 2- or 4-phase rotation sequence and bipolar windings, comprising a rotor, a laminated stator enclosed between two square section flanges with sides not more than 40 mm wide and fitted with biterminate shaft, wires and connectors	0
ex 8501 10 99	Hybrid stepping motor with an angle of step of 0,9°. 400 steps per revolution, 2-phase rotation sequence and bipolar windings, comprising a rotor and a stator encapsulated in a cylindrical housing with a maximum diameter of 47 mm and maximum thickness of 14 mm, fitted with a single shaft output and cables with connectors	0
ex 8501 10 99	Hybrid stepping motor with an angle of step of 0,9°, 400 steps per revolution and 2-phase rotation sequence, and bipolar windings, comprising a rotor, a laminated stator enclosed between two square section flanges with sides not exceeding 40 mm, an integral two or three-phase tachometer enclosed in a cap with a maximum diameter of 35 mm, and separate cables and connectors for the motor and tachometer outputs, with maximum dimensions of 40 × 40 × 62 mm, including the shaft	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8501 10 99	Hybrid stepping motor with an angle of step of $0,9^\circ$, 400 steps per revolution, 2-phase rotation sequence with bipolar winding, comprising a rotor, a laminated stator enclosed between two flanges, one of square section with a side of 40 mm maximum, the other front face having a shaped profile with two projections with fixing slots, an integral 2- or 3-phase tachometer enclosed in a cover of diameter of 35 mm maximum, separate cables and connectors for the motor and tachometer outputs, with overall dimensions not exceeding $40 \times 40 \times 62$ mm, including the shaft but excluding the projections of the front flange	0
ex 8501 10 99	Bipolar stepping motors with an angle of step of $1,8^\circ$, 200 steps per revolution, 2-phase rotation sequence with bipolar-type windings, maximum external dimensions of $39 \times 39 \times 20$ or 25 mm excluding shaft, fixing screws and boss, with a minimum torque of 0,25 N m for the version with a maximum height of 20 mm and 0,35 N m for the version with a maximum height of 25 mm	0
ex 8501 10 99	Direct-current bipolar stepping motor with a single stator, an output of not more than 37,5 W, a rotary angle/step of 180° , two steps per rotation, a 2-phase rotation cycle with single-pole winding, an output torque of not less than $0,1 \times 10^{-6}$ Nm and not more than $0,1 \times 10^{-4}$ Nm and a supply voltage of not more than 3 V	0
ex 8504 40 99	Static converter consisting of a combination of seven diodes in cascade, for output voltages of not less than 40 kV DC with a load current of not less than 3 mA	0
ex 8506 19 10	Unit consisting of not more than 2 lithium batteries embedded in a socket for integrated circuits (battery-buffered socket), with not more than 28 connecting pins and incorporating a control circuit	0
ex 8517 90 91	Assembly for telephonic apparatus consisting of a microphone, protecting circuit and four-way connecting socket, mounted on a printed circuit, with dimensions not exceeding 22×40 mm	0
ex 8517 90 91 ex 8542 20 00	Opto-electronic receiving device (PINFET receiver) with a wavelength range 1 300—1 600 nanometres, and a speed of not less than 678 megabits per second, in the form of a hybrid integrated circuit, contained in a housing the exterior dimensions of which do not exceed $25 \times 13 \times 13$ mm, with not more than 16 connecting pins, with an attached optical fibre lead (pig-tail), and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 416/7/970 30 QDFI-XXXX-001 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8523 20 10	Rigid magnetic disks, prelubricated, oxide type, with a high coercivity (800 Oe), an outer diameter of 95 mm, an inner diameter of 25 mm and a thickness of 1,27 mm	0
ex 8529 10 70	Ceramic filter package comprising two ceramic filters with 3 connecting pins and one ceramic resonator with two connecting pins, each having a frequency of $10,7 \text{ MHz} \pm 30 \text{ kHz}$, contained in a housing the exterior dimensions of which do not exceed $10 \times 10 \times 5$ mm	0
ex 8532 29 00	Gold capacitor with a rated capacitance of 100 mF, an operating voltage of 5,5 V and a leakage current of not more than 100 μA , contained in a cylindrical housing of a height of less than 8 mm and a diameter of not more than 14 mm	0
ex 8532 30 10	Variable plate capacitor with plastic dielectric, with a capacitance of not more than $2 \times 355 \text{ pF}$ for the AM section and not more than $2 \times 20 \text{ pF}$ for the FM section, contained in a housing the exterior dimensions of which do not exceed 21×24 mm	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)																																																																								
ex 8532 30 90	Adjustable capacitor, in the form of a circular plate with a diameter of not more than 2,5 mm, fitted with a screw head in its centre and two connecting tags, of a thickness not exceeding 3 mm and a capacity of from 5 to 30 picofarads, for the manufacture of products falling within Chapter 91 (a)	0																																																																								
ex 8533 29 00	Device consisting of fixed resistors with a positive temperature coefficient having a nominal resistance in DC of 19,6 Ohm at 20 °C, an insulation resistance of more than 1 MOhm, for the protection of telephone exchanges against prolonged increases in voltage of not more than 1 000 V, contained in a housing the exterior dimensions of which do not exceed 48 × 19 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures: 20793 or — other identification markings relating to fixed resistors complying with the abovementioned description	0																																																																								
ex 8534 00 11 ex 8534 00 19	Single-face printed circuit, of dimensions not exceeding 30 × 30 mm, for the manufacture of products falling within Chapter 91 (a)	0																																																																								
ex 8536 41 10 ex 8536 41 90 ex 8536 49 00	Thermal relays contained in a hermetically sealed glass cartridge not exceeding 35 mm in length excluding wires, with a maximum leakage rate of 10 ⁻⁶ cm ³ He/sec at one bar in the temperature range 0 to 160 °C, to be incorporated into compressors for refrigerating equipment (a)	0																																																																								
ex 8536 50 00	Telephone line switch assembly consisting of one moveable and one stationary bifurcated spring with contact area of diffused gold on palladium silver inlay, mounted in polycarbonate material, and of dimensions not exceeding 40 × 20 × 13 mm	0																																																																								
ex 8540 30 00	Colour cathode-ray tubes with a dot mask equipped with electron guns placed side by side (in-line-technology) with a distance of less than 0,45 mm between colour dots and with at least one of the following characteristics: — a diagonal screen measurement of not less than 42 cm or less than 25 cm, a diagonal angle of deflection of not more than 90° and convergence errors exceeding 0,8 mm at the corners, — a built-in system, inseparably linked to the tube, for the absorption of vibration (so called potting system), — without internal magnetic screen, — a phosphor layer calibrated with the following nominal coordinates for the colour dots: <table><tr><td></td><td>red</td><td>green</td><td>blue</td></tr><tr><td>X</td><td>0,64</td><td>0,29</td><td>0,15</td></tr><tr><td>Y</td><td>0,33</td><td>0,60</td><td>0,06</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,64</td><td>0,31</td><td>0,155</td></tr><tr><td>Y</td><td>0,34</td><td>0,595</td><td>0,07</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,62</td><td>0,21</td><td>0,15</td></tr><tr><td>Y</td><td>0,33</td><td>0,615</td><td>0,06</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,610</td><td>0,307</td><td>0,150</td></tr><tr><td>Y</td><td>0,350</td><td>0,595</td><td>0,065</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,61</td><td>0,205</td><td>0,15</td></tr><tr><td>Y</td><td>0,35</td><td>0,680</td><td>0,065</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,62</td><td>0,29</td><td>0,15</td></tr><tr><td>Y</td><td>0,35</td><td>0,60</td><td>0,065</td></tr></table>		red	green	blue	X	0,64	0,29	0,15	Y	0,33	0,60	0,06	or				X	0,64	0,31	0,155	Y	0,34	0,595	0,07	or				X	0,62	0,21	0,15	Y	0,33	0,615	0,06	or				X	0,610	0,307	0,150	Y	0,350	0,595	0,065	or				X	0,61	0,205	0,15	Y	0,35	0,680	0,065	or				X	0,62	0,29	0,15	Y	0,35	0,60	0,065	0
	red	green	blue																																																																							
X	0,64	0,29	0,15																																																																							
Y	0,33	0,60	0,06																																																																							
or																																																																										
X	0,64	0,31	0,155																																																																							
Y	0,34	0,595	0,07																																																																							
or																																																																										
X	0,62	0,21	0,15																																																																							
Y	0,33	0,615	0,06																																																																							
or																																																																										
X	0,610	0,307	0,150																																																																							
Y	0,350	0,595	0,065																																																																							
or																																																																										
X	0,61	0,205	0,15																																																																							
Y	0,35	0,680	0,065																																																																							
or																																																																										
X	0,62	0,29	0,15																																																																							
Y	0,35	0,60	0,065																																																																							

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Combined Nomenclature code	Description	Rate of autonomous duty (%)																																																												
ex 8540 30 00	Colour cathode ray tubes with a dot mask equipped with electron guns in a triangular fashion (delta technology) with a distance of less than 0,4 mm between colour dots, with at least one of the following characteristics: — a diagonal screen measurement of at least 66 cm — equipped with a phosphor layer calibrated with the following nominal coordinates for the colour dots: <table><tr><td></td><td><i>red</i></td><td><i>green</i></td><td><i>blue</i></td></tr><tr><td>X</td><td>0,64</td><td>0,29</td><td>0,15</td></tr><tr><td>Y</td><td>0,33</td><td>0,60</td><td>0,06</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,64</td><td>0,31</td><td>0,155</td></tr><tr><td>Y</td><td>0,34</td><td>0,595</td><td>0,07</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,610</td><td>0,307</td><td>0,150</td></tr><tr><td>Y</td><td>0,350</td><td>0,595</td><td>0,065</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,61</td><td>0,205</td><td>0,15</td></tr><tr><td>Y</td><td>0,35</td><td>0,680</td><td>0,065</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,62</td><td>0,29</td><td>0,15</td></tr><tr><td>Y</td><td>0,35</td><td>0,60</td><td>0,065</td></tr></table>		<i>red</i>	<i>green</i>	<i>blue</i>	X	0,64	0,29	0,15	Y	0,33	0,60	0,06	or				X	0,64	0,31	0,155	Y	0,34	0,595	0,07	or				X	0,610	0,307	0,150	Y	0,350	0,595	0,065	or				X	0,61	0,205	0,15	Y	0,35	0,680	0,065	or				X	0,62	0,29	0,15	Y	0,35	0,60	0,065	0
	<i>red</i>	<i>green</i>	<i>blue</i>																																																											
X	0,64	0,29	0,15																																																											
Y	0,33	0,60	0,06																																																											
or																																																														
X	0,64	0,31	0,155																																																											
Y	0,34	0,595	0,07																																																											
or																																																														
X	0,610	0,307	0,150																																																											
Y	0,350	0,595	0,065																																																											
or																																																														
X	0,61	0,205	0,15																																																											
Y	0,35	0,680	0,065																																																											
or																																																														
X	0,62	0,29	0,15																																																											
Y	0,35	0,60	0,065																																																											
ex 8540 30 00	Flat screen monochrome cathode ray tubes having a diagonal screen measurement of not less than 142 mm and not more than 145 mm, a luminescence of between 300 and 400 lumen, a resolution of between 0,06 and 0,1 mm, phosphor types P 1 or P 55 or P 56, an anode voltage of more than 34 kV, a focus voltage of more than 7 kV and a cathode current of not less than 3 mA	0																																																												
ex 8540 30 00	Cathode-ray tubes with a memory (direct view storage tubes) for the reproduction of alphanumeric and analogue data, equipped with a scanning device, for reading the images	0																																																												
ex 8540 89 11	Displays in the form of a tube consisting of a glass housing mounted on a board the dimensions of which do not exceed 350 × 300 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallized base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons	0																																																												
ex 8541 10 91	Silicon power rectifier diodes of planar technology, with a recovery time of less than 100 nanoseconds, a maximum recurring reverse voltage of 200 V, and average conducting-state, current of 2,5 A, contained in a housing the exterior dimensions of which do not exceed 11 × 17 mm	0																																																												
ex 8541 10 99	Germanium-gold diodes with forward voltage not exceeding 1 V at 5 mA	0																																																												
ex 8541 29 90	Transistor with a power of not less than 150 W at a voltage of not less than 160 V and with a cut-off frequency of not less than 20 MHz, contained in a housing the exterior dimensions of which do not exceed 37 × 22 mm, with not more than 3 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: <table><tr><td>2 SA 1170</td><td>2 SC 2774</td></tr><tr><td>2 SA 1215</td><td>2 SC 2921</td></tr><tr><td>2 SA 1494</td><td>2 SC 3858</td></tr></table> or — other identification markings relating to power transistors complying with the abovementioned description	2 SA 1170	2 SC 2774	2 SA 1215	2 SC 2921	2 SA 1494	2 SC 3858	0																																																						
2 SA 1170	2 SC 2774																																																													
2 SA 1215	2 SC 2921																																																													
2 SA 1494	2 SC 3858																																																													

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8541 40 10	Light emitting diode (LED) made from a gallium-based semiconductor compound, mounted in a rectangular housing the exterior dimensions of which do not exceed $4 \times 20 \times 21$ mm, with two connecting pins, and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: LT 9305 SLF 209 LT 9306 SLF 909 or — other identification markings relating to LEDs, complying with the abovementioned description, for use in the manufacture of radio broadcast receivers and sound recorders or reproducers (a)	0
ex 8541 40 10	Assembly consisting of not more than 10 light-emitting diodes (LEDs) made from a gallium-based semiconductor compound, mounted in a rectangular housing the exterior dimensions of which do not exceed $68 \times 25 \times 4$ mm, with not more than 20 connecting pins, and bearing: — an identification marking consisting of or including the following combination of figures and letters: LT 9355 or — other identification markings relating to assemblies complying with the abovementioned description, for use in the manufacture of radio broadcast receivers and sound recorders or reproducers (a)	0
ex 8541 40 10	Laser diode with one photodiode, emitting light of a nominal wavelength of 780 nm, contained in a housing having a diameter of not more than 10 mm and a height of not more than 7 mm, with 3 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: LT 022 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8541 40 10 ex 8542 20 00	Digital display of a size not exceeding 25×35 mm, consisting of a printed circuit board on which are mounted, under a plastic cover, up to 22 light-emitting diodes manufactured from gallium-based semiconductor compounds. Each display consists of a single character with or without a plus or minus sign and/or one or two dots	7
ex 8541 40 10 ex 8542 20 00	Digital displays, consisting of a printed circuit board of a size not exceeding 35×90 mm with a single line of characters, not less than three in number, comprising light-emitting diodes made from gallium-based semiconductor compounds mounted thereon. Each character is composed of up to eight segments with or without a decimal point and the line of characters has a protective cover of plastic	0
ex 8541 40 93	Opto-electronic circuit consisting of one or more light-emitting diodes and one or more photo diodes with amplifier, contained in a plastic housing with not more than 16 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HC PL 2400 HC PL 5700 HC PL 5730 or — other identification markings relating to opto-electronic circuits complying with the abovementioned description	0
ex 8541 60 00	Quartz crystal oscillating at a frequency of 32 768 Hz, contained in a cylindrical housing of a length not exceeding 8,2 mm and a diameter not exceeding 3,2 mm, for the manufacture of products falling within Chapter 91 (a)	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Combined Nomenclature code	Description	Rate of autonomous duty (%)												
ex 8541 60 00	Polarized ceramic piezo-electric crystals oscillating in a frequency range of not less than 500 and not more than 12 500 kHz, contained in a housing the exterior dimensions of which do not exceed 14 × 15 mm, with not more than 3 connecting pins	0												
ex 8542 11 30	Electrically erasable, programmable read-only memories (so-called E ² PROMs), in the form of an unmounted monolithic integrated circuit (chip) with a storage capacity of 16 Kbits, used in the manufacture of microwave systems for the identification of persons and objects (a)	0												
ex 8542 11 71	Static random access memories of C-MOS technology (C-MOS S-RAMs) in the form of a monolithic integrated circuit with a storage capacity of 16 × 4 bits, an access time not exceeding 35 ns, contained in a housing the exterior dimensions of which do not exceed 9 × 21 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including one of the following combination of figures and letters: CY7C189 CY7C190 CY74S189 CY54S189 CY27S03 CY27S07 or — other identification markings relating to C-MOS S-RAMs complying with the abovementioned description	0												
ex 8542 11 71	Static random access memories of C-MOS technology (C-MOS S-RAMs) in the form of a monolithic integrated circuit with a storage capacity of 256 × 4 bits and an access time not exceeding 60 ns, contained in a housing the exterior dimensions of which do not exceed 12 × 29 mm, with not more than 22 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CY7C122 CY 93422 CY93L422 or — other identification markings relating to C-MOS S-RAMs complying with the abovementioned description	0												
ex 8542 11 71	Static, random-access memory of C-MOS technology (C-MOS S-RAM) with a storage capacity of 2 K × 8 bits and with a nominal standby power of 0,005 milliwatts at 25 °C in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters <table> <tr> <td>TC5516APL-2</td><td>TC5517CPL-15</td><td>TC5517BPL-20</td></tr> <tr> <td>TC5516AFL-2</td><td>TC5517CPL-20</td><td>TC5517BPL-25</td></tr> <tr> <td>TC5516APL</td><td>TC5517CFL-15</td><td>TC5517BFL-20</td></tr> <tr> <td>TC65516AFL</td><td>TC5517CFL-20</td><td>TC65517BFL-25</td></tr> </table> or — other identification markings relating to C-MOS S-RAMs complying with the abovementioned description	TC5516APL-2	TC5517CPL-15	TC5517BPL-20	TC5516AFL-2	TC5517CPL-20	TC5517BPL-25	TC5516APL	TC5517CFL-15	TC5517BFL-20	TC65516AFL	TC5517CFL-20	TC65517BFL-25	7
TC5516APL-2	TC5517CPL-15	TC5517BPL-20												
TC5516AFL-2	TC5517CPL-20	TC5517BPL-25												
TC5516APL	TC5517CFL-15	TC5517BFL-20												
TC65516AFL	TC5517CFL-20	TC65517BFL-25												
ex 8542 11 71	Non-volatile memory in the form of a monolithic integrated circuit, consisting of a C-MOS S-RAM, with a capacity of 16 Kbits and internal power supply, contained in a housing the exterior dimensions of which do not exceed 19 × 36 mm, with not more than 28 connecting pins and bearing:													

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Combined Nomenclature code	Description	Rate of autonomous duty (%)																																																
ex 8542 11 71 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures and letters: DS 1220 Y MK 48 Z 02 (B) or — other identification markings relating to non-volatile memories complying with the abovementioned description:	7																																																
ex 8542 11 71	Static, random access memory of C-MOS technology (C-MOS S-RAM) with a storage capacity of 32 K bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combinations of figures and letters: TC 5532 or — other identifying markings relating to C-MOS S-RAMs complying with the abovementioned description:	0																																																
ex 8542 11 71	Static, random-access memories of C-MOS technology (C-MOS S-RAMs), with a storage capacity of 8 K × 8 bits with an access time of not less than 80 nanoseconds, in the form of a monolithic integrated circuit, contained in a plastic housing the exterior dimensions of which do not exceed 18 × 39 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combination of figures and letters: <table><tr><td>TC5564PL-15</td><td>HM6264P-10</td><td>MB8464A-10</td><td>PD4464C-15</td></tr><tr><td>TC5564PL-20</td><td>HM6264P-12</td><td>MB8464A-10L</td><td>PD4464C-20</td></tr><tr><td>TC5565PL-12</td><td>HM6264P-15</td><td>MB8464A-10LL</td><td>PD4464G-15</td></tr><tr><td>TC5565PL-15</td><td>HM6264LP-10</td><td>MB8464A-15</td><td>PD4464G-20</td></tr><tr><td>TC5565FL-12</td><td>HM6264LP-12</td><td>MB8464A-15L</td><td></td></tr><tr><td>TC5565FL-15</td><td>HM6264LP-15</td><td>MB8464A-15LL</td><td></td></tr><tr><td>TC5565PL-12L</td><td></td><td>MB8464A-12</td><td></td></tr><tr><td>TC5565PL-15L</td><td></td><td>MB8464-12L</td><td></td></tr><tr><td>TC5565FL-12L</td><td></td><td>MB8464-12LL</td><td></td></tr><tr><td>TC5565FL-15L</td><td></td><td>MB8464-15</td><td></td></tr><tr><td></td><td></td><td>MB8464-15L</td><td></td></tr><tr><td></td><td></td><td>MB8464-15LL</td><td></td></tr></table> or — other identification markings relating to C-MOS S-RAMs complying with the abovementioned description:	TC5564PL-15	HM6264P-10	MB8464A-10	PD4464C-15	TC5564PL-20	HM6264P-12	MB8464A-10L	PD4464C-20	TC5565PL-12	HM6264P-15	MB8464A-10LL	PD4464G-15	TC5565PL-15	HM6264LP-10	MB8464A-15	PD4464G-20	TC5565FL-12	HM6264LP-12	MB8464A-15L		TC5565FL-15	HM6264LP-15	MB8464A-15LL		TC5565PL-12L		MB8464A-12		TC5565PL-15L		MB8464-12L		TC5565FL-12L		MB8464-12LL		TC5565FL-15L		MB8464-15				MB8464-15L				MB8464-15LL		0
TC5564PL-15	HM6264P-10	MB8464A-10	PD4464C-15																																															
TC5564PL-20	HM6264P-12	MB8464A-10L	PD4464C-20																																															
TC5565PL-12	HM6264P-15	MB8464A-10LL	PD4464G-15																																															
TC5565PL-15	HM6264LP-10	MB8464A-15	PD4464G-20																																															
TC5565FL-12	HM6264LP-12	MB8464A-15L																																																
TC5565FL-15	HM6264LP-15	MB8464A-15LL																																																
TC5565PL-12L		MB8464A-12																																																
TC5565PL-15L		MB8464-12L																																																
TC5565FL-12L		MB8464-12LL																																																
TC5565FL-15L		MB8464-15																																																
		MB8464-15L																																																
		MB8464-15LL																																																
ex 8542 11 71	Non-volatile memory consisting of a static read/write random access memory of C-MOS technology (C-MOS S-RAM), with a storage capacity of 64 Kbits and an internal energy source, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 20 × 42 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: DS 1225 Y or — an identification markings relating to non-volatile memories complying with the abovementioned description:	0																																																
ex 8542 11 71	Static random access memories (S-RAMs) of C-MOS technology, with a storage capacity of 256 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 39 × 17 mm, with not more than 28 connecting pins and bearing:																																																	

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 71 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures and letters: HM 62256, PD 43256 C, TC 55257 P or — other identification markings relating to S-RAMs complying with the abovementioned description	0
ex 8542 11 71	Non-volatile memory in the form of a monolithic integrated circuit, consisting of a static C-MOS random access memory, with a storage capacity of 256 K bits and built-in energy source, contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: DS 1230 or — other identification markings relating to non-volatile memories complying with the above-mentioned description	0
ex 8542 11 71	Static random-access memories of N-MOS (including H-MOS) technology (N-MOS S-RAMs) with a storage capacity of 256 × 4 bits with access time not exceeding 25 nano/seconds in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 9122 – 25 91 L 22 – 25 or — other identification markings relating to C-MOS S-RAMs complying with the abovementioned description	0
ex 8542 11 71	Static random-access memories of N-MOS (including H-MOS) technology (N-MOS S-RAMs) with a storage capacity of 8 K bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 4008 8112 4118 8114 4801 8185 8104 PD 421 8108 or — other identification markings relating to N-MOS S-RAMs complying with the abovementioned description	0
ex 8542 11 71	Static read/write random-access memories N-MOS (including H-MOS) technology (N/H-MOS RAMs, static), with a storage capacity of 72 K bits, in the form of a monolithic integrated circuit, contained in a housing whose dimensions do not exceed 10 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: TMM 2089 or — other identification markings relating to static, read/write memories complying with the abovementioned description	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 71	Static random-access memories of bipolar technology (bipolar S-RAMs) in the form of a monolithic integrated circuit and with a storage capacity of 64×9 bits, contained in a housing the exterior dimensions of which do not exceed 16×40 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 82 S 09 MBM 93419 - or — other identification markings relating to bipolar S-RAMs complying with the abovementioned description	0
ex 8542 11 71	Static random access memories of bipolar technology (bipolar S-RAMs) in the form of a monolithic integrated circuit, consisting of a substrate layer on which are mounted either 1 or 2 chips each having a storage capacity of 1 K bit, contained in a housing the exterior dimensions of which do not exceed 13×13 mm, with not more than 23 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 770639 770823 5120360 7379769 - or — other identification markings relating to bipolar S-RAMs complying with the abovementioned description	0
ex 8542 11 71	Static memories consisting of two stacked substrate layers with one or two static random access memories of bipolar technology (bipolar S-RAMs), in the form of monolithic integrated circuits, each with a storage capacity of 1 K bit and with a maximum storage capacity of 4 K bits, contained in a housing the exterior dimensions of which do not exceed 13×13 mm, with not more than 23 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 770965 4599497 7379442 - or — other identification markings relating to static memories complying with the abovementioned description	0
ex 8542 11 71	Static, random-access memories of TTL technology (TTL S-RAMs) with a storage capacity of 1 K bit and an access time not exceeding 45 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16×30 mm, with not more than 22 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 93422 93425 - or — other identification markings relating to TTL S-RAMs complying with the abovementioned description	0
ex 8542 11 71	Dynamic random access memories of C-MOS technology (C-MOS D-RAMs) with a storage capacity of 256 K bits in the form of a monolithic integrated circuit, contained in a housing whose external dimensions do not exceed 17×34 mm, with not more than 18 connecting pins and bearing:	

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 71 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures and letters: P 51 C 256 P 51 C 259 or — other identification markings relating to C-MOS D-RAMs complying with the abovementioned description	0
ex 8542 11 71	Dynamic, random-access read/write memory of N-MOS (including H-MOS) technology, (N-MOS D-RAMs) with a storage capacity of 64 K × 4 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 34 mm, with not more than 20 connecting pins arranged in two parallel lines (dual-in-line package) and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HM 50464 MSM 4464 MB 81464 PD 41254 PD 41464 TMM 41464 TMS 4464 or — other identification markings relating to N-MOS D-RAMs complying with the abovementioned description	10
ex 8542 11 71	Dual port dynamic random access memory (D-RAM) of N-MOS (including H-MOS) technology, with data registers and a serial read output control, with a storage capacity of 256 K bits in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 13 × 39 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: MB 81461 PD 41264 or — other identification markings relating to D-RAMs complying with the abovementioned description	0
ex 8542 11 71	Dynamic random access memories (D-RAMs), of N-MOS (including H-MOS) technology with a storage capacity of 256 K bits and access times not exceeding 150 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 12 × 22 mm, with not more than 20 connecting pins with zig-zag in-line package and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HM 50256 ZP MB 81256 P PD 41256 V or — other identification markings relating to components complying with the abovementioned description	10
ex 8542 11 71	Random access memories of ECL technology (ECL-RAMs) with a storage capacity of 256 × 4 bits, and access time not exceeding 8 ns in the form of a monolithic integrated circuit, contained in a housing the dimensions of which do not exceed 11 × 32 mm, with not more than 24 connecting pins and bearing:	

Combined Nomenclature code	Description	Rate of autonomous duty (%)																
ex 8542 11 71 (cont'd)	— an identification marking consisting of or including the following combination of figures: 10422 or — other identification markings relating to ECL-RAMs complying with the abovementioned description	0																
ex 8542 11 71	Random access memories of ECL technology (ECL-RAMs) with a storage capacity of 4 K bits and an access time not exceeding 50 ns in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 11 × 32 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 10470 10474 or — other identification markings relating to ECL-RAMs complying with the abovementioned description	0																
ex 8542 11 71	Random access memories of ECL technology (ECL-RAMs) with a storage capacity of 16 K bits and an access time not exceeding 15 ns in the form of a monolithic integrated circuit, contained in a housing the dimensions of with do not exceed 18 × 37 mm, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures: 10480 10484 100484 or — other identification markings relating to ECL-RAMs complying with the abovementioned description	0																
ex 8542 11 71	Dynamic read/write random access memories manufactured in N-MOS (including H-MOS) technology (D-RAMs), in the form of a monolithic integrated circuit, consisting of a substrate layer with not less than two and not more than eight chips having a storage capacity of 128,192 or 256 K bits and a storage capacity of not less than 256 K bits and not more than two megabits, contained in a housing whose dimensions do not exceed 30 × 30 mm, with not more than 57 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: <table><tr><td>6025841</td><td>6031587</td><td>6870392</td><td>7379172</td></tr><tr><td>6025843</td><td>6031591</td><td>6870393</td><td>7379174</td></tr><tr><td>6025856</td><td></td><td>6870395</td><td>7379176</td></tr><tr><td>6025858</td><td></td><td></td><td>7379181</td></tr></table> or — other identification markings relating to dynamic read/write memories of the type described above	6025841	6031587	6870392	7379172	6025843	6031591	6870393	7379174	6025856		6870395	7379176	6025858			7379181	0
6025841	6031587	6870392	7379172															
6025843	6031591	6870393	7379174															
6025856		6870395	7379176															
6025858			7379181															
ex 8542 11 71	Read-only memories (ROMs), in the form of a monolithic integrated circuit, with a storage capacity of 16 K × 8 bits, with read-register and serial output control, contained in a housing the exterior dimensions of which do not exceed 50 × 16 mm, with not more than 40 connecting pins and bearing:																	

Combined Nomenclature code	Description	Rate of autonomous duty (%)																																																												
ex 8542 11 71 (cont'd)	— an identification marking consisting of one of the following combinations of figures or including one of those combinations: from 62000 to 62999 or — other identification markings relating to ROMs complying with the abovementioned description	0																																																												
ex 8542 11 71	Read-only memory in C-MOS technology (C-MOS ROM) with a storage capacity of 256 K bits and a standby current of not more than 0,03 mA, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 17 × 50 mm, with not more than 54 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HN 61256 HN 613256 MB 83256 or — other identification markings relating to C-MOS ROMs complying with the abovementioned description	7																																																												
ex 8542 11 71	Read-only memory of C-MOS technology (C-MOS ROM) with a storage capacity of one megabit in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HN 62301 P MB 83 1000 MB 83 1124 TC 53 1000 P or — other identification markings relating to C-MOS ROMs complying with the abovementioned description	7																																																												
ex 8542 11 71	Programmable, non-erasable, read-only memories (PROMs) of Schottky TTL technology, with a storage of 2 K bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 24 connecting pins or contact areas, and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters:<table><tr><td>27 S 12</td><td>5305</td><td>6305</td><td>76 LS 03</td></tr><tr><td>27 S 13</td><td>5306</td><td>6306</td><td>7620</td></tr><tr><td></td><td>5308</td><td>6308</td><td>7621</td></tr><tr><td>28 L 22</td><td>5309</td><td>6309</td><td></td></tr><tr><td>28 LA 22</td><td>53 S 240</td><td>63 S 240</td><td>82 S 114</td></tr><tr><td>28 L 2 XMFC</td><td>53 S 241</td><td>63 S 241</td><td>82 S 130</td></tr><tr><td></td><td></td><td>6335</td><td>82 S 131</td></tr><tr><td>29613</td><td>54 S 570</td><td>6336</td><td></td></tr><tr><td>29770</td><td>54 S 571</td><td></td><td>93436</td></tr><tr><td>29771</td><td></td><td>7053</td><td>93446</td></tr><tr><td></td><td>5604</td><td>7058</td><td></td></tr><tr><td>38510</td><td>5624</td><td></td><td>MB 7115</td></tr><tr><td></td><td></td><td>74 S 570</td><td>MB 7116</td></tr><tr><td></td><td></td><td>74 S 571</td><td>MB 7117</td></tr><tr><td></td><td></td><td></td><td>MB 7118</td></tr></table>or — other identification markings relating to PROMs complying with the abovementioned description	27 S 12	5305	6305	76 LS 03	27 S 13	5306	6306	7620		5308	6308	7621	28 L 22	5309	6309		28 LA 22	53 S 240	63 S 240	82 S 114	28 L 2 XMFC	53 S 241	63 S 241	82 S 130			6335	82 S 131	29613	54 S 570	6336		29770	54 S 571		93436	29771		7053	93446		5604	7058		38510	5624		MB 7115			74 S 570	MB 7116			74 S 571	MB 7117				MB 7118	0
27 S 12	5305	6305	76 LS 03																																																											
27 S 13	5306	6306	7620																																																											
	5308	6308	7621																																																											
28 L 22	5309	6309																																																												
28 LA 22	53 S 240	63 S 240	82 S 114																																																											
28 L 2 XMFC	53 S 241	63 S 241	82 S 130																																																											
		6335	82 S 131																																																											
29613	54 S 570	6336																																																												
29770	54 S 571		93436																																																											
29771		7053	93446																																																											
	5604	7058																																																												
38510	5624		MB 7115																																																											
		74 S 570	MB 7116																																																											
		74 S 571	MB 7117																																																											
			MB 7118																																																											
ex 8542 11 71	Programmable non-erasable MOS technology read-only memories (PROMs) with a storage capacity of 16 K bits, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 39 × 17 mm, with not more than 32 connecting pins or contact areas and bearing:																																																													

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 71 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures and letters: 7 C 245 7 C 291 7 C 292 HM 6616 or — other identification markings relating to PROMs complying with the abovementioned description	0
ex 8542 11 71	Programmable non-erasable read-only memories (PROMs) of bipolar technology with a storage capacity of 16 K bits and a standby current equal to, or of more than, 50 m A and less than, or equal to, 80 m A in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 33 × 14 mm, with not more than 24 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: 27 PS 191 A or — other identification markings relating to PROMs complying with the abovementioned description	0
ex 8542 11 71	Programmable non-erasable read-only memories (PROMs) with a storage of 32 K bits, in the form of a monolithic integrated circuit, whose external dimensions do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 63 S 3281 AM 27 S 43 MB 7141 MB 7142 or — other identification markings relating to PROMs complying with the abovementioned description	0
ex 8542 11 71	Programmable non-erasable read-only memory (PROM) in the form of a monolithic integrated circuit having a storage capacity of 64 K bits and an access time of not more than 65 nanoseconds, contained in a housing whose external dimensions do not exceed 17 × 39 mm, with a maximum of 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CY 7C 261 CY 7C 263 CY 7C 264 CY 7C 268 CY 7C 269 or — other identification markings relating to PROMs complying with the abovementioned description	0
ex 8542 11 71	UV-erasable, programmable, read-only memories (EPROMs) with a storage capacity of 2 K bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with a quartz window on the upper surface and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 82140 PP AMI 702 ADC or — other identification markings relating to EPROMs complying with the abovementioned description	4

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 71	UV-erasable, programmable, read-only memory (EPROM) equipped with a programmable input/output system, with a storage capacity of 2 K × 8 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 52 mm, with a quartz window on the upper face and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: D 8755 A TMP 8755 AC or — other identification markings relating to memories complying with the abovementioned description	0
ex 8542 11 71	UV-erasable programmable read-only memory (EPROM) in the form of a monolithic integrated circuit having a storage capacity of 16 K bits and an access time of not more than 65 ns, contained in a housing the external dimensions of which do not exceed 17 × 39 mm, equipped with a quartz window on its upper surface, and bearing: — an identification code consisting of or including one of the following combinations of figures and letters: CY 245 W CY 7C 291 W or — other identifying codes relating to memories complying with the abovementioned description	0
ex 8542 11 71	UV-erasable programmable read-only memory (EPROM) in the form of a monolithic integrated circuit having a storage capacity of 64 K bits and an access time of not more than 65 ns, contained in a housing the external dimensions of which do not exceed 17 × 39 mm, equipped with a quartz window on its upper surface, and bearing: — an identification code consisting of or including one of the following combinations of figures and letters: CY 7C 261 W CY 7C 263 W CY 7C 268 W CY 7C 269 W or — other identifying codes relating to memories complying with the abovementioned description	0
ex 8542 11 71	Electrically erasable, programmable, read-only memories (E²PROMs) with a storage capacity of 4 K bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 28 C 04 X 2404 X 24 C 04 X 2804 A or — other identification markings relating to E²PROMs complying with the abovementioned description	0
ex 8542 11 71	Electrically erasable, programmable, read-only memories (E²PROMs) with a storage capacity of 16 K bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas bearing:	

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 71 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures and letters: 28 C 16 28 C 17 52 B 13 52 B 13 H - AM 2817 A - X 24 C 16 - X 2816 A - or — other identification markings relating to E²PROMs complying with the abovementioned description	0
ex 8542 11 71	Electrically erasable, programmable, read-only memories (E²PROMs) with a storage capacity of 64 K bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 28 C 64 52 B 33 52 B 33 H - MBM 28 C 65 - MCM 2864 - X 2864 A - or — other identification markings relating to E²PROMs complying with the abovementioned description	0
ex 8542 11 71	Electrically erasable, programmable, read-only memories (E²PROMs) with a storage capacity of 128 K bits, in the form of a monolithic circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: - X 28128 A - or — other identification markings relating to E²PROMs complying with the abovementioned description	0
ex 8542 11 71	Electrically erasable, programmable, read-only memories (E²PROMs) with a storage capacity of 256 K bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 28256 28 C 256 48 C 256 - or — other identification markings relating to E²PROMs complying with the abovementioned description	0
ex 8542 11 71	Monolithic integrated circuit consisting of a static, random-access memory (S-RAM) with a storage capacity of 256 bits superimposed bit-for-bit on a programmable, electrically erasable, read-only-memory (E²PROM), contained in a housing the exterior dimensions of which do not exceed 8 × 24 mm, with not more than 18 connecting pins and bearing:	

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 71 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures and letters: - X 2210 - X 2443 - X 2444 - or — other identification markings relating to S-RAMs superimposed of E²PROMs complying with the abovementioned description	0
ex 8542 11 71	Monolithic integrated circuit consisting of a static random-access memory (S-RAM) with a storage capacity of 1 K bit, superimposed bit-for-bit on an electrically erasable, programmable, read-only memory (E²PROM), contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: - X 2001 - X 2201 A - X 2212 - or — other identifications markings relating to S-RAMs stacked on E²PROMs complying with the abovementioned description	0
ex 8542 11 71	Monolithic integrated circuit consisting of a static, random-access memory (S-RAM) with a storage capacity of 2 K bits, superimposed bit-for-bit on an electrically erasable, programmable, read-only memory (E²PROM), contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of the following combination of figures and letters: - X 2002 - or — other identification markings relating to S-RAMs stacked on E²PROMs complying with the abovementioned description	0
ex 8542 11 71	Monolithic integrated circuit consisting of a static, random-access memory (S-RAM) with a storage capacity of 4 K bits, superimposed bit-for-bit on an electrically erasable, programmable, read-only-memory (E²PROM), contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of the following combination of figures and letters: - X 2004 - or — other identification markings relating to S-RAMs stacked on E²PROMs complying with the abovementioned description	0
ex 8542 11 75	8-bit-single-chip microcomputer of C-MOS technology consisting of a random access memory with a capacity of 2 K bits, a programmable read-only memory with a capacity of 64 K bits and a multi-protocol serial communication port, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 52 × 52 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or containing the following combination of figures and letters: 80 C 152 - or — other identification markings relating to circuits complying with the abovementioned description	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)																																				
ex 8542 11 75	Single-chip microcomputer of C-MOS technology, in the form of a monolithic integrated circuit, consisting of an arithmetical logic unit (ALU) with an organization of 4 bits, a read-only memory (ROM) with a storage capacity of 2 K × 8 bits, a dual-tone, multi-frequency (DTMF) generator, a random access memory (RAM) with a storage capacity of 1 K bit, whether or not with another random access memory (RAM) with a storage capacity of 512 bits, contained in a housing whose dimensions do not exceed 16 × 54 mm, with not more than 42 connecting pins and bearing: — an identification marking consisting of one of the following combinations of figures and letters: T 6978 TCM 8301 TCM 8302 or — other identification markings relating to single-chip microcomputers complying with the abovementioned description	0																																				
ex 8542 11 75	Single-chip microcomputer in C-MOS-technology, in the form of a monolithic integrated circuit consisting of an ALU with a capacity of 32 bits, a ROM with a capacity of 24 K bits and a RAM with a capacity of 2 K bits, contained in a housing the exterior dimensions of which are not less than 30 × 30 mm, with not less than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: MB 8764 or — other identification markings relating to single-chip microcomputers complying with the abovementioned description	0																																				
ex 8542 11 75	Single-chip microcomputers, in the form of a monolithic integrated circuit, consisting of an arithmetical unit with a capacity of four bits plus a read-only memory (ROM) with a capacity of not less than 18 K bits and not more than 104 K bits and a random-access memory (RAM) with a capacity of not less than 512 bits and not more than 4 K bits, contained in a housing the exterior dimensions of which do not exceed 20 × 60 mm, with not more than 80 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: <table><tr><td>CD 3200-3299</td><td>TP 0310-03299</td><td>HD 38800</td><td>HD 404 189</td></tr><tr><td></td><td>TP 0450-04599</td><td>HD 38820</td><td>HD 614 080</td></tr><tr><td>TMC 0270-0279</td><td>TP 0480-04899</td><td>HD 44796</td><td></td></tr><tr><td>TMC 0500-0599</td><td>TP 0500-05999</td><td>HD 44800</td><td></td></tr><tr><td>TMC 0980-0989</td><td>T 7767 BS</td><td>HD 44801</td><td></td></tr><tr><td>TMC 1500-1599</td><td></td><td>HD 44820</td><td></td></tr><tr><td>TMC 1980-1999</td><td></td><td>HD 44840</td><td></td></tr><tr><td></td><td></td><td>HD 44860</td><td></td></tr><tr><td></td><td></td><td>HD 614042</td><td></td></tr></table> or — other identification markings relating to single-chip microcomputers complying with the abovementioned description	CD 3200-3299	TP 0310-03299	HD 38800	HD 404 189		TP 0450-04599	HD 38820	HD 614 080	TMC 0270-0279	TP 0480-04899	HD 44796		TMC 0500-0599	TP 0500-05999	HD 44800		TMC 0980-0989	T 7767 BS	HD 44801		TMC 1500-1599		HD 44820		TMC 1980-1999		HD 44840				HD 44860				HD 614042		0
CD 3200-3299	TP 0310-03299	HD 38800	HD 404 189																																			
	TP 0450-04599	HD 38820	HD 614 080																																			
TMC 0270-0279	TP 0480-04899	HD 44796																																				
TMC 0500-0599	TP 0500-05999	HD 44800																																				
TMC 0980-0989	T 7767 BS	HD 44801																																				
TMC 1500-1599		HD 44820																																				
TMC 1980-1999		HD 44840																																				
		HD 44860																																				
		HD 614042																																				
ex 8542 11 75	Single-chip microcomputer, in the form of a monolithic integrated circuit, consisting of an arithmetic-logic unit with a capacity of 8 bits plus an electronic, programmable, read-only memory (EPROM) UV-erasable with a capacity of 32 K bits and a random access memory (RAM) with a capacity of 1 K bit, contained in a housing the exterior dimensions of which do not exceed 16 × 53 mm, with a quartz window and not more than 40 connecting pins and bearing:																																					

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 75 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures: 7742 8751 or — other identification markings relating to single-chip microcomputers complying with the abovementioned description	0
ex 8542 11 75	Single-chip 8-bit microcomputer of MOS technology, having universal peripheral interface functions, consisting of a central processing unit, a random access read-write memory (RAM) with a storage capacity of 1 K bit, UV-erasable, programmable read-only memory (EPROM) with a storage capacity of 2 K bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 15 × 52 mm, having a quartz window on the upper face, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: D 8742 or — other identification markings relating to circuits complying with the abovementioned description	0
ex 8542 11 75	Single-chip 8-bit microcomputer of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit incorporating 16-bit arithmetic/logic unit (ALU), 4 K bits ROM, 2 K bits RAM, contained in a housing the external dimensions of which do not exceed 42 × 17 mm with not more than 64 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: PD 7811 G or — other identification markings relating to microcomputers complying with the abovementioned description	10
ex 8542 11 75	8-bit microprocessor of C-MOS technology, consisting of a central processing unit (CPU), a memory controller, a two-channel DMA controller, two-channel programmable 16-bit counter/timer, a wait-state generator, a two-channel asynchronous serial communication interface (ASCII) and a bus controller, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 62 × 26 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: Z 64180 or — other identification markings relating to microprocessors complying with the abovementioned description	0
ex 8542 11 75	16-bit microprocessor of C-MOS technology, consisting of a central processing unit (CPU), a memory controller, a 2 K bit cache memory, three programmable 16-bit counter/timers, a full duplex universal asynchronous receiver/transmitter (UART) and four DMA channels, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 26 × 26 mm, with not more than 68 connecting pins or contact areas and bearing:	

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 75 (cont'd)	— an identification marking consisting of or including the following combination of figures and letters: Z 280 - or — other identification markings relating to microprocessors complying with the abovementioned description	0
ex 8542 11 75	16-bit microprocessor of C-MOS technology, consisting of a central processing unit (CPU) and a 8-bit or 16-bit external data bus, contained in a housing the exterior dimensions of which do not exceed 54 × 16 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: Z 70108 Z 70116 - or — other identification markings relating to microprocessors complying with the abovementioned description	0
ex 8542 11 75	32-bit microprocessor (MPU) of C-MOS technology in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 38 × 38 mm, with not more than 132 connecting pins and bearing: — an identification marking either consisting of or including one of the following combinations of figures and letters: 80386 MC 68020 MC 68030 MC 68032 - or — other identification markings relating to circuits complying with the abovementioned description	0
ex 8542 11 75	8-bit microprocessor of N-MOS (including H-MOS) technology, for the encoding/decoding of data (data ciphering processor), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 53 × 15 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: Z 8068 Z 9518 - or — other identification markings relating to microprocessors complying with the abovementioned description	0
ex 8542 11 75	8-bit microprocessor of N-MOS (including H-MOS) technology with 16 bit internal architecture, in the form of a monolithic integrated circuit consisting of a central processing unit (CPU), a timing generator, two independent DMA channels, a programmable interrupt controller, three programmable 16 bit timers, programmable memory and peripheral chip select, a programmable wait state generator and a local bus controller, contained in a housing the dimensions of which do not exceed 30 × 30 mm with not more than 68 connecting pins or contact areas, and bearing: — an identification marking consisting of or including the following combination of figures: 80188 - or — other identification markings relating to microprocessors complying with the abovementioned description	7

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 75	16-bit microprocessor in N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit, consisting of a central processing unit (CPU), a timing generator, two independent DMA channels, a programmable interrupt controller, three programmable 16 bit timers, programmable memory and external chip selection logic, a programmable wait state generator with bus control unit, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures: 80186 or — other identification markings relating to microprocessors complying with the abovementioned description	0
ex 8542 11 75	16-bit microprocessor of N-MOS technology (including H-MOS) in the form of a monolithic integrated circuit, consisting of a central processing unit (CPU), a memory management and protection unit (MMU) and a real address and virtual address operating mode system (OSO), contained in a housing whose exterior dimensions do not exceed 30 × 30 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures: 80286 or — other identification markings relating to microprocessors complying with the abovementioned description	10
ex 8542 11 75	16-bit microprocessor of bipolar technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 25 × 82 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AM 29116 SBP 9989 or — other identification markings relating to microprocessors complying with the abovementioned description	0
ex 8542 11 75	Floating-point arithmetic co-processor of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 30 × 30 mm, with not more than 80 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters or figures: 80387 MC 68881 MC 68882 or — other identification markings relating to circuits complying with the abovementioned description	0
ex 8542 11 75	Graphics co-processor of C-MOS technology comprising an advanced DRAM controller for graphics memory, shift registers and DMA channel, up to 256 simultaneous colours, multi-tasking support, integral sequential DRAM/access DRAMs, contained in a housing the exterior dimensions of which do not exceed 37 × 37 mm, with not more than 88 connecting pins or contact areas and bearing:	

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 75 (cont'd)	— an identification marking consisting of or including the following combination of figures: 82786 - or — other identification markings relating to graphics co-processors complying with the abovementioned description	7
ex 8542 11 75	Text co-processor, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 25×25 mm, with not more than 68 connecting pins, and bearing: — an identification marking consisting of or including the following combination of figures and letters: C 82730 - or — other identification markings relating to text co-processors complying with the abovementioned description	0
ex 8542 11 75	Numeric processor extension unit of N-MOS (including H-MOS) technology (N-MOS NPX) containing not more than 14 registers, in the form of a monolithic integrated circuit, contained in a package the exterior dimensions of which do not exceed 16×53 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 80287 8087 NS 32081 TX 32081 W - or — other identification markings relating to N-MOS NPXs complying with the abovementioned description	0
ex 8542 11 75	Central processing unit of N-MOS (including H-MOS) technology (N-MOS CPU), in the form of a monolithic integrated circuit consisting of a 16×16 bit service memory, a 16×20 bit service memory, a 32×32 bit service memory, an 8×8 bit service memory, a 16 bit register, two 20 bit registers, an 8 bit register, one 12 bit register, a 5 bit counter and timing network, contained in a housing the exterior dimensions of which do not exceed 25×25 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: LSI-604041855 - or — other identification markings relating to N-MOS central processing units complying with the abovementioned description	0
ex 8542 11 91	Arithmetic-logic of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit, consisting of one 32 bit register, one 24 bit register, one 4 bit register, twelve 1 bit registers, two 16×24 bit service memories, one logic network performing arithmetic and logic operations, decoding logic, and error detection and management logic, one 8 bit counter and a timing network, contained in a housing the exterior dimensions of which do not exceed 23×82 mm, with not more than 64 connecting pins and bearing: — the identification marking: ALU 0486 - or — other identification markings relating to arithmetic-logic units complying with the abovementioned description	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Logic circuit of N-MOS (including H-MOS) technology (N-MOS LC) serving as a clock generator for central process unit, main memory and input/output interfaces, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 25 × 25 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: H 108982 (MCC) - or — other identification markings relating to N-MOS logic circuits (N-MOS LCs) complying with the abovementioned description	0
ex 8542 11 91	Clock generator and controller for microprocessors, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 24 × 8 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letter: Z 8581 - or — other identification markings relating to clock generators and controllers complying with the abovementioned description	0
ex 8542 11 91	Logic circuit of bipolar technology, with not more than six logic functions, a supply voltage of not less than 11 V and not more than 18 V, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8 × 23 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: FZH 101 A FZH 111 A FZH 191 FZH 201 FZJ 121 FZK 101 - or — other identification markings relating to logic circuits complying with the abovementioned description	0
ex 8542 11 91	Logic control circuits of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit, consisting of one 7 bit register, three timers, one multiplexer sequential and combining networks intended to perform control operations, decodifying logic, error detection and management logic and a timing network, contained in a housing the exterior dimensions of which do not exceed 23 × 82 mm, with not more than 64 connecting pins and bearing: — the identification marking: MIC 0482 - or — other identification markings relating to logic control circuits complying with the abovementioned description	0
ex 8542 11 91	Semi-custom logic array (gate array) of C-MOS technology with metal gates, in the form of a monolithic integrated circuit with an operating voltage of 12 volts, with not less than 637 two-input functions, having within the array a digital code produced by an electron beam, contained in a housing whose exterior dimensions do not exceed 29 × 11 mm, with not more than 22 connecting pins and bearing:	

Combined Nomenclature code	Description	Rate of autonomous duty (%)																		
ex 8542 11 91 (cont'd)	— an identification marking consisting of or including the following combination of figures and letters: FB 215 - or — other identification markings relating to gate arrays complying with the abovementioned description	7																		
ex 8542 11 91	Field programmable array logics (PALs) of C-MOS-technology, in the form of a monolithic integrated circuit, with fusible links, a programmable AND array, fixed OR array, not more than 32 inputs and not more than 10 outputs, whether or not with registers, contained in a housing the exterior dimensions of which do not exceed 19 × 39 mm, with not more than 24 connecting pins and bearing: — an identification marking either consisting of or including one of the following combinations of figures and letters: 16 P 8 16 RP 4 C 16 L 8 C 16 R 4 C 16 R 6 C 16 R 8 C 20 G 10 C 22 V 10 - or — other identification markings relating to PALs complying with the abovementioned description	0																		
ex 8542 11 91	Programmable, non-erasable, logic circuits (field programmable logic array) of TTL Schottky technology, with not more than 48 AND functions, not more than eight OR functions, and not more than 16 inputs, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: <table data-bbox="391 1424 824 1583"> <tr> <td>FP 54 AS 839</td><td>FP 74 AS 839</td><td>82 S 100</td></tr> <tr> <td>FP 54 AS 840</td><td>FP 74 AS 840</td><td>82 S 101</td></tr> <tr> <td>SN 54 LS 333</td><td>SN 74 LS 333</td><td></td></tr> <tr> <td>SN 54 LS 334</td><td>SN 74 LS 334</td><td>93458</td></tr> <tr> <td>SN 54 LS 335</td><td>SN 74 LS 335</td><td>93459</td></tr> <tr> <td>SN 54 LS 336</td><td>SN 74 LS 336</td><td></td></tr> </table> - or — other identification markings relating to field programmable logic arrays complying with the abovementioned description	FP 54 AS 839	FP 74 AS 839	82 S 100	FP 54 AS 840	FP 74 AS 840	82 S 101	SN 54 LS 333	SN 74 LS 333		SN 54 LS 334	SN 74 LS 334	93458	SN 54 LS 335	SN 74 LS 335	93459	SN 54 LS 336	SN 74 LS 336		5
FP 54 AS 839	FP 74 AS 839	82 S 100																		
FP 54 AS 840	FP 74 AS 840	82 S 101																		
SN 54 LS 333	SN 74 LS 333																			
SN 54 LS 334	SN 74 LS 334	93458																		
SN 54 LS 335	SN 74 LS 335	93459																		
SN 54 LS 336	SN 74 LS 336																			
ex 8542 11 91	Non-erasable user-programmable logic sequencer of bipolar technology, having not more than 48 AND functions, a 6-bit state register, an 8-bit output register, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 82 S 105 - or — other identification markings relating to circuits complying with the abovementioned description	0																		

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 91	UV-erasable programmable logic device (EPLD) of C-MOS technology containing not less than 600 logic gates, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 29×124 mm, with a quartz window on the upper surface, with not more than 24 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combination of figures and letters: EP 600 16 I 8-W 16 R 4-W 16 R 6-W 16 R 8-W 22 V 10-W or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Gate arrays of C-MOS technology in the form of a monolithic integrated circuit containing not less than 100 K transistors and not more than 500 000 transistors, contained in a housing the exterior dimensions of which do not exceed 50×50 mm, with not more than 299 connecting pins and bearing: — an identification consisting of or including one of the following combinations of figures and letters: LCA 10026 LCA 10075 LCA 10038 LCA 10100 LCA 10051 LCA 10129 or — other identification markings relating to microprocessors complying with the abovementioned description	7
ex 8542 11 91	Error detection and correction circuit of N-MOS (including H-MOS) technology capable of detecting and correcting single bit errors and detecting all double bit errors, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 30×30 mm, with not more than 68 contact areas and bearing: — an identification marking consisting of or including the following combination of figures: 8206 or — other identification markings relating to N-MOS error detection and correction circuits complying with the abovementioned description	0
ex 8542 11 91	Burst error processor (BEP) of N-MOS (including H-MOS) technology for detecting and correcting multiple errors derived from a line of magnetic discs, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16×54 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: Z 8065 AM 9520 AM 9521 or — any other identification markings relating to N-MOS burst error processor complying with the abovementioned description	0
ex 8542 11 91	Error correction and detection unit (ECDU) of bipolar technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16×62 mm, with not more than 48 connecting pins and bearing:	

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 91 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures or figures and letters: 2960 74 F 630 74 F 631 74 LS 630 74 LS 631 DP 8400 - or — other identification markings relating to error correction and detection units (ECDUs) complying with the abovementioned description	0
ex 8542 11 91	Control and interface circuit for central processor (CPU-controller) of C-MOS technology in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of letters and figures: 82 C 201 82 C 206 FE 2000 FE 2010 FE 3000 FE 3010 L 1 A 0392 - or — other identification markings relating to control and interfacing circuits complying with the abovementioned description	0
ex 8542 11 91	Hard-disc controller of N-MOS (including H-MOS) technology (N-MOS-HDCs), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 53 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HDC 9224 PD 7261 WD 1010 WD 2010 WD 5010 WD 5011 - or — other identification markings relating to N-MOS HDCs complying with the abovementioned description	0
ex 8542 11 91	4-channel read/write monolithic integrated circuit of bipolar technology for controlling magnetic heads in hard disk units, contained in a housing whose exterior dimensions do not exceed 12 × 19 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: SSI 510 - or — other identification markings relating to integrated circuits complying with the abovementioned description	0
ex 8542 11 91	Floppy disc controller of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 16 × 62 mm, with not more than 48 connecting pins and bearing:	

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 91 (cont'd)	— an identification marking consisting of or including one of the following combinations of letters and figures: FE 2100 G 70360-33 L 1 A 0519 MB 89311 WD 16 C 92 WD 37 C 65 - or — other identification markings relating to adaptor circuits complying with the abovementioned description	7
ex 8542 11 91	Buffer manager and controller of N-MOS (including H-MOS) technology in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 54 × 17 mm with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: WD 1015 - or — other identification markings relating to buffer management control processors complying with the abovementioned description	0
ex 8542 11 91	Buffer manager and controller of C-MOS technology in the form of a monolithic integrated circuit contained in a house whose exterior dimensions do not exceed 31 × 31 mm with not more than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: WD 11 C 00-22 WD 83 C 580 WD 83 C 583 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit for static memory control (S-RAM) with address multiplexing and pulse generation facility, in the form of a monolithic integrated circuit of MOS technology contained in a housing whose dimensions do not exceed 28 × 54 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AIC 300 OMTI 506 - or — other identification markings relating to electronic control circuits complying with the abovementioned description	0
ex 8542 11 91	Control circuit of bipolar technology in the form of a monolithic integrated circuit for the control of dynamic random-access memories (D-RAMs), capable of multiplexing addresses and generating timing, contained in a housing the exterior dimensions of which do not exceed 17 × 62 mm, with not more than 48 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: DP 8408 DP 8409 MB 1422 SN 74 S 409 - or — other identification markings relating to electronic control circuits complying with the abovementioned description	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Dynamic random access memory controller of N-MOS (including H-MOS) technology (N-MOS D-RAM controller) capable of multiplexing addresses and generating timing, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 17×62 mm, with not more than 48 connecting pins or 52 contact areas, and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: C 8208 THCT 4502 - or — other identification markings relating to N-MOS D-RAM controllers complying with the abovementioned description	0
ex 8542 11 91	Memory controller of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing whose dimensions do not exceed 36×36 mm, with not more than 132 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: MC 68851 - or — other identification markings relating to controllers complying with the abovementioned description	0
ex 8542 11 91	Memory management unit of N-MOS (including H-MOS) technology (N-MOS MMU) with a maximum addressing capacity of 4 G bytes, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 36×82 mm, with not more than 125 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 68451, TX 32082 W NS 32082 NS 32382 - or — other identification markings relating to N-MOS MMUs complying with the abovementioned description	0
ex 8542 11 91	Sequence control circuit of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit, consisting of one 32 bit register, three 16 bit registers, one 16×16 bit service memory, one 7×17 bit last-in-first-out (LIFO) memory, one adder circuit, decodifying logic, priority logic, error detection and management logic, one 16 bit multiplexer, one 8 bit counter and a timing network, contained in a housing the exterior dimensions of which do not exceed 23×82 mm, with not more than 64 connecting pins and bearing: — the identification marking: CSS 0484 - or — other identification markings relating to sequence control circuits complying with the abovementioned description	0
ex 8542 11 91	Input-output circuit of N-MOS (including H-MOS) technology for data control equipped with a timing control with a static random access memory (S-RAM) with a capacity of 128×8 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16×54 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or letters and figures: 6532 CO 10750 - or — other identification markings relating to input-output control circuits complying with the abovementioned description	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Sequential data control circuit of MOS technology for interface between a hard disc memory unit and the memory control unit in the form of a monolithic integrated circuit of MOS technology contained in a housing whose exterior dimensions do not exceed 28 × 54 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AIC 010 AIC 100 OMTI 505 - or — other identification markings relating to sequential circuits complying with the abovementioned description	0
ex 8542 11 91	Control circuit of C-MOS technology for the control of S/RAMs, capable of multiplexing addresses and generating pulses, and for the sequential control of data for the peripheral magnetic unit/rigid disk interface, and memory control, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm, with not more than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of letters and figures: OMTI 5055 (20513) - or — other identification markings relating to control circuits complying with the abovementioned description	0
ex 8542 11 91	Status and shift control unit of bipolar technology in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 57 mm with not more than 42 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AM 2904 - or — other identification markings relating to status and shift control units complying with the abovementioned description	0
ex 8542 11 91	Circuit of advanced low power Schottky (ALPS) technology for the asynchronous control of signal lines (bus) and the conversion of a local bus into a multiplexed bus (BAM) in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 37 × 13 mm, with not more than 28 connecting pins and bearing: — an identification marking: 68452 - or — other identification markings relating to ALPS BAMs complying with the abovementioned description	0
ex 8542 11 91	Contention resolving a local area network (LAN) controller, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 63 × 63 mm, with not more than 84 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 8001 MCM 68590 8003 WD 2840 82586 WD 80 C 24 82588 WD 83 C 503 AM 7990 WD 83 C 510 COM 9026 WD 83 C 603 DP 8390 WD 83 C 690 - or — other identification markings relating to contention resolving local area network controllers complying with the abovementioned description	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Enhanced programmable communications interface (EPCI), in the form of a monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 17×39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures: 2661 - or — other identification markings relating to EPCIs complying with the abovementioned description	0
ex 8542 11 91	Serial communication controllers of C-MOS technology, with two independent duplex channels with a capacity of 2 Mbits/sec, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 53×18 mm, with not more than 44 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: Z 80 C 30 Z 85 C 30 Z 85 C 35 - or — other identification markings relating to controllers complying with the abovementioned description	0
ex 8542 11 91	Display controller and character generator (DCCG) for liquid crystal dot matrix display system in the form of a monolithic integrated circuit of C-MOS technology, contained in a housing the exterior dimensions of which do not exceed 20×26 mm, with not more than 60 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: HD 61830 - or — other identification markings relating to C-MOS Display Controller and character generators complying with the abovementioned description	0
ex 8542 11 91	Interpolation pulse generator of C-MOS technology for controlling geometrical functions, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17×39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: KM 3701 - or — other identification markings relating to interpolation modules complying with the abovementioned description	0
ex 8542 11 91	Video control circuit for graphics and memory (video controller), in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 15×52 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 38301-A L IA 2099 PVC-2 - or — other identification markings relating to devices complying with the abovementioned description	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Monochrome display controller (MDC) of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 25 × 25 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 01-01.00 551 A or — other identification markings relating to circuits complying with the abovementioned description	0
ex 8542 11 91	Cathode-ray tube controller (CRTC) of C-MOS technology in the form of a monolithic integrated circuit, contained in a housing whose dimensions do not exceed 32 × 62 mm, with not more than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: 82 C 434 or — other identification markings relating to controllers complying with the abovementioned description	0
ex 8542 11 91	Control circuit for cathode-ray tubes or liquid crystal displays (CRT and LCD controller) of C.MOS technology, in the form of a monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 30 × 30 mm, with not more than 84 connecting pins or contact areas, and bearing: — an identification marking consisting of or including the following combination of letters and figures: V 6355-DJ or — other identification markings relating to electronic control circuits complying with the abovementioned description	0
ex 8542 11 91	Cathode-ray tube controller (CRTC) of N-MOS (including H-MOS) technology in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 62 × 25 mm, with not more than 68 connecting pins and bearing: — an identification marking either consisting of or including one of the following combinations of figures and letters: AM 8052 D 8275 H HD 6845 HD 68 A 45 P 8275 H or — other identification markings relating to CRTCs complying with the abovementioned description	7
ex 8542 11 91	Cathode-ray tube controller (CRTC) of bipolar technology in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 15 × 5.5 mm with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: SCB 2675 or — other identification markings relating to CRTCs complying with the abovementioned description	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Programmable advanced video display controller (AVDGs) of N-MOS (including H-MOS) technology in the form of a monolithic integrated circuit, contained in a housing whose external dimensions do not exceed 15 × 55 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: SCN 2674 - or — other identification markings relating to controllers complying with the abovementioned description	7
ex 8542 11 91	Graphics controller of C-MOS technology in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: PEGA 82 C 431 - or — other identification markings relating to graphics controllers complying with the abovementioned description	0
ex 8542 11 91	Graphic display controller (GDC), of N-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 52 × 18 mm, with not more than 44 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: Z 7220 A - or — other identification markings relating to GDCs complying with the abovementioned description	0
ex 8542 11 91	Colour selection controller of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 19 × 52 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: 82 C 433 - or — other identification markings relating to controllers complying with the abovementioned description	0
ex 8542 11 91	Analogue-digital monolithic circuit, capable of controlling spindle motors and keeping their speed constant, contained in a housing whose exterior dimensions do not exceed 9 × 25 mm, with not more than 20 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: MGA 3015 A UC 1633 UC 1634 UC 3633 UC 3634 - or — other identification markings relating to analogue-digital integrated circuits complying with the abovementioned description	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Analogue-digital monolithic integrated circuit of bipolar technology, for damping the oscillations of stepping motors during the positioning phase, contained in a housing whose exterior dimensions do not exceed 18 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of letters: STEDA or — other identification markings relating to integrated circuits complying with the abovementioned description	0
ex 8542 11 91	Controller for servo-devices of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 54 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: KM 3702 or — other identification markings relating to controllers complying with abovementioned description	0
ex 8542 11 91	Eight-Channel control circuit for maintaining a constant electromagnetic traction force with incorporated diodes and a storage capacity of eight bits, in the form of a monolithic integrated circuit, of C-MOS technology contained in a housing the exterior dimensions of which do not exceed 9 × 28 mm, with not more than 22 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: UCN 5801 or — other identification markings relating to control circuits complying with the abovementioned description	0
ex 8542 11 91	Four-Channel control circuit for maintaining a constant electromagnetic traction force with incorporated diodes and a storage capacity of four bits, in the form of a monolithic integrated circuit of C-MOS technology, contained in a housing the exterior dimensions of which do not exceed 7 × 22 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: UCN 5813 or — other identification markings relating to control circuits complying with the abovementioned description	0
ex 8542 11 91	Control circuit of TTL technology in the form of a monolithic integrated circuit for the firing of magnetic print hammers, contained in a housing the exterior dimensions of which do not exceed 8 × 23 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 801379-002 810751-001 or — other identification markings relating to integrated circuits complying with the abovementioned description	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 91	8-bit-(octal) dynamic memory bipolar driver in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 33 mm, with not more than 20 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AM 2965 AM 2966 or — other identification markings relating to dynamic memory bipolar drivers complying with the abovementioned description	0
ex 8542 11 91	Parallel communications interface of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 64 × 64 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figure and letters: PPC-1 or — other identification markings relating to electronic control circuits complying with the above-mentioned description	0
ex 8542 11 91	Subscriber line interface circuit (SLIC) with a high voltage rating of not less than 200 V, with direct internal relay drive, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: HC 5504 or — other identification markings relating to SLICS complying with the abovementioned description	0
ex 8542 11 91	Programmable communication interface of N-MOS (including H-MOS) technology (N-MOS PCIs), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 8251 A or — other identification markings relating to N-MOS PCIs complying with the abovementioned description	7
ex 8542 11 91	Control circuit for data block transfer between dynamic memory and peripherals (DMA Transfer Controller or „DTC“), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 63 × 16 mm, with not more than 48 connecting pins, and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: Z 8516 Z 9516 or — other identification markings relating to DTCs complying with the abovementioned description	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Serial interface, capable of implementing the data stream encoding, decoding and associated control functions for a local area network, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 8002 8023 82501 - AM 7991 - COM 9032 - or — other identification markings relating to serial interface devices complying with the abovementioned description	0
ex 8542 11 91	Station digital interface circuit for parallel/serial or serial/parallel conversion of digital signals in telephone sets, of C-MOS technology (C-MOS STID), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins, and bearing: — an identification marking consisting of or including the following combination of figures and letters: - WCC 295 G - or — other identification markings relating to station interface digital circuits complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit of bipolar technology with 8, 9 or 10-bit registers, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 9 × 34 mm, with not more than 24 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: - AM 29821 - AM 29822 - AM 29823 - AM 29824 - AM 29825 - AM 29826 - AM 29843 - AM 29844 - or — other identification markings relating to bus interface circuits complying with the abovementioned description	0
ex 8542 11 91	Multiple bus interface circuit (Multiple Bus Buffer) of low power Schottky technology for interfacing the error correction and detection unit system data bus and dynamic random access memory (D-RAM), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: - AM 2961 - or — other identification markings relating to error correction multiple bus buffers complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit of ALPS technology, in the form of a monolithic integrated circuit, for the management of address signals, contained in a housing the external dimensions of which do not exceed 25 × 25 mm, with not more than 68 connecting pins and bearing:	

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 91 (cont'd)	— an identification marking consisting of or including the following combination of figures and letters: 82 A 203 or — other identification markings relating to bus interface circuits complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit of ALPS technology, in the form of a monolithic integrated circuit, for the management of data flow in the signal lines of the CPU, contained in a housing the external dimensions of which do not exceed 25 × 25 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 82 A 205 or — other identification markings relating to bus interface circuits complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit in C-MOS technology, in the form of a monolithic integrated circuit, for the control of communication lines comprising a numerical bus, two independent receivers and a transmitter consisting of a first-in first-out (FIFO) memory, contained in a housing whose exterior dimensions do not exceed 20 × 52 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: HS 3282 or — other identification markings relating to bus interface circuits complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit of C-MOS technology, in the form of a monolithic integrated circuit, for the management of address signals, comprising a circuit with 4 × 2-input AND gates, 2 buffer circuits, 2 latch circuits, 4 independent transceivers, a 256 × 4 bit PROM, contained in a housing the external dimensions of which do not exceed 31 × 31 mm, with not more than 84 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: FE 3020 or — other identification markings relating to bus interface circuits complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit C-MOS technology, in the form of a monolithic integrated circuit, for the management of I/O data flow in signal lines, with 4 independent transceivers, a circuit with 4 × 2-input NAND gates, a circuit with 4 × 2-input AND gates, a separator circuit, a flip-flop circuit, contained in a housing the external dimensions of which do not exceed 31 × 31 mm, with not more than 84 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: FE 3030 or — other identification markings relating to bus interface circuits complying with the abovementioned description	0
ex 8542 11 91	Interface circuit for the synchronization of data flow from a hard disc drive, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 16 × 35 mm, with not more than 28 connecting pins and bearing:	

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 91 (cont'd)	— an identification marking consisting of or including the following combination of figures and letters: DP 8462 - or — other identification markings relating to interfaces complying with the abovementioned description	0
ex 8542 11 91	Analogue-digital monolithic integrated circuit of bipolar technology for interface signals between the peripheral hard-disc, memory unit and the central unit, contained in a housing the external dimensions of which do not exceed 15 × 50 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 581 C - or — other identification markings relating to integrated circuits complying with the abovementioned description	0
ex 8542 11 91	Interface circuit of C-MOS technology for signals between peripheral hard disc memory units and central units, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 28 × 53 mm, with not more than 80 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: OMTI 5080 (OMTI 20508) OMTI 5090 (OMTI 20509) WD 11 C 00 - or — other identification markings relating to bus interface circuits complying with the abovementioned description	0
ex 8542 11 91	Encoder/decoder serial interface circuit for hard disc drives, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 × 37 mm, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AIC 250 AIC 270 OMTI 5027 OMTI 507 - or — other identification markings relating to interface circuits complying with the abovementioned description	0
ex 8542 11 91	Monolithic integrated circuit with a least 16 analogue switching elements, of C-MOS technology, for controlling low frequency signals in the range of 20 Hz to 20 000 Hz, capable of dealing with signals up to 3 V with a distortion of not more than 0,05 % over the whole frequency range at a voltage of 1 V, contained in a housing the exterior dimensions of which do not exceed 16 × 40 mm, with not more than 42 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: TC 9164 N TC 9177 P TC 9184 P - or — other identification markings relating to monolithic integrated circuits complying with the abovementioned description	7

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 99	Computing unit for the multiplication or processing of fixed and floating point numbers, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 42 × 42 mm, with not more than 144 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: ADSP 3210, ADSP 3220 - or — other identification markings relating to computing units complying with the abovementioned description	0
ex 8542 11 99	8 × 8 bit multiplier accumulator (MAC) of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 62 × 16 mm, with not more than 48 connecting pins and bearing: — an identification marking consisting of or including the following combination of numbers and letters: ADSP-1008 A - or — other identification markings relating to MACs complying with the abovementioned description	0
ex 8542 11 99	Floppy-disc data separator (FDDS), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 27 × 8 mm, with not more than 20 connecting pins and bearing: — an identification marking consisting of or including the following combinations of figures and letters: FDC 9216 FDC 9216-B FDC 9229 T FDC 9229 BT WD 9216-00 WD 92 C 32 - or — other identification markings relating to FDDS, complying with the abovementioned description	0
ex 8542 11 99	Hard Disc Data Separator (HDDS) in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 16 × 37 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: DP 8460-2 DP 8460-3 DP 8460-4 DP 8465 HDC 9226 WD 10 C 20 WD 10 C 21 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Six- or eight-channel monolithic integrated circuit for the generation of read/write signals for hard disc drivers, contained in a housing the exterior dimensions of which do not exceed 13 × 13 mm, with not more than 40 connecting pins and bearing:	

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 99 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures and letters: SSI 117 SSI 501 or — other identification markings relating to integrated circuits complying with the abovementioned description	0
ex 8542 11 99	Universal synchronous/asynchronous receiver/transmitter (USART) of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: MSM 82 C 51 or — other identification markings relating to universal synchronous/asynchronous receiver/transmitters complying with the abovementioned description	7
ex 8542 11 99	Dual universal asynchronous receiver/transmitter (DUART) of MOS-technology, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 16 × 53 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: MC 2681 SCN 2681 or — other identification markings relating to circuits complying with the abovementioned description	0
ex 8542 11 99	Programmable asynchronous communication element circuit N-MOS technology, for the asynchronous transmission and reception of data, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 54 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: INS 8250 INS 82 C 50 NS 16450 NS 16550 NS 16 C 450 WD 8250 or — other identification markings relating to ACE circuits complying with the abovementioned description	0
ex 8542 11 99	Monolithic integrated circuit in N-MOS technology (including H-MOS) for the display of graphic symbols on a cathode-ray-tube operating in stroke mode, contained in a housing whose exterior dimensions do not exceed 28 × 61 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: FCD 96 114 898 FCD 96 114 899 FCD 96 149 135 FCD 28 042 277 or — other identification markings relating to circuits complying with the abovementioned description	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 99	Sequential control and generating circuit of CMOS technology for the memory display, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 19 × 52 mm, with not more than 44 connecting pins or contact surfaces and bearing: — an identification marking consisting of or including the following combination of figures and letters: 82 C 432 - or — other identification markings relating to integrated circuits complying with the abovementioned description	0
ex 8542 11 99	Demodulator/tone decoder of bipolar technology for frequency decoding, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 10 × 21 mm, with not more than 14 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: XR 2211 - or — other identification markings relating to demodulator tone decoders complying with the abovementioned description	0
ex 8542 11 99	Encoder/decoder circuit using Manchester code (MED) for the transmission of data in continuous flux with a repeater mode in C-MOS technology, having an output voltage of 4,5 volts, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 33 mm, with not more than 20 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: HD 6409 - or — other identification markings relating to circuits complying with the abovementioned description	0
ex 8542 11 99	Pulse code modulation (PCM) codec of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit, consisting of a sample and hold circuit digital-to-analogue converter, comparator, successive approximation register and logic function to interface to a full duplex PCM link, contained in a housing whose exterior dimensions do not exceed 11 × 29 mm, with not more than 22 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 2911 A-1 - or — other identification markings relating to PCM codecs complying with the abovementioned description	7
ex 8542 11 99	Subscriber line audio-processing circuit (SLAC) with two digital signal processors, an analogue-digital converter and a digital-analogue converter, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AM 7901 AM 7905 - or — other identification markings relating to SLACs complying with the abovementioned description	7

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 99	Analogue-digital signal converter, containing amplifiers, D/A and A/D converters with a supply voltage of 12 V $\pm$ 10 % and a digital serial interface with asynchronous receiver/transmitter, in the form of a monolithic integrated circuit, contained in a housing whose external dimensions do not exceed 18 $\times$ 18 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 75002 - or — other identification markings relating to programmable amplifiers with asynchronous receiver/transmitter complying with the abovementioned description	0
ex 8542 11 99	Analogue to digital converter for the calculation of the average value of variable wave-forms, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 $\times$ 10 mm, with not more than 14 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 536 A - or — other identification markings relating to integrated circuits complying with the abovementioned description	0
ex 8542 11 99	12-bit-analogue to digital converter, in the form of a monolithic integrated circuit incorporating a voltage reference and clock, contained in a housing the external dimensions of which do not exceed 36 $\times$ 15 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 574 A - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Pulse code modulation (PCM) transmit/receive filter of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit, consisting of two filters of a PCM line or trunk termination, contained in a housing whose exterior dimensions do not exceed 10 $\times$ 21 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: D 2912 A - or — other identification markings relating to PCM filters complying with the abovementioned description	7
ex 8542 11 99	C-MOS clock circuit, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 $\times$ 54 mm, with not more than 16 connecting pins, and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HI 2060 HI 2065 MSM 5537 T 3605 - or — other identification markings relating to clock circuits complying with the abovementioned description for the production of automatic time-switches, instrument panel clock and clocks of a similar type for motor vehicles (a)	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 99	C-MOS clock circuit, operating from a single 1,5 V power supply, with a liquid crystal display (LCD) driver, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 15 × 21 mm, with not more than 56 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: TC 8219 AF - or — other identification markings relating to C-MOS clock circuits complying with the abovementioned description	0
ex 8542 11 99	C-MOS clock/calendar circuit, incorporating a quartz crystal oscillator, independent timer recorders and a timer, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 7 × 20 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: MM 581 74 A 58274 - or — other identification markings relating to clock/calendar circuits complying with the abovementioned description	0
ex 8542 11 99	C-MOS clock circuit with audio and hour-count output, in the form of a monolithic integrated circuit, contained in a housing whose dimensions do not exceed 17 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: SVM 5530 7910 - or — other identification markings relating to clock/calendar circuits complying with the abovementioned description	0
ex 8542 11 99	MOS programmable interval timer (MOS PIT), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures: 8253 8254 82 C 54 - or — other identification markings relating to MOS PITs complying with the abovementioned description	0
ex 8542 11 99	Function generator of bipolar technology for the generation of variable waveforms, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 10 × 21 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: XR 2206 XR 8038 - or — other identification markings relating to function generators complying with the abovementioned description	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)												
ex 8542 11 99	Digital signal synthesizer of C-MOS technology with one frequency generator producing one signal and able to output one sound, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8×25 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: UMC 3511 A - or — other identification markings relating to digital signal synthesizers (DSS) complying with the abovementioned description	0												
ex 85 42 11 99	Programmable digital signal synthesizer of C-MOS technology with 13 frequency generators each producing up to five sounds and an output capacity of up to 65 sounds, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 15×50 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: DPS 6401 - or — other identification markings relating to digital signal synthesizers complying with the abovementioned description	0												
ex 8542 11 99	Programmable digital signal synthesizer of C-MOS technology with 32 frequency generators to generate eight notes each and a simultaneous output of up to 160 notes, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 25×25 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of letters: MEG - or — other identification markings relating to digital synthesizers (DSS) complying with the abovementioned description	0												
ex 8542 11 99	C-MOS-phoneme speech synthesizer, with a supply current of less than 10 mA, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17×39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: <table data-bbox="318 1536 857 1637"> <tr> <td>CD 54121 N2L</td><td>CM 54104</td><td>SC 01</td></tr> <tr> <td>CD 54122 N2L</td><td>CM 54145 N2L</td><td>SSI 263</td></tr> <tr> <td>CD 54123 N2L</td><td>CM 54146 N2L</td><td></td></tr> <tr> <td>CD 54147 N2L</td><td>CM 54166 N2L</td><td></td></tr> </table> - or — other identification markings relating to phoneme speech synthesizers complying with the abovementioned description	CD 54121 N2L	CM 54104	SC 01	CD 54122 N2L	CM 54145 N2L	SSI 263	CD 54123 N2L	CM 54146 N2L		CD 54147 N2L	CM 54166 N2L		0
CD 54121 N2L	CM 54104	SC 01												
CD 54122 N2L	CM 54145 N2L	SSI 263												
CD 54123 N2L	CM 54146 N2L													
CD 54147 N2L	CM 54166 N2L													
ex 8542 11 99	Amplifier, of bipolar technology for the amplification of either read or write signals of floppy discs, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 11×29 mm, with not more than 22 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: XR 2247 XR 3470 - or — other identification markings relating to amplifiers complying with the abovementioned description	0												

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 11 99	Six-Channel monolithic integrated circuit (Read/write data processor circuit) for the amplification and conversion of read signals and conversion of write signals for hard disc drives, contained in a housing the exterior dimensions of which do not exceed 19 × 38 mm, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of letters and figures: SSI 540 SSI 541 or — other identification markings relating to integrated circuits complying with the abovementioned description	0
ex 8542 11 99	Repeater circuit, of bipolar technology for the regeneration of pulse code-modulated signals, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 10 × 21 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: XR C 240 or — other identification markings relating to repeater circuits complying with the abovementioned description	0
ex 8542 11 99	Smoke detector operating in a temperature range between at least - 20 °C to 50 °C, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 23 × 9 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CS 235 V 24216 or — other identification markings relating to smoke detectors complying with the abovementioned description	0
ex 8542 19 20	Amplifier, in the form of a monolithic integrated analog circuit the exterior dimensions of which do not exceed 3 × 3 mm for use in the manufacture of products falling within subheading 9021 40 00 (a)	0
ex 8542 19 30	Amplifier, in the form of a monolithic integrated analog circuit, contained in a housing the exterior dimensions of which do not exceed 2 × 4 × 4 mm, with not more than 10 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: C 05 V 35 or — other identification markings relating to amplifiers complying with the abovementioned description for the manufacture of products falling within subheading 9021 40 00 (a)	0
ex 8542 19 30	Electronically adjustable differential amplifiers for at least the full range of signals from 0 to not less than 400 MHz, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 11 × 11 mm, with not more than 16 connecting pins, and bearing: — an identification marking consisting of or including the following combination of figures: 0078-10 or — other identification markings relating to amplifiers complying with the abovementioned description	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 19 30	Amplifier for a full range of signals from 0 to 60 KHz, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed $6 \times 13 \times 26$ mm, with not more than 18 connecting pins and a leakage of not more than $0.3 \mu\text{A}$ and bearing: — an identification marking consisting of or including the following combination of figures and letters: ISO 100 - or — other identification markings relating to amplifiers complying with the abovementioned description, for use in the manufacture of telephone exchanges (a)	0
ex 8542 19 30	Read/write amplifier for thin film magnetic heads, in the form of a monolithic integrated analogue circuit, contained in a housing the exterior dimensions of which do not exceed 8×11 mm, with not more than 24 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: VM 114 - or — other identification markings relating to amplifiers complying with the abovementioned description	0
ex 8542 19 30	Winchester disc drive amplifier for magnetic heads, in the form of a monolithic integrated analogue circuit, contained in a housing the exterior dimensions of which do not exceed 7×7 mm, with not more than 10 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: A 2480 FC - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 30	Amplifier with a programmable gain factor in the form of a monolithic integrated analogue circuit, contained in a housing the exterior dimensions of which do not exceed 30×45 mm, with not more than 32 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 3606 G - or — other identification markings relating to amplifiers complying with the abovementioned description	0
ex 8542 19 30	Thermocouple amplifier for instrumentation control at temperatures from 0° to 50°C, incorporating an alarm system, in the form of a monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 20×8 mm, with not more than 14 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AD594 AD595 - or — other identification markings relating to thermocouple amplifiers complying with the abovementioned description	0
ex 8542 19 90	Monolithic integrated analogue circuit of bipolar technology for the overload protection of telephone exchanges, contained in a housing the exterior dimensions of which do not exceed 11×10 mm, with not more than 3 connecting pins and bearing:	

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 19 90 (cont'd)	— an identification marking consisting of or including the following combination of figures: 1515 or — other identification markings relating to monolithic integrated circuits complying with the abovementioned description	0
ex 8542 19 90	Frequency generator in the form of an analogue monolithic integrated circuit of bipolar technology, with an operating voltage of not less than 40 and not more than 130 V AC, which generates signals oscillating between 512 Hz ($\pm 22\%$) and 640 Hz ($\pm 22\%$) at a 10 Hz rate, contained in a housing the external dimensions of which do not exceed 9×11 mm, with not more than 8 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: QMV 155 or — other identification markings relating to integrated circuits complying with the abovementioned description	0
ex 8542 19 90	Monolithic integrated analogue circuit for the reduction of audio noise by 14 dB, contained in a housing the exterior dimensions of which do not exceed 26×7 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: HA 12043 or — other identification markings relating to analogue circuits complying with the abovementioned description	0
ex 8542 19 90	Premagnetization control circuit for audio frequency magnetic tapes, of bipolar technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 26×8 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: PC 1297 CA or — other identification markings relating to monolithic integrated circuits complying with the abovementioned description	0
ex 8542 19 90	Temperature transducer in the form of a monolithic analogue integrated circuit, contained in a housing the exterior dimensions of which do not exceed 6×4 mm, with not more than three connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 590 or — other identification markings relating to transducers complying with the abovementioned description	0
ex 8542 19 90	Monolithic integrated analogue circuit of C-MOS technology for controlling the speed of linear or rotary motors and the positioning of magnetic heads, contained in a housing the exterior dimensions of which do not exceed 14×38 mm, with not more than 28 connecting pins and bearing:	

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 19 90 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures and letters: A 2460 A 2461 or — other identification markings relating to integrated analog circuits complying with the abovementioned description	0
ex 8542 19 90	Monolithic integrated analogue circuit of bipolar technology for driving linear motors or motors with rotating arms, working at 20 V/2,5 A maximum, contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: EL 2007 EL 2017 or — other identification markings relating to integrated analogue circuits complying with the abovementioned description	0
ex 8542 19 90	Phase-locked loop (PLL) frequency synthesizer of N-MOS (including H-MOS) technology for the AM and FM frequency ranges, in the form of a monolithic integrated analogue circuit, contained in a housing the exterior dimensions of which do not exceed 25 × 7 mm, with not more than 20 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: LM 7000 or — other identification markings relating to circuits complying with the abovementioned description	0
ex 8542 20 00	32-bit microprocessor in C-MOS technology, in the form of a hybrid integrated circuit, consisting of a single substrate layer on which are mounted two chips, comprising a central processing unit (CPU) and a memory unit, the exterior dimensions of which do not exceed 33 × 76 mm, with not more than 60 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 57-00000, 57-19400 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 00	Video digital to analogue converter (VDAC) with a maximum conversion time of 10 nanoseconds, in the form of a hybrid integrated circuit, contained in a housing the exterior dimensions of which do not exceed 20 × 35 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: VDAC 0405 H VDAC 0605 H VDAC 0805 H or — other identification markings relating to VDACs complying with the abovementioned description	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8542 20 00	Four-channel digital-to-analogue converter, each channel having a capacity of 12 bits, in the form of a hybrid integrated circuit, contained in a housing the external dimensions of which do not exceed 41 × 21 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 390 - or — other identification markings relating to converters complying with the abovementioned description	0
ex 8542 20 00	Amplifier in the form of a hybrid integrated circuit for the frequency range 20 Hz to 20 000 Hz, contained in a housing the exterior dimensions of which do not exceed 45 × 80 mm, with not more than 30 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: STK 4041 STK 4151 STK 4201 - or — other identification markings relating to hybrid circuits complying with the abovementioned description	0
ex 8542 20 00	Subscriber-connection units (crosspoint switch) with not less than four and not more than 12 switches and an operating voltage of at least 150 V, in the form of a hybrid integrated circuit, contained in a housing whose dimensions do not exceed 92 × 41 mm, with not more than 94 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 904 719 - or — other identification markings relating to a crosspoint switch complying with the abovementioned description	0
ex 8542 20 00	Infrared receiver with a carrier frequency of not less than 36 kHz and not more than 40 kHz, in the form of a hybrid integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 15 mm, with not more than 5 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: BX 1317 BX 1323 BX 1387 BX 1407 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 00	Filters operating in the frequency ranges between 5 and 11 kHz or 2,2 and 2,5 mHz, in the form of a hybrid integrated circuit, contained in a housing the exterior dimensions of which do not exceed 33 × 17 mm, with not more than 4 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: SLC 2570 - or — other identification markings relating to filters complying with the abovementioned description	0

Combined Nomenclature code	Description	Rate of autonomous duty (%)
ex 8543 80 90	Modulators for the range from 0,5 to 4,2 mHz, contained in a housing the external dimensions of which do not exceed 74 × 48 mm	0
ex 9013 80 00	Liquid crystal devices (LCD's) consisting of a layer of liquid crystals between two glass sheets or plates, with a minimum of seven and a maximum of 32 figures or letters, whose exterior dimensions are: — 52 × 22 mm, or — 67 × 27 mm, or — 63 × 22 mm, with not more than 192 connecting pins or contact areas, for use in the manufacture of calculators (a)	0
ex 9021 90 90	Portable reading appliance for the visually handicapped in which a fibre optic camera transmits a magnified image on to a display screen, and parts thereof	3

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.