

Official Journal

of the European Communities

ISSN 0378 - 6978

L 329

Volume 31

1 December 1988

English edition

Legislation

Contents

I *Acts whose publication is obligatory*

- ★ **Council Regulation (EEC) No 3696/88 of 18 November 1988 temporarily suspending the autonomous Common Customs Tariff duty on certain industrial products 1**

2

Acts whose titles are printed in light type are those relating to day-to-day management of agricultural matters, and are generally valid for a limited period.

The titles of all other Acts are printed in bold type and preceded by an asterisk.

I

(Acts whose publication is obligatory)

COUNCIL REGULATION (EEC) No 3696/88

of 18 November 1988

temporarily suspending the autonomous Common Customs Tariff duty on certain industrial products

THE COUNCIL OF THE EUROPEAN COMMUNITIES,

Having regard to the Treaty establishing the European Economic Community, and in particular Article 28 thereof,

Having regard to the proposal from the Commission,

Whereas production of the products referred to in this Regulation is at present inadequate or non-existent within the Community and producers are thus unable to meet the needs of user industries in the Community;

Whereas it is in the Community's interest in certain cases to suspend the autonomous Common Customs Tariff duties only partially, particularly because of the existence of Community production, and in other cases to suspend them completely;

Whereas, taking account of the difficulties involved in accurately assessing the development of the economic situation in the sectors concerned in the near future, these

suspension measures should be taken only temporarily, by fixing their period of validity by reference to the interests of Community production;

HAS ADOPTED THIS REGULATION:

Article 1

The autonomous Common Customs Tariff duties for the products listed in the tables appearing in the Annexes shall be suspended at the level indicated in respect of each of them.

These suspensions shall apply:

- from 1 January 1989 to 31 March 1989 for the products in Table I,
- from 1 January 1989 to 30 June 1989 for the products in Table II.

Article 2

This Regulation shall enter into force on 1 January 1989.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 18 November 1988.

For the Council

The President

V. PAPANDREOU

ANNEX

TABLE I

CN code	Description	Rate of autonomous duty (%)
ex 3004 90 99	Dried purified protein fraction, consisting principally of des-1-alanine-(125-serine)interleukin-2(human), obtained from genetically-manipulated <i>Escherichia coli</i>	0
ex 3901 90 00	Copolymer of ethylene with methyl acrylate containing by weight 16 % or more but not exceeding 20 % of methyl acrylate, in one of the forms mentioned in note 6 (b) to Chapter 39	0
ex 8471 93 50	Floppy disc storage units for automatic data-processing machines	0
ex 8542 11 71	Dynamic random access memories (D-RAMS) of MOS technology with a storage capacity of 1 Megabit and an access time not exceeding 150 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 9 mm, with not more than 26 connecting pins with small outline (J-bend) plastic chip carrier package and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HM 511000JP TC 511000J PD 421000LA MB 81C1000-PJ HM 511000 HM 511000P HM 511002P - or — other identification markings relating to devices complying with the abovementioned description	12

TABLE II

CN code	Description	Rate of autonomous duty (%)
ex 2811 19 00	Sulphamidic acid	0
ex 2917 39 90	Benzene-1,2,4-tricarbonyl trichloride	0
ex 2924 29 90	5-((R)-1-Hydroxy-2-((R)-1-methyl-3-phenylpropylamino)ethyl)salicylamide-2,3-di-O-benzoyl-(+)-tartaric acid (1/1)	0
ex 2926 90 90	Isophthalonitrile	6
ex 2926 90 90	Ethyl cyanoacetate	7
ex 2926 90 90	Methyl cyanoacetate	7
ex 2930 90 90	Netobimin (INN)	0
ex 2935 00 00	Sulfadimethoxine (INN) and its sodium salt	0
ex 2937 10 90	Protirelin tartrate (INN)	0
ex 2937 20 90	9,21-Dichloro-11- <i>beta</i> ,17-dihydroxy-16- <i>alpha</i> -methylpregna-1,4-diene-3,20-dione 17-(2-furoate)	0
ex 2941 90 00	Cefixime (INN)	0
ex 2941 90 00	Kitasamycin (INN) and its tartrate	0
ex 2941 90 00	Monensin (INN) and its salts	0
ex 2941 90 00	Pirarubicin (INN)	0
ex 3003 40 00	Granules containing by weight 40 % or more but not exceeding 50 % of theophylline	0
ex 3003 90 90	Granules containing by weight 0,7 % or more but not exceeding 1,2 % of glycerol trinitrate	0
ex 3004 90 19	Purified collagen dispersed in a phosphate physiological saline solution whether or not containing lidocaine (INN)	3
ex 3505 10 00	Self-adhesive plastic film, coated or covered on one side with glycerol trinitrate mixed with an acrylic adhesive, containing 4 mg/cm ² or more of glycerol trinitrate, protected by a release sheet, not put up in forms of packings for retail sale	0
ex 3505 10 50	O-(2-Hydroxyethyl)amylopectin hydrolysate	0
3701 91 10	Film in the flat, put up in disc form and incorporated in a cartridge	5,3
ex 3815 90 00 ex 3823 90 20	Catalyst in the form of rodlets, containing an acid aluminosilicate (zeolite of the Y type) in the sodium form, containing by weight not more than 11 % sodium expressed as sodium oxide	0
ex 3815 90 00	Catalyst in the form of rodlets of a diameter of 3 mm or more but not exceeding 10 mm, consisting of oxides of copper and chromium, for use in the manufacture of fatty alcohols (a)	0
ex 3815 90 00	Catalyst in powder form consisting of oxides of chromium, copper and barium, for use in the manufacture of fatty alcohols (a)	0
ex 3823 90 91	Tetramethylammonium hydroxide dissolved in methanol	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)
ex 3823 90 98	Preparation in powder form, containing by weight 75% or more of zinc bis[3,5-bis 1-(phenylethyl)salicylate]	0
ex 3901 10 90	Polyethylene containing by weight 0,25% or more of carbonyl groups in the chain, in pellet form	0
ex 3901 20 00	Polyethylene, in one of the forms mentioned in note 6 (b) to Chapter 39, having a density of not less than 0,958 g/cm ³ at 23 °C and containing by weight not more than: — 50 ppm of aluminium, — 2 ppm of calcium, — 2 ppm of chromium, — 2 ppm of iron, — 2 ppm of nickel, — 2 ppm of titanium, — 8 ppm of vanadium, for the manufacture of chlorosulphonated polyethylene (a)	0
ex 3901 20 00	Polyethylene, in one of the forms mentioned in note 6 (b) to Chapter 39, having a specific gravity of not less than 0,945 and not more than 0,985 g/cm ³ for the manufacture of typewriter ribbon or similar ribbon (a)	0
ex 3901 90 00	Ionomer resin consisting of a salt of a copolymer ethylene and methacrylic acid	0
ex 3901 90 00	Ionomer resin consisting of a salt of a terpolymer of ethylene, isobutyl acrylate and methacrylic acid	0
ex 3903 90 00	Copolymer, entirely of maleic anhydride with styrene, or entirely of maleic anhydride with styrene and an acrylic monomer, whether or not containing a styrene-butadiene block copolymer, in one of the forms mentioned in note 6 (b) to Chapter 39	0
ex 3903 90 00	Copolymers, solely of allyl alcohol with styrene, which have an acetyl value of not less than 175	0
ex 3907 20 90	<i>alpha</i> -4-Hydroxybutyl- <i>omega</i> -hydroxypoly (oxytetramethylene), with a halogen or metal content each of less than 1 mg/kg and a colour of not more than 20 units on the Hazen scale	0
ex 3907 20 90	Poly(oxypropylene) having alkoxysilyl end-groups	0
ex 3920 62 00	Polyethylene terephthalate film of a thickness of 100 micrometres or more but not exceeding 130 micrometres, for use in the manufacture of photopolymer printing plates (a)	0
ex 3920 92 00	Poly(epsilon-caprolactam) film with a softening point of 200 °C or more and a copper content of 130 mg/kg or more but not exceeding 170 mg/kg for sheet-moulding compounds (a)	0
ex 3920 99 19 ex 3921 90 50	Polyimide sheet and strip, uncoated, or coated or covered solely with plastic	0
ex 3920 99 50	Biaxially orientated polyvinyl alcohol film containing not less than 97% by weight of polyvinyl alcohol, uncoated, with a thickness of not more than 1 mm	0
ex 3920 99 50 ex 3921 90 60	Ion-exchange membranes of fluorinated plastic material, for use in chlor-alkali electrolytic cells (a)	0
ex 4104 10 91 ex 4104 21 00	Leather of East India kip, whole, whether or not the heads and legs have been removed, each weighing more than 4,5 kg net and not more than 8 kg, not further prepared than vegetable tanned, whether or not having undergone certain treatments, but obviously unsuitable for immediate use for the manufacture of leather articles	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)
ex 5911 10 00	Needle-punched synthetic fibre felts on a woven synthetic fibre base not containing polyester, coated or covered on one side with polytetrafluoroethylene film, for the manufacture of filtration products (a)	0
ex 5911 10 00	Needle-punched polyester felts on a woven polyester base coated or covered on one side with polytetrafluoroethylene film, of a weight per square metre not exceeding 500 g, for the manufacture of filtration products (a)	0
ex 7019 32 00 ex 7019 39 00	Non-woven products of non-textile glass fibre, of a weight per square metre of not more than 120 g and a fibre diameter, excluding any coating, of not more than 7 micrometres, for the manufacture of filtration products (a)	0
ex 7019 90 10	Non-textile glass fibres in which fibres of a diameter of less than 3,5 micrometres predominate	0
ex 8421 99 00	Components of separators for the separation or purification of gases from gas mixtures, consisting of a bundle of permeable hollow fibres enclosed within a container, whether or not perforated, of an overall length of not less than 300 mm and not more than 3 700 mm and a diameter of not more than 500 mm	0
ex 8471 99 90	Optical reader for reading dot-matrix printing characters and converting them into electrical signals, comprising a read head containing an optical detector, an amplifier, a focusing lens and two lamps, linked by one or two flat cables to a central module of which the dimensions do not exceed 200 × 220 mm, comprising a printed circuit board on which are mounted a microprocessor, an image recognition circuit and an analogue-to-digital converter	0
ex 8473 10 00	Integrated memory unit for electronic typewriters, comprising a printed circuit with two or four static read/write random-access memories each with 8 K × 8 bit capacity, electronic control components and memory back-up-batteries, contained in a cartridge fitted with connectors, of external dimensions not exceeding 11 × 40 × 90 mm, and bearing: — an identification marking consisting of or including the following combination of letters: MEMOCART or — other identification markings relating to devices complying with the abovementioned description	0
ex 8473 10 00 ex 8473 30 00	Dot-matrix displays consisting of a layer of liquid crystal between two glass sheets or plates with a maximum of 15 360 dots (arranged in 64 lines and 240 columns), complete with an interface electronics board in C-MOS technology whose exterior dimensions do not exceed 186 × 75 × 15 mm, with not more than 544 contact areas	0
ex 8473 10 00 ex 8473 30 00	Dot-matrix displays, whose external dimensions do not exceed 15 × 90 × 280 mm excluding cables and connectors consisting of a layer of liquid crystals between two glass sheets or plates with 30 720 dots (arranged in 64 lines and 480 columns), mounted on a printed-circuit board comprising electronic components providing drive functions, with or without cable and connector	0
ex 8473 10 00 ex 8473 30 00	Dot-matrix displays, whose external dimensions do not exceed 15 × 62 × 276 mm excluding cables and connectors consisting of a layer of liquid crystals between two glass sheets or plates with 32 768 dots (arranged in 64 lines and 512 columns), mounted on a printed-circuit board comprising electronic components providing drive and control functions, with or without cable and connector	0
ex 8473 30 00	Ferrite magnetic heads of Winchester technology for disc file peripherals, as well as carrying arms equipped with such magnetic heads, capable of recording to a density of not less than 10 tracks per millimetre	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)
ex 8473 30 00	Magnetic bubble memories with a storage capacity of not more than four megabits contained in a housing the exterior dimensions of which do not exceed 43 × 44 mm, with not more than 42 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: - BDL 0133 MBM 2011 FBM 64 DA - BDL 0134 MBM 2256 7110 - BDN 0151 FBM 54 DB 7114-1 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8473 30 00	Component forming the arithmetic/logic element of a central processing unit, comprising not more than nine printed circuit boards, the dimensions of which do not exceed 290 × 310 mm on each of which are mounted not more than 121 ECL gate arrays or ECL random access memories (ECL-RAMs) and combinations thereof contained in a framework the dimensions of which do not exceed 611 × 501 × 596 mm which serves as a housing and interconnector for the printed circuit boards, which bear: — an identification marking consisting of or including one of the following combinations of figures and letters: - CO1B 2675 E 500 - CO1B 2675 H 500 - CO1B 2675 H 501 - CO1B 2675 H 502 - CO1B 2675 H 503 - CO1B 2675 H 504 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8473 30 00	Assemblies for automatic data-processing machines, consisting of two stacked substrate layers with one or two static random-access memories of bipolar technology (bipolar S-RAMs) in the form of monolithic integrated circuits, each with a storage capacity of 1 Kbit and with a maximum storage capacity of 4 Kbits, contained in a housing the exterior dimensions of which do not exceed 13 × 13 mm, with not more than 23 connecting pins and bearing: — an identification marking, consisting of or including one of the following combinations of figures: 770965 4599497 7379442 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8473 40 00	Thermal printer heads of thick or thin film technology consisting of a printed circuit with at least one tantalum capacitor and an electrolytic capacitor contained in a metal support with connector, printer element and heat sink, supplied with the appropriate support and transport roll	0
ex 8483 10 90	Integrally forged and roughly shaped generator and turbine shafts of a weight exceeding 215 tonnes	0
ex 8501 10 99	DC electric motor, brushless, with a torque of not more than 0,2 Nm, with a coupling flange of a diameter of 74 mm, a spindle of a diameter of 40 mm, rated speed of 3 600 rpm, supply voltage of 12 V ± 10 %, with cables and connectors	0
ex 8501 10 99	DC electric motor, brushless, with a torque of not more than 0,20 Nm, with outside rotor of a maximum diameter of 55 mm, coupling flange of a diameter of 77 mm and precision-made chuck of a diameter of 44 mm, four-phase winding, rated speed of 3 600 rpm, supply voltage of 12 V ± 10 % and fitted with wires and connectors	0

CN code	Description	Rate of autonomous duty (%)
ex 8501 10 99	DC electric motor, brushless, with a torque of not more than 0,05 Nm, an outside rotor of a maximum diameter of 92 mm, aluminium precision-made hub with an outside diameter of 40 mm, two-phase winding, rated speed of 3 600 rpm, supply voltage of 12 V $\pm$ 10 %	0
ex 8501 10 99	Hybrid stepping motor with an angle of step 0,9°, 400 steps per revolution, two- or four-phase rotation sequence and bipolar windings, comprising a rotor, a laminated stator enclosed between two square section flanges with sides not more than 40 mm wide and fitted with biterminate shaft, wires and connectors	0
ex 8501 10 99	Hybrid stepping motor with an angle of step of 0,9°, 400 steps per revolution, two-phase rotation sequence and bipolar windings, comprising a rotor and a stator encapsulated in a cylindrical housing with a maximum diameter of 47 mm and maximum thickness of 14 mm, fitted with a single shaft output and cables with connectors	0
ex 8501 10 99	Hybrid stepping motor with an angle of step of 0,9°, 400 steps per revolution and two-phase rotation sequence, and bipolar windings, comprising a rotor, a laminated stator enclosed between two square section flanges with sides not exceeding 40 mm, an integral 2- or 3-phase tachometer enclosed in a cap with a maximum diameter of 35 mm, and separate cables and connectors for the motor and tachometer outputs, with maximum dimensions of 40 $\times$ 40 $\times$ 62 mm, including the shaft	0
ex 8501 10 99	Hybrid stepping motor with an angle of step of 0,9°, 400 steps per revolution, two-phase rotation sequence with bipolar winding, comprising a rotor, a laminated stator enclosed between two flanges, one of square section with a side of 40 mm maximum, the other front face having a shaped profile with two projections with fixing slots, an integral two- or three-phase tachometer enclosed in a cover of diameter of 35 mm maximum, separate cables and connectors for the motor and tachometer outputs, with overall dimensions not exceeding 40 $\times$ 40 $\times$ 62 mm, including the shaft but excluding the projections of the front flange	0
ex 8501 10 99	Direct-current bipolar stepping motor with a single stator, an output of not more than 37,5 W, a rotary angle/step of 180°, two steps per rotation, a two-phase rotation cycle with single-pole winding, an output torque of not less than 0,1 $\times$ 10 ⁻⁶ Nm and not more than 0,1 $\times$ 10 ⁻⁴ Nm and a supply voltage of not more than 3 V	0
ex 8504 40 99	Static converter consisting of a combination of seven diodes in cascade, for output voltages of not less than 40 kV DC with a load current of not less than 3 mA	0
ex 8506 19 10	Lithium iodine single cell battery with dimensions not exceeding 45 $\times$ 9 $\times$ 23 mm and a voltage not exceeding 2,8 V	0
ex 8506 19 10	Unit consisting of not more than two lithium batteries embedded in a socket for integrated circuits (battery-buffered socket), with not more than 28 connecting pins and incorporating a control circuit	0
ex 8506 19 90	Dry zinc/carbon batteries of a voltage of not less than 5,5 V and not more than 6,5 V and of a size not exceeding 110 $\times$ 90 $\times$ 5 mm, for incorporation in film cassettes for instant pictures (a)	0
ex 8517 90 91	Assembly for telephonic apparatus consisting of a microphone, protecting circuit and four-way connecting socket, mounted on a printed circuit, with dimensions not exceeding 22 $\times$ 40 mm	0
ex 8523 20 10	Rigid magnetic discs, prelubricated, oxide type, with a coercivity of 300 Oe or more	0
ex 8523 20 10	Rigid magnetic disc with a thin-film metallic coating, having a coercivity of more than 600 Oersted/Oe, an external diameter of 88 mm or more but not exceeding 231 mm	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)												
ex 8529 10 70	Ceramic filter package comprising two ceramic filters with three connecting pins and one ceramic resonator with two connecting pins, each having a frequency of 10,7 MHz ± 30 kHz, contained in a housing the exterior dimensions of which do not exceed 10 × 10 × 5 mm	0												
ex 8532 29 00	Gold capacitor with a rated capacitance of 100 mF, an operating voltage of 5,5 V and a leakage current of not more than 100 µA, contained in a cylindrical housing of a height of less than 8 mm and a diameter of not more than 14 mm	0												
ex 8532 30 10	Variable plate capacitor with plastic dielectric, with a capacitance of not more than 2 × 355 pF for the AM section and not more than 2 × 20 pF for the FM section, contained in a housing the exterior dimensions of which do not exceed 21 × 24 mm	0												
ex 8532 30 90	Adjustable capacitor, in the form of a circular plate with a diameter of not more than 2,5 mm, fitted with a screw head in its centre and two connecting tags, of a thickness not exceeding 3 mm and a capacity of from 5 to 30 picofarads, for the manufacture of products falling within Chapter 91 (a)	0												
ex 8533 29 00	Device consisting of fixed resistors with a positive temperature coefficient having a nominal resistance in DC of 19,6 Ω at 20 °C, an insulation resistance of more than 1 MΩ, for the protection of telephone exchanges against prolonged increases in voltage of not more than 1 000 V, contained in a housing the exterior dimensions of which do not exceed 48 × 19 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures: 20793 or — other identification markings relating to devices complying with the abovementioned description	0												
ex 8533 40 10	Slide potentiometers with one or two resistor tracks and a slide distance of 20 mm, contained in a housing with not more than eight connecting pins	0												
ex 8534 00 11 ex 8534 00 19	Single-face printed circuit, of dimensions not exceeding 30 × 30 mm, for the manufacture of products falling within Chapter 91 (a)	0												
ex 8536 41 10 ex 8536 41 90 ex 8536 49 00	Thermal relays contained in a hermetically sealed glass cartridge not exceeding 35 mm in length excluding wires, with a maximum leakage rate of 10 ⁻⁶ cm ³ He/sec at one bar in the temperature range 0 to 160 °C, to be incorporated into compressors for refrigerating equipment (a)	0												
ex 8536 50 00	Telephone line switch assembly consisting of one moveable and one stationary bifurcated spring with contact area of diffused gold on palladium silver inlay, mounted in polycarbonate material, and of dimensions not exceeding 40 × 20 × 13 mm	0												
ex 8536 50 00	Reed switches in the form of a glass capsule containing not more than three electrical contacts on metal arms and a small quantity of mercury	0												
ex 8540 11 10	Colour cathode-ray tubes with a slit mask, equipped with electron guns placed side by side (in-line technology) with a distance between stripes of the same colour not exceeding 0,47 mm and having the following characteristics: — a diagonal screen measurement not less than 12 and not more than 16 cm — a diagonal angle of deflection not exceeding 55°	0												
ex 8540 11 10	Colour cathode-ray tubes with a slit mask, equipped with electron guns placed side by side (in-line technology) with a distance between stripes of the same colour of not more than 0,47 mm and having the following characteristics: — a diagonal screen measurement not less than 22 and not more than 26 cm — a diagonal angle of deflection of not more than 76° — a phosphor layer calibrated with the following nominal coordinates for the colour dots <table><tr><td></td><td>red</td><td>green</td><td>blue</td></tr><tr><td>X</td><td>0,610</td><td>0,298</td><td>0,151</td></tr><tr><td>Y</td><td>0,342</td><td>0,588</td><td>0,064</td></tr></table>		red	green	blue	X	0,610	0,298	0,151	Y	0,342	0,588	0,064	0
	red	green	blue											
X	0,610	0,298	0,151											
Y	0,342	0,588	0,064											

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)																																																																								
ex 8540 11 90	Colour cathode-ray tubes with a slit mask, equipped with electron guns placed side by side (in-line technology), with a distance between stripes of the same colour of not more than 0,86 mm and having the following characteristics: — a diagonal screen measurement of not less than 76 cm — a diagonal angle of deflection of not more than 110°	10																																																																								
ex 8540 20 90	Photomultiplier consisting of a photocathode tube with nine dynodes, for light of wavelength of 160 nanometres or more but not exceeding 930 nm, of a diameter not exceeding 14 mm and a height not exceeding 94 mm	0																																																																								
ex 8540 30 00	Colour cathode-ray tubes with a dot mask, equipped with electron guns placed side by side (in-line technology), with a distance of less than 0,45 mm between colour dots and with at least one of the following characteristics: — a diagonal screen measurement of not less than 42 cm or less than 26 cm, a diagonal angle of deflection of not more than 90° and convergence errors exceeding 0,8 mm at the corners — a built-in system, inseparably linked to the tube, for the absorption of vibration (so called potting system) — without internal magnetic screen — a phosphor layer calibrated with the following nominal coordinates for the colour dots: <table><tr><td></td><td>red</td><td>green</td><td>blue</td></tr><tr><td>X</td><td>0,64</td><td>0,29</td><td>0,15</td></tr><tr><td>Y</td><td>0,33</td><td>0,60</td><td>0,06</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,64</td><td>0,31</td><td>0,155</td></tr><tr><td>Y</td><td>0,34</td><td>0,595</td><td>0,07</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,62</td><td>0,21</td><td>0,15</td></tr><tr><td>Y</td><td>0,33</td><td>0,615</td><td>0,06</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,610</td><td>0,307</td><td>0,150</td></tr><tr><td>Y</td><td>0,350</td><td>0,595</td><td>0,065</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,61</td><td>0,205</td><td>0,15</td></tr><tr><td>Y</td><td>0,35</td><td>0,680</td><td>0,065</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,62</td><td>0,29</td><td>0,15</td></tr><tr><td>Y</td><td>0,35</td><td>0,60</td><td>0,065</td></tr></table>		red	green	blue	X	0,64	0,29	0,15	Y	0,33	0,60	0,06	or				X	0,64	0,31	0,155	Y	0,34	0,595	0,07	or				X	0,62	0,21	0,15	Y	0,33	0,615	0,06	or				X	0,610	0,307	0,150	Y	0,350	0,595	0,065	or				X	0,61	0,205	0,15	Y	0,35	0,680	0,065	or				X	0,62	0,29	0,15	Y	0,35	0,60	0,065	0
	red	green	blue																																																																							
X	0,64	0,29	0,15																																																																							
Y	0,33	0,60	0,06																																																																							
or																																																																										
X	0,64	0,31	0,155																																																																							
Y	0,34	0,595	0,07																																																																							
or																																																																										
X	0,62	0,21	0,15																																																																							
Y	0,33	0,615	0,06																																																																							
or																																																																										
X	0,610	0,307	0,150																																																																							
Y	0,350	0,595	0,065																																																																							
or																																																																										
X	0,61	0,205	0,15																																																																							
Y	0,35	0,680	0,065																																																																							
or																																																																										
X	0,62	0,29	0,15																																																																							
Y	0,35	0,60	0,065																																																																							
ex 8540 30 00	Colour cathode-ray tubes with a dot mask equipped with electron guns in a triangular fashion (delta technology) with a distance of less than 0,4 mm between colour dots and with at least one of the following characteristics: — a diagonal screen measurement of at least 66 cm — equipped with a phosphor layer calibrated with the following nominal coordinates for the colour dots: <table><tr><td></td><td>red</td><td>green</td><td>blue</td></tr><tr><td>X</td><td>0,64</td><td>0,29</td><td>0,15</td></tr><tr><td>Y</td><td>0,33</td><td>0,60</td><td>0,06</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,64</td><td>0,31</td><td>0,155</td></tr><tr><td>Y</td><td>0,34</td><td>0,595</td><td>0,07</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,610</td><td>0,307</td><td>0,150</td></tr><tr><td>Y</td><td>0,350</td><td>0,595</td><td>0,065</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,61</td><td>0,205</td><td>0,15</td></tr><tr><td>Y</td><td>0,35</td><td>0,680</td><td>0,065</td></tr><tr><td>or</td><td></td><td></td><td></td></tr><tr><td>X</td><td>0,62</td><td>0,29</td><td>0,15</td></tr><tr><td>Y</td><td>0,35</td><td>0,60</td><td>0,065</td></tr></table>		red	green	blue	X	0,64	0,29	0,15	Y	0,33	0,60	0,06	or				X	0,64	0,31	0,155	Y	0,34	0,595	0,07	or				X	0,610	0,307	0,150	Y	0,350	0,595	0,065	or				X	0,61	0,205	0,15	Y	0,35	0,680	0,065	or				X	0,62	0,29	0,15	Y	0,35	0,60	0,065	0												
	red	green	blue																																																																							
X	0,64	0,29	0,15																																																																							
Y	0,33	0,60	0,06																																																																							
or																																																																										
X	0,64	0,31	0,155																																																																							
Y	0,34	0,595	0,07																																																																							
or																																																																										
X	0,610	0,307	0,150																																																																							
Y	0,350	0,595	0,065																																																																							
or																																																																										
X	0,61	0,205	0,15																																																																							
Y	0,35	0,680	0,065																																																																							
or																																																																										
X	0,62	0,29	0,15																																																																							
Y	0,35	0,60	0,065																																																																							

CN code	Description	Rate of autonomous duty (%)
ex 8540 30 00	Flat screen monochrome cathode-ray tubes having a diagonal screen measurement of not less than 142 mm and not more than 145 mm, a luminescence of between 300 and 400 lumen, a resolution of between 0,06 and 0,1 mm, phosphor types P 1 or P 55 or P 56, an anode voltage of more than 34 kV, a focus voltage of more than 7 kV and a cathode current of not less than 3 mA	0
ex 8540 30 00	Cathode-ray tubes with a memory (direct view storage tubes) for the reproduction of alphanumeric and analogue data, equipped with a scanning device, for reading the images	0
ex 8540 41 00	Continuous wave magnetron with a power output of less than 1 000 W, for the manufacture of microwave ovens of CN code 8516 50 00 (a)	0
ex 8540 89 11	Displays in the form of a tube consisting of a glass housing mounted on a board the dimensions of which do not exceed 350 × 300 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallized base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons	0
ex 8540 91 00	Tungsten elements coated with insulating material, grids and cathodes for use in the manufacture of electron guns for monochrome cathode-ray tubes (a)	0
ex 8540 91 00	Deflector yoke for cathode-ray tubes with an operating frequency of between 31 250 Hz and 64 000 Hz incorporating a quadripolar magnet	0
ex 8541 10 91	Silicon power rectifier diodes of planar technology, with a recovery time of less than 100 ns, a maximum recurring reverse voltage of 200 V, and average conducting-state current of 2,5 A, or more, contained in a flat housing the exterior dimensions of which exceed 9 × 9 × 5 mm, but do not exceed 17 × 11 × 5 mm	0
ex 8541 10 99	Germanium-gold diodes with forward voltage not exceeding 1 V at 5 mA	0
ex 8541 29 90	Transistor with a power of not less than 150 W at a voltage of not less than 160 V and with a cut-off frequency of not less than 20 MHz, contained in a housing the exterior dimensions of which do not exceed 37 × 22 mm, with not more than three connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 2 SA 1170 2 SC 2774 2 SA 1215 2 SC 2921 2 SA 1494 2 SC 3858 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8541 40 10	Light-emitting diode (LED) made from a gallium-based semiconductor compound, mounted in a rectangular housing the exterior dimensions of which do not exceed 4 × 20 × 21 mm, with two connecting pins, and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: LT 9305 SLF 209 LT 9306 SLF 909 - or — other identification markings relating to devices complying with the abovementioned description, for use in the manufacture of radio broadcast receivers and sound recorders or reproducers (a)	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)
ex 8541 40 10	Assembly consisting of not more than 10 light-emitting diodes (LEDs) made from a gallium-based semiconductor compound, mounted in a rectangular housing the exterior dimensions of which do not exceed $68 \times 25 \times 4$ mm, with not more than 20 connecting pins, and bearing: — an identification marking consisting of or including the following combination of figures and letters: LT 9355 or — other identification markings relating to devices complying with the abovementioned description, for use in the manufacture of radio broadcast receivers and sound recorders or reproducers (a)	0
ex 8541 40 10	Laser diode with one photodiode, emitting light of a nominal wavelength of 780 nm, contained in a housing having a diameter of not more than 10 mm and a height of not more than 7 mm, with three connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: LT 022 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8541 40 10 ex 8542 20 00	Digital display of a size not exceeding 25×35 mm, consisting of a printed circuit board on which are mounted, under a plastic cover, up to 22 light-emitting diodes manufactured from gallium-based semiconductor compounds. Each display consists of a single character with or without a plus or minus sign and/or one or two dots	7
ex 8541 40 10 ex 8542 20 00	Digital displays, consisting of a printed circuit board of a size not exceeding 35×90 mm with a single line of characters, not less than three in number, comprising light-emitting diodes made from gallium-based semiconductor compounds mounted thereon. Each character is composed of up to eight segments with or without a decimal point and the line of characters has a protective cover of plastic	0
ex 8542 40 91	Module of not more than five solar cells of thin-film technology, on a substrate the exterior dimensions of which do not exceed 70×18 mm	0
ex 8541 40 93	Opto-electronic circuit consisting of one or more light-emitting diodes and one or more photodiodes with amplifier circuit, contained in a plastic housing with not more than 16 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HC PL 2400 HC PL 5700 HC PL 5730 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8541 60 00	Quartz crystal oscillating at a frequency of 32 768 Hz, contained in a cylindrical housing of a length not exceeding 8,2 mm and a diameter not exceeding 3,2 mm, for the manufacture of products falling within Chapter 91 (a)	0
ex 8541 60 00	Polarized ceramic piezo-electric crystals oscillating in a frequency range of not less than 500 and not more than 12 500 kHz, contained in a housing the exterior dimensions of which do not exceed 14×15 mm, with not more than three connecting pins	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)												
ex 8542 11 30	Electrically erasable, programmable read-only memories (so-called E ² PROMs), in the form of an unmounted monolithic integrated circuit (chip) with a storage capacity of 16 Kbits, used in the manufacture of microwave systems for the identification of persons and objects (a)	0												
ex 8542 11 71	Write buffer memory, of C-MOS technology, with an organization of 4 × 16 bits comprising eight bits of address and eight bits of data, and four-bit parity in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 68 connecting pins, and bearing: — an identification marking consisting of or including the following combination of figures and letters: R 2020/16 or — other identification markings relating to devices complying with the abovementioned descriptions	0												
ex 8542 11 71	Static random-access memories of C-MOS technology (C-MOS S-RAMs), in the form of a monolithic integrated circuit with a storage capacity of 16 × 4 bits, an access time not exceeding 35 ns, contained in a housing the exterior dimensions of which do not exceed 9 × 21 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CY7C189 CY7C190 CY74S189 CY54S189 CY27S03 CY27S07 or — other identification markings relating to devices complying with the abovementioned description	0												
ex 8542 11 71	Static random-access memories of C-MOS technology (C-MOS S-RAMs), with a storage capacity of 256 × 4 bits and an access time not exceeding 60 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 12 × 29 mm, with not more than 22 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CY7C122 CY 93422 CY93L422 or — other identification markings relating to devices complying with the abovementioned description	0												
ex 8542 11 71	Static random-access memory of C-MOS technology (C-MOS S-RAM), with a storage capacity of 2 K × 8 bits and with a nominal standby power of not more than 0,005 mW at 25 °C, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: <table> <tr> <td>TC5516APL-2</td><td>TC5517CPL-15</td><td>TC5517BPL-20</td></tr> <tr> <td>TC5516AFL-2</td><td>TC5517CPL-20</td><td>TC5517BPL-25</td></tr> <tr> <td>TC5516APL</td><td>TC5517CFL-15</td><td>TC5517BFL-20</td></tr> <tr> <td>TC6516AFL</td><td>TC5517CFL-20</td><td>TC5517BFL-25</td></tr> </table> or — other identification markings relating to devices complying with the abovementioned description	TC5516APL-2	TC5517CPL-15	TC5517BPL-20	TC5516AFL-2	TC5517CPL-20	TC5517BPL-25	TC5516APL	TC5517CFL-15	TC5517BFL-20	TC6516AFL	TC5517CFL-20	TC5517BFL-25	7
TC5516APL-2	TC5517CPL-15	TC5517BPL-20												
TC5516AFL-2	TC5517CPL-20	TC5517BPL-25												
TC5516APL	TC5517CFL-15	TC5517BFL-20												
TC6516AFL	TC5517CFL-20	TC5517BFL-25												

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)																																																				
ex 8542 11 71	Non-volatile memory consisting of a C-MOS S-RAM, with a capacity of 16 Kbits and internal power supply, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 19 × 36 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: DS 1220 Y MK 48 Z 02 (B) or — other identification markings relating to devices complying with the abovementioned description	7																																																				
ex 8542 11 71	Static random-access memory of C-MOS technology (C-MOS S-RAM), with a storage capacity of 32 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: TC 5532 or — other identification markings relating to devices complying with the abovementioned description	0																																																				
ex 8542 11 71	Static random-access memories of MOS technology (MOS S-RAMs), with a storage capacity of 8 K × 8 bits with an access time of not less than 80 ns, in the form of a monolithic integrated circuit, contained in a plastic housing the exterior dimensions of which do not exceed 18 × 39 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: <table><tr><td>TC5564PL-15</td><td>HM6264P-10</td><td>MB8464A-10</td><td>PD4464C-15</td></tr><tr><td>TC5564PL-20</td><td>HM6264P-12</td><td>MB8464A-10L</td><td>PD4464C-20</td></tr><tr><td>TC5565PL-12</td><td>HM6264P-15</td><td>MB8464A-10LL</td><td>PD4464G-15</td></tr><tr><td>TC5565PL-15</td><td>HM6264LP-10</td><td>MB8464A-15</td><td>PD4464G-20</td></tr><tr><td>TC5565FL-12</td><td>HM6264LP-12</td><td>MB8464A-15L</td><td></td></tr><tr><td>TC5565FL-15</td><td>HM6264LP-15</td><td>MB8464A-15LL</td><td>MSM 5165AL-12</td></tr><tr><td>TC5565PL-12L</td><td></td><td>MB8464A-12</td><td>MSM 5165AL-15</td></tr><tr><td>TC5565PL-15L</td><td>HY6264P-15</td><td>MB8464-12L</td><td></td></tr><tr><td>TC5565FL-12L</td><td></td><td>MB8464-12LL</td><td></td></tr><tr><td>TC5565FL-15L</td><td>KM6264AL-10</td><td>MB8464-15</td><td></td></tr><tr><td>TMM2063P-10</td><td></td><td>MB8464-15L</td><td></td></tr><tr><td>TMM2063P-12</td><td></td><td>MB8464-15LL</td><td></td></tr><tr><td>TMM2063P-15</td><td></td><td></td><td></td></tr></table> or — other identification markings relating to devices complying with the abovementioned description	TC5564PL-15	HM6264P-10	MB8464A-10	PD4464C-15	TC5564PL-20	HM6264P-12	MB8464A-10L	PD4464C-20	TC5565PL-12	HM6264P-15	MB8464A-10LL	PD4464G-15	TC5565PL-15	HM6264LP-10	MB8464A-15	PD4464G-20	TC5565FL-12	HM6264LP-12	MB8464A-15L		TC5565FL-15	HM6264LP-15	MB8464A-15LL	MSM 5165AL-12	TC5565PL-12L		MB8464A-12	MSM 5165AL-15	TC5565PL-15L	HY6264P-15	MB8464-12L		TC5565FL-12L		MB8464-12LL		TC5565FL-15L	KM6264AL-10	MB8464-15		TMM2063P-10		MB8464-15L		TMM2063P-12		MB8464-15LL		TMM2063P-15				0
TC5564PL-15	HM6264P-10	MB8464A-10	PD4464C-15																																																			
TC5564PL-20	HM6264P-12	MB8464A-10L	PD4464C-20																																																			
TC5565PL-12	HM6264P-15	MB8464A-10LL	PD4464G-15																																																			
TC5565PL-15	HM6264LP-10	MB8464A-15	PD4464G-20																																																			
TC5565FL-12	HM6264LP-12	MB8464A-15L																																																				
TC5565FL-15	HM6264LP-15	MB8464A-15LL	MSM 5165AL-12																																																			
TC5565PL-12L		MB8464A-12	MSM 5165AL-15																																																			
TC5565PL-15L	HY6264P-15	MB8464-12L																																																				
TC5565FL-12L		MB8464-12LL																																																				
TC5565FL-15L	KM6264AL-10	MB8464-15																																																				
TMM2063P-10		MB8464-15L																																																				
TMM2063P-12		MB8464-15LL																																																				
TMM2063P-15																																																						
ex 8542 11 71	Non-volatile memory consisting of a static read/write random access memory of C-MOS technology (C-MOS S-RAM), with a storage capacity of 64 Kbits and an internal energy source, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 20 × 42 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: DS 1225 Y or — an identification markings relating to devices complying with the abovementioned description	0																																																				

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 71	Static random access memories (S-RAMs) of C-MOS technology, with a storage capacity of 256 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 39 × 17 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HM 62256, PD 43256 C, TC 55257 P - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Non-volatile memory consisting of a static C-MOS random-access memory, with a storage capacity of 256 Kbits and built-in energy source, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 19 × 40 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: DS 1230 DS 1235 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Static random-access memories of N-MOS (including H-MOS) technology (N-MOS S-RAMs), with a storage capacity of 256 × 4 bits with an access time not exceeding 25 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 9122 - 25 91 L 22 - 25 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Static random-access memories of N-MOS (including H-MOS) technology (N-MOS S-RAMs), with a storage capacity of 8 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 4008 8112 4118 8114 4801 8185 8104 PD 421 8108 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Static read/write random-access memories of N-MOS (including H-MOS) technology (N-MOS S-RAMs), with a storage capacity of 72 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 10 × 39 mm, with not more than 28 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 71 (cont'd)	— an identification marking consisting of or including the following combination of figures and letters: TMM 2089 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Static random-access memories (S-RAMs) of MOS technology, with a storage capacity of 1 K × 4 bits and access time not exceeding 25 ns, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 8 × 32 mm, with not less than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AM 9150-20 CY 7 C 150-15 AM 9150-25 CY 7 C 150-25 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Static random-access memories of bipolar technology (bipolar S-RAMs), with a storage capacity of 64 × 9 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 40 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 82 S 09 MBM 93419 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Static random-access memories of bipolar technology (bipolar S-RAMs) consisting of a substrate layer on which are mounted either one or two chips each having a storage capacity of 1 Kbit, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 13 × 13 mm, with not more than 23 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 770639 770823 5120360 7379769 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Static random-access memories of TTL technology (TTL S-RAMs), with a storage capacity of 1 Kbit and an access time not exceeding 45 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 30 mm, with not more than 22 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 93422 93425 - or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 71	Dynamic FIFO (first in, first out) read/write memory, of N-MOS (including H-MOS) technology, with a storage capacity of 7 280 or 9 080 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 12 × 36 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: PD 41101 PD 41102 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Dynamic random-access memories of C-MOS technology (C-MOS D-RAMs), with a storage capacity of 256 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 34 mm, with not more than 20 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HM 50256 53 C 256 53 C 464 P 51 C 256 53 C 258 53 C 466 P 51 C 259 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Dynamic read/write random-access memory of N-MOS (including H-MOS) technology (N/H-MOS D-RAM) with a storage capacity of 64 Kbit, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 22 × 7 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: KM 4164 MN 4264 or — other identification markings relating to devices complying with the abovementioned description	10
ex 8542 11 71	Dynamic random-access memories (D-RAMs), of N-MOS (including H-MOS) technology, with a storage capacity of 256 Kbits and an access time not exceeding 150 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 34 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HM 50256 PD 41254 HM 50464 PD 41256 PD 41464 MB 81256 MB 81464 TMM 41464 TMS 4464 MSM 4256 MSM 4464 or — other identification markings relating to devices complying with the abovementioned description	10

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 71	Dual port dynamic random-access memory (D-RAM) of N-MOS (including H-MOS) technology, with data registers and a serial read output control, with a storage capacity of 256 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 13 × 39 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: MB 81461 PD 41264 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Random-access memories of ECL technology (ECL-RAMs) with a storage capacity of 256 × 4 bits, and the access time not exceeding 8 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 11 × 32 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures: 10422 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Random-access memories of ECL technology (ECL-RAMs) with a storage capacity of 4 Kbits and an access time not exceeding 50 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 11 × 32 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 10470 10474 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Random-access memories of ECL technology (ECL-RAMs) with a storage capacity of 16 Kbits and an access time not exceeding 15 ns in the form of a monolithic integrated circuit, contained in a housing the dimensions of which do not exceed 18 × 37 mm, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures: 10480 10484 100484 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Random-access memories of ECL technology (ECL-RAMs) with a storage capacity of 64 Kbits in the form of a monolithic integrated circuit, contained in a housing the dimensions of which do not exceed 10 × 29 mm, with not more than 22 connecting pins or contact areas and bearing:	

CN code	Description	Rate of autonomous duty (%)																
ex 8542 11 71 (cont'd)	— an identification marking consisting of or including the following combination of figures: 10490 or — other identification markings relating to devices, complying with the abovementioned description	0																
ex 8542 11 71	Dynamic read/write random-access memories manufactured in N-MOS (including H-MOS) technology (D-RAMs), consisting of a substrate layer with not less than two and not more than eight chips having a storage capacity of 128, 192 or 256 Kbits and a storage capacity of not less than 256 Kbits and not more than two megabits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm, with not more than 57 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: <table><tr><td>6025841</td><td>6031587</td><td>6870392</td><td>7379172</td></tr><tr><td>6025843</td><td>6031591</td><td>6870393</td><td>7379174</td></tr><tr><td>6025856</td><td></td><td>6870395</td><td>7379176</td></tr><tr><td>6025858</td><td></td><td></td><td>7379181</td></tr></table> - or — other identification markings relating to devices complying with the abovementioned description	6025841	6031587	6870392	7379172	6025843	6031591	6870393	7379174	6025856		6870395	7379176	6025858			7379181	0
6025841	6031587	6870392	7379172															
6025843	6031591	6870393	7379174															
6025856		6870395	7379176															
6025858			7379181															
ex 8542 11 71	Read-only memory in C-MOS technology (C-MOS ROM) with a storage capacity of 256 Kbits and a standby current of not more than 0,03 mA, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 17 × 50 mm, with not more than 54 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HN 61256 HN 613256 MB 83256 or — other identification markings relating to devices complying with the abovementioned description	7																
ex 8542 11 71	Read-only memory of C-MOS technology (C-MOS ROM) with a storage capacity of one megabit, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HN 62301 P MB 83 1000 MB 83 1124 TC 53 1000 P or — other identification markings relating to devices complying with the abovementioned description	7																
ex 8542 11 71	Programmable, non-erasable, read-only memories (PROMs) of Schottky TTL technology, with a storage capacity of 2 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 24 connecting pins or contact areas, and bearing:																	

CN code	Description	Rate of autonomous duty (%)																																																												
ex 8542 11 71 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures or figures and letters: <table><tr><td>27 S 12</td><td>5305</td><td>6305</td><td>76 LS 03</td></tr><tr><td>27 S 13</td><td>5306</td><td>6306</td><td>7620 —</td></tr><tr><td></td><td>5308</td><td>6308</td><td>7621</td></tr><tr><td>28 L 22</td><td>5309</td><td>6309</td><td></td></tr><tr><td>28 LA 22</td><td>53 S 240</td><td>63 S 240</td><td>82 S 114</td></tr><tr><td>28 L 2 XMFC</td><td>53 S 241</td><td>63 S 241</td><td>82 S 130</td></tr><tr><td></td><td></td><td>6335</td><td>82 S 131</td></tr><tr><td>29613</td><td>54 S 570</td><td>6336</td><td></td></tr><tr><td>29770</td><td>54 S 571</td><td></td><td>93436</td></tr><tr><td>29771</td><td></td><td>7053</td><td>93446</td></tr><tr><td></td><td>5604</td><td>7058</td><td></td></tr><tr><td>38510</td><td>5624</td><td></td><td>MB 7115</td></tr><tr><td></td><td></td><td>74 S 570</td><td>MB 7116</td></tr><tr><td></td><td></td><td>74 S 571</td><td>MB 7117</td></tr><tr><td></td><td></td><td></td><td>MB 7118</td></tr></table> or — other identification markings relating to devices complying with the abovementioned description	27 S 12	5305	6305	76 LS 03	27 S 13	5306	6306	7620 —		5308	6308	7621	28 L 22	5309	6309		28 LA 22	53 S 240	63 S 240	82 S 114	28 L 2 XMFC	53 S 241	63 S 241	82 S 130			6335	82 S 131	29613	54 S 570	6336		29770	54 S 571		93436	29771		7053	93446		5604	7058		38510	5624		MB 7115			74 S 570	MB 7116			74 S 571	MB 7117				MB 7118	0
27 S 12	5305	6305	76 LS 03																																																											
27 S 13	5306	6306	7620 —																																																											
	5308	6308	7621																																																											
28 L 22	5309	6309																																																												
28 LA 22	53 S 240	63 S 240	82 S 114																																																											
28 L 2 XMFC	53 S 241	63 S 241	82 S 130																																																											
		6335	82 S 131																																																											
29613	54 S 570	6336																																																												
29770	54 S 571		93436																																																											
29771		7053	93446																																																											
	5604	7058																																																												
38510	5624		MB 7115																																																											
		74 S 570	MB 7116																																																											
		74 S 571	MB 7117																																																											
			MB 7118																																																											
ex 8542 11 71	Programmable non-erasable read-only memories (PROMs) of MOS technology, with a storage capacity of 16 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 39 × 17 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 7 C 245 7 C 291 7 C 292 HM 6616 or — other identification markings relating to devices complying with the abovementioned description	0																																																												
ex 8542 11 71	Programmable non-erasable read-only memories (PROMs) of bipolar technology with a storage capacity of 16 Kbits and a standby current equal to, or of more than, 50 mA and less than, or equal to, 80 mA in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 33 × 14 mm, with not more than 24 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: 27 PS 191 A or — other identification markings relating to devices complying with the abovementioned description	0																																																												
ex 8542 11 71	Programmable non-erasable read-only memories (PROMs) with a storage capacity of 32 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 63 S 3281 AM 27 S 43 MB 7141 MB 7142 or — other identification markings relating to devices complying with the abovementioned description	0																																																												

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 71	Programmable non-erasable read-only memory (PROM) having a storage capacity of 64 Kbits and an access time of not more than 65 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 44 mm, with a maximum of 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CY 7C 261 CY 7C 263 CY 7C 264 CY 7C 268 CY 7C 269 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	UV-erasable, programmable, read-only memories (EPROMs) with a storage capacity of 2 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with a quartz window on the upper surface and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 82140 PP AMI 702 ADC - or — other identification markings relating to EPROMs complying with the abovementioned description	4
ex 8542 11 71	UV-erasable, programmable, read-only memory (EPROM) equipped with a programmable input/output system, with a storage capacity of 2 K × 8 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 52 mm, with a quartz window on the upper face and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: D 8755 A TMP 8755 AC - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	UV-erasable programmable read-only memory (EPROM) having a storage capacity of 16 Kbits and an access time of not more than 65 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with a quartz window on its upper surface, and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CY 245 W CY 7C 291 W - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	UV-erasable programmable read-only memory (EPROM) having a storage capacity of 64 Kbits and an access time of not more than 65 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with a quartz window on its upper surface, and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CY 7C 261 W CY 7C 263 W CY 7C 268 W CY 7C 269 W - or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 71	Electrically erasable, programmable, read-only memories (E²PROMs) with a storage capacity of 4 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 28 C 04 X 2404 X 24 C 04 X 2804 A - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Electrically erasable, programmable, read-only memories (E²PROMs) with a storage capacity of 64 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 28 C 64 52 B 33 52 B 33 H MBM 28 C 65 MCM 2864 X 2864 A - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Electrically erasable, programmable, read-only memories (E²PROMs) with a storage capacity of 128 Kbits, in the form of a monolithic circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: X 28128 A - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Electrically erasable, programmable, read-only memories (E²PROMs) with a storage capacity of 256 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 28256 28 C 256 48 C 256 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Static random-access memory (S-RAM) with a storage capacity of 256 bits superimposed bit-for-bit on an electrically erasable, programmable, read-only-memory (E²PROM), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8 × 24 mm, with not more than 18 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 71 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures and letters: X 2210 X 2443 X 2444 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Static random-access memory (S-RAM) with a storage capacity of 1 Kbit, superimposed bit-for-bit on an electrically erasable, programmable, read-only memory (E²PROM), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: X 2001 X 2201 A X 2212 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Static random-access memory (S-RAM) with a storage capacity of 2 Kbits, superimposed bit-for-bit on an electrically erasable, programmable, read-only memory (E²PROM), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of the following combination of figures and letters: X 2002 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 71	Static random-access memory (S-RAM) with a storage capacity of 4 Kbits, superimposed bit-for-bit on an electrically erasable, programmable, read-only memory (E²PROM), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of the following combination of figures and letters: X 2004 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	Single-chip microcomputer of C-MOS technology, consisting of an arithmetical logic unit (ALU) with an organization of four bits, a read-only memory (ROM) with a storage capacity of 2 K × 8 bits, a dual-tone, multi-frequency (DTMF) generator, a random access memory (RAM) with a storage capacity of 1 Kbit, whether or not with another random access memory (RAM) with a storage capacity of 512 bits, in the form of a monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 16 × 54 mm, with not more than 42 connecting pins and bearing: — an identification marking consisting of one of the following combinations of figures and letters: T 6978 TCM 8301 TCM 8302 - or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 75	4-bit single-chip microcomputers of C-MOS technology, consisting of a read-only memory (ROM) with a capacity of 16 Kbits and a random-access memory (RAM) with a capacity of not more than 1 536 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 39 mm, with not more than 67 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: TMP 47 C 200 TMP 47 C 220 TMP 47 C 221 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	4-bit single-chip microcomputers of C-MOS technology, consisting of a read-only memory (ROM) with a capacity of 4 K × 8 bits, random-access memories (RAM) with a total capacity of 3 Kbits, a DMTF-generator, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 16 × 54 mm, with not more than 42 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: TMP 47 C 452 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	8-bit single-chip microcomputer of C-MOS technology consisting of a random access memory with a storage capacity of 2 Kbits, a programmable read-only memory with a storage capacity of 64 Kbits and a multi-protocol serial communication port, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 63 × 52 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: 80 C 152 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	32-bit single-chip microcomputer in C-MOS-technology, in the form of a monolithic integrated circuit consisting of a ROM with a capacity of 24 Kbits and a RAM with a capacity of 2 Kbits, contained in a housing the exterior dimensions of which are not less than 30 × 30 mm, with not less than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: MB 8764 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)																																				
ex 8542 11 75	8-bit single-chip microcomputer of N-MOS (including H-MOS) technology, having universal peripheral interface functions, consisting of a random access read-write memory (RAM) with a storage capacity of 2 Kbit, a non-erasable, programmable read-only memory (PROM) or a UV-erasable, programmable read-only memory (EPROM) with a storage capacity of 16 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 53 mm, with not more than 44 connecting pins or 44 contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures: 8042 8742 or — other identification markings relating to devices complying with the abovementioned description	0																																				
ex 8542 11 75	32-bit single-chip microcomputers of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit consisting of 24 registers of 32 bits and a RAM with a capacity of 2 Kbits, contained in a housing the exterior dimensions of which do not exceed 24 × 24 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: HGC 6127 or — other identification markings relating to devices complying with the abovementioned description	0																																				
ex 8542 11 75	8-bit single-chip microcomputer of MOS technology, having universal peripheral interface functions, consisting of a central processing unit, a random access read-write memory (RAM) with a storage capacity of 1 Kbit, UV-erasable, programmable read-only memory (EPROM) with a storage capacity of 2 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 53 mm, having a quartz window on the upper face, with not more than 44 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: D 8742 or — other identification markings relating to devices complying with the abovementioned description	0																																				
ex 8542 11 75	4-bit single-chip microcomputers consisting of a read-only memory (ROM) with a capacity of not less than 18 Kbits and not more than 104 Kbits and a random-access memory (RAM) with a capacity of not less than 512 bits and not more than 4 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 20 × 60 mm, with not more than 80 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: <table><tr><td>CD 3200-3299</td><td>TP 0310-03299</td><td>HD 38800</td><td>HD 404 189</td></tr><tr><td></td><td>TP 0450-04599</td><td>HD 38820</td><td>HD 614 080</td></tr><tr><td>TMC 0270-0279</td><td>TP 0480-04899</td><td>HD 44796</td><td></td></tr><tr><td>TMC 0500-0599</td><td>TP 0500-05999</td><td>HD 44800</td><td></td></tr><tr><td>TMC 0980-0989</td><td>T 7767 BS</td><td>HD 44801</td><td></td></tr><tr><td>TMC 1500-1599</td><td></td><td>HD 44820</td><td></td></tr><tr><td>TMC 1980-1999</td><td></td><td>HD 44840</td><td></td></tr><tr><td></td><td></td><td>HD 44860</td><td></td></tr><tr><td></td><td></td><td>HD 614042</td><td></td></tr></table> or — other identification markings relating to devices complying with the abovementioned description	CD 3200-3299	TP 0310-03299	HD 38800	HD 404 189		TP 0450-04599	HD 38820	HD 614 080	TMC 0270-0279	TP 0480-04899	HD 44796		TMC 0500-0599	TP 0500-05999	HD 44800		TMC 0980-0989	T 7767 BS	HD 44801		TMC 1500-1599		HD 44820		TMC 1980-1999		HD 44840				HD 44860				HD 614042		0
CD 3200-3299	TP 0310-03299	HD 38800	HD 404 189																																			
	TP 0450-04599	HD 38820	HD 614 080																																			
TMC 0270-0279	TP 0480-04899	HD 44796																																				
TMC 0500-0599	TP 0500-05999	HD 44800																																				
TMC 0980-0989	T 7767 BS	HD 44801																																				
TMC 1500-1599		HD 44820																																				
TMC 1980-1999		HD 44840																																				
		HD 44860																																				
		HD 614042																																				

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 75	8-bit single-chip microcomputer, consisting of an electronic, programmable, read-only memory (EPROM) UV-erasable with a capacity of 32 Kbits and a random access memory (RAM) with a capacity of 1 Kbit, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 53 mm, with a quartz window and not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 7742 8751 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	16-bit single-chip microcomputer, comprising a read-only memory (ROM) with a capacity of 64 Kbits, a random access memory (RAM) with a capacity of 2 Kbits, a digital / analogue converter with sample / hold, contained in a housing the exterior dimensions of which do not exceed 40 × 40 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures: 8397 or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 75	32-bit single-chip microcomputer, consisting of a read-only memory (ROM) having a storage capacity of 16 Kbits, random-access memories (RAM) having a total storage capacity of 32 Kbits a floating decimal point arithmetical unit with a capacity of 32 bits in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 30 × 53 mm, with not more than 100 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: DSP 32 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	8-bit microprocessor of C-MOS technology, consisting of a central processing unit (CPU), a memory controller, a two-channel DMA controller, two-channel programmable 16-bit counter/timer, a wait-state generator, a two-channel asynchronous serial communication interface (ASCI) and a bus controller, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 62 × 26 mm, with not more than 80 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: Z 64180 HD 64 A 180 HD 64 B 180 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	16-bit microprocessor of C-MOS technology, consisting of a central processing unit (CPU) and an 8-bit or 16-bit external data bus, contained in a housing the exterior dimensions of which do not exceed 54 × 16 mm, with not more than 40 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 75 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures and letters: Z 70108 Z 70116 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	16-bit microprocessor of C-MOS technology, consisting of a central processing unit (CPU), a memory controller, a 2 Kbit cache memory, three programmable 16-bit counter/timers, a full duplex universal asynchronous receiver/transmitter (UART) and four DMA channels, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 26 × 26 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: Z 280 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	32-bit microprocessor of C-MOS technology, with an external data bus of 32 bits and an external address bus of 32 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 45 × 45 mm, with not more than 175 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 80386 MC 68020 NS 32532 MC 68030 NS 32C032 MC 68032 R 2000/16 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	8-bit microprocessor of N-MOS (including H-MOS) technology, for the encoding/decoding of data (data ciphering processor), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 53 × 15 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: Z 8068 Z 9518 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	8-bit microprocessor of N-MOS (including H-MOS) technology with 16 bit internal architecture, in the form of a monolithic integrated circuit consisting of a central processing unit (CPU), a timing generator, two independent DMA channels, a programmable interrupt controller, three programmable 16-bit timers, programmable memory and peripheral chip select, a programmable wait state generator and a local bus controller, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm with not more than 68 connecting pins or contact areas, and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 75 (cont'd)	— an identification marking consisting of or including the following combination of figures: 80188 - or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 75	16-bit microprocessor in N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit, consisting of a central processing unit (CPU), a timing generator, two independent DMA channels, a programmable interrupt controller, three programmable 16-bit timers, programmable memory and external chip selection logic, a programmable wait state generator with bus control unit, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures: 80186 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	16-bit microprocessor of N-MOS technology (including H-MOS) consisting of a central processing unit (CPU), a memory management and protection unit (MMU) and a real address and virtual address operating mode system (OSO), in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 30 × 30 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures: 80286 - or — other identification markings relating to devices complying with the abovementioned description	10
ex 8542 11 75	32-bit microprocessor of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 38 × 38 mm, with not more than 132 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: NCR 32000 NS 32032 NS 32332 CPU 0404 1871 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	16-bit microprocessor of bipolar technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 25 × 82 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AM 29116 SBP 9989 - or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 75	Central processing unit of N-MOS (including H-MOS) technology (N-MOS CPU), consisting of one 16 × 16-bit service memory, one 16 × 20-bit service memory, one 32 × 32-bit service memory, one 8 × 8-bit service memory, one 16-bit register, two 20-bit registers, one 8-bit register, one 12-bit register, one 5-bit counter and timing network, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 25 × 25 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: LSI-604041855 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	Numeric processor extension unit of N-MOS (including H-MOS) technology (N-MOS NPX) containing not more than 14 registers, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 53 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 80287 8087 NS 32081 TX 32081 W - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	Floating-point arithmetic co-processor of MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 30 × 53 mm, with not more than 84 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 80387 NCR 32020 MC 68881 NS 32381 MC 68882 R 2010/16 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	Text co-processor, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 25 × 25 mm, with not more than 68 connecting pins, and bearing: — an identification marking consisting of or including the following combination of figures and letters: C 82730 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 75	16-bit communications processor of N-MOS (including H-MOS) technology, consisting of a random access memory (RAM) with a storage capacity of 22 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 15 × 60 mm, with not more than 48 connecting pins of contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: TMS 38010 - or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Arithmetic-logic unit of N-MOS (including H-MOS) technology, consisting of one 32-bit register, one 24-bit register, one 4-bit register, 12 1-bit registers, two 16 × 24-bit service memories, one logic network performing arithmetic and logic operations, decodifying logic, and error detection and management logic, one 8-bit counter and a timing network, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 23 × 82 mm, with not more than 64 connecting pins and bearing: — the identification marking: ALU 0486 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Logic circuit of N-MOS (including H-MOS) technology (N-MOS LC) serving as a clock generator for central process unit, main memory and input/output interfaces, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 25 × 25 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: H 108982 (MCC) - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Clock generator and controller for microprocessors, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 24 × 9 mm, with not more than 20 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: Z 8581, 8284, 82 C 84, 82 C 284, 82384, 82284, 82304 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Clock generator for a graphics controller in the form of a monolithic integrated circuit of C-MOS technology contained in a housing the exterior dimensions of which do not exceed 20 × 7 mm with 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figure and letters: PCLK 1 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Logic circuit of bipolar technology, with not more than six logic functions, a supply voltage of not less than 11 V and not more than 18 V, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8 × 23 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: FZH 101 A FZH 111 A FZH 191 FZH 201 FZJ 121 FZK 101 - or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Logic control circuits of N-MOS (including H-MOS) technology, consisting of one 7-bit register, three timers, one multiplexer, sequential and combining networks intended to perform control operations, decoding logic, error detection and management logic and a timing network, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 23×82 mm, with not more than 64 connecting pins and bearing: — the identification marking: MIC 0482 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Semi-custom logic array (gate array) of C-MOS technology with metal gates, with an operating voltage of 12 volts, with not less than 637 two-input functions, having within the array a digital code produced by an electron beam, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 29×11 mm, with not more than 22 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: FB 215 or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 91	Field programmable array logics (PALs) of C-MOS-technology, a programmable AND array, fixed OR array, not more than 32 inputs and not more than 12 outputs, whether or not with registers, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 19×39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 16 P 8 16 RP 4 C 16 L 8 C 16 R 4 C 16 R 6 C 16 R 8 C 20 G 10 C 22 V 10 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Programmable, non-erasable, logic circuits (field programmable logic array) of TTL Schottky technology, with not more than 48 AND functions, not more than eight OR functions, and not more than 16 inputs, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17×39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: FP 54 AS 839 FP 74 AS 839 82 S 100 FP 54 AS 840 FP 74 AS 840 82 S 101 SN 54 LS 333 SN 74 LS 333 SN 54 LS 334 SN 74 LS 334 93458 SN 54 LS 335 SN 74 LS 335 93459 SN 54 LS 336 SN 74 LS 336 or — other identification markings relating to devices complying with the abovementioned description	5

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Non-erasable user-programmable logic sequencer of bipolar technology, having not more than 48 AND functions, a 6-bit state register, an 8-bit output register, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17×39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 82 S 105 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	UV-erasable programmable logic device (EPLD) of C-MOS technology containing not less than 600 logic gates, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 29×124 mm, with a quartz window on the upper surface, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: EP 600 16 L 8-W 16 R 4-W 16 R 6-W 16 R 8-W 22 V 10-W - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Error detection and correction circuit of N-MOS (including H-MOS) technology capable of detecting and correcting single bit errors and detecting all double bit errors, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 30×30 mm, with not more than 68 contact areas and bearing: — an identification marking consisting of or including the following combination of figures: 8206 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Burst error processor (BEP) of N-MOS (including H-MOS) technology for detecting and correcting multiple errors derived from a line of magnetic disks, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16×54 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: Z 8065 AM 9520 AM 9521 - or — any other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Error correction and detection unit (ECDU) of bipolar technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16×62 mm, with not more than 48 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures or figures and letters: 2960 74 F 630 74 F 631 74 LS 630 74 LS 631 DP 8400 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	CPU controller, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 100 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 82 C 201 82230 82 C 221 FE 2000 82231 FE 2010 FE 3000 FE 3010 L 1 A 0392 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control and interface circuit for peripherals, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 132 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures or figures and letters: 82 C 206 82 C 226 82306 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Hard-disc controller of MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 31 × 53 mm, with not more than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 1454-001 HDC 9224 PD 7261 WD 1010 WD 2010 WD 42 C 22 WD 5010 WD 5011 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Floppy-disc controller of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 62 mm, with not more than 48 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of letters and figures: FE 2100 G 70360-33 L 1 A 0519 MB 89311 WD 16 C 92 WD 37 C 65 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	4-channel read/write monolithic integrated circuit of bipolar technology for controlling magnetic heads in hard-disk units, contained in a housing whose exterior dimensions do not exceed 12 × 19 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: SSI 510 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus controller of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 100 connecting pins and bearing: — an identification marking consisting of or including one of the following combination of figures or figures and letters: 82 C 301 82 C 88 82 C 211 82 C 288 82 308 82 309 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Buffer manager and controller of C-MOS technology in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: WD 11 C 00-22 WD 83 C 580 WD 83 C 583 WD 12 C 00-22 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Buffer manager and controller of N-MOS (including H-MOS) technology in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 54 × 17 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: WD 1015 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Control circuit of C-MOS technology for the control of S/RAMs, capable of multiplexing addresses and generating pulses, and for the sequential control of data for the peripheral magnetic unit/rigid disk interface, and memory control, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm, with not more than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of letters and figures: OMTI 5055 (OMTI 20513) - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit for static memory control (S-RAM), of MOS technology, with address multiplexing and pulse generation facility, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 28 × 54 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AIC 300 OMTI 506 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Dynamic random access memory controller of N-MOS (including H-MOS) technology (N-MOS D-RAM controller) capable of multiplexing addresses and generating timing, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 17 × 62 mm, with not more than 48 connecting pins or 52 contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: C 8208 THCT 4502 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit of bipolar technology for the control of dynamic random-access memories (D-RAMs), capable of multiplexing addresses and generating timing, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 62 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: DP 8408 DP 8428 DP 8409 DP 8429 MB 1422 SN 74 S 409 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Memory control circuit of C-MOS technology, in the form of a monolithic integrated digital circuit, contained in a housing the dimensions of which do not exceed 36 × 36 mm, with not more than 144 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91 (cont'd)	— an identification marking either consisting of or including one of the following combination of figures and letters: 82 C 302 82 C 202 82 C 212 82 C 222 82 C 322 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Memory management unit of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the dimension of which do not exceed 36 × 36 mm, with not more than 132 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: MC 68851 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Memory management unit of N-MOS (including H-MOS) technology (N-MOS MMU) with a maximum addressing capacity of 4 Gbytes, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 36 × 82 mm, with not more than 132 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 68451 TX 32082 W NS 32082 NS 32382 0404 1872 - or — other identification markings relating devices complying with the abovementioned description	0
ex 8542 11 91	Sequence control circuit of N-MOS (including H-MOS) technology, consisting of one 32-bit register, three 16-bit registers, one 16 × 16-bit service memory, one 7 × 17-bit last-in-first-out (LIFO) memory, one adder circuit, decodifying logic, priority logic, error detection and management logic, one 16-bit multiplexer, one 8-bit counter and a timing network, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 23 × 82 mm, with not more than 64 connecting pins and bearing: — the identification marking: CSS 0484 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Input-output circuit of N-MOS (including H-MOS) technology for data control equipped with a timing control with a static random-access memory (S-RAM) with a capacity of 128 × 8 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 54 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 6532 CO 10750 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Sequential data control circuit of MOS technology for interface between a hard-disk memory unit and the memory control unit, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 28 × 54 mm, with not more than 68 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)																					
ex 8542 11 91 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures and letters: AIC 010 AIC 100 OMTI 505 or — other identification markings relating to devices complying with the abovementioned description	0																					
ex 8542 11 91	Status and shift control unit of bipolar technology in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 57 mm with not more than 42 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AM 2904 or — other identification markings relating to devices complying with the abovementioned description	0																					
ex 8542 11 91	Circuit of advanced low power Schottky (ALPS) technology for the asynchronous control of signal lines (bus) and the conversion of a local bus into a multiplexed bus (BAM), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 37 × 13 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures: 68452 or — other identification markings relating to devices complying with the abovementioned description	0																					
ex 8542 11 91	Contention resolving a local area network (LAN) controller, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 63 × 63 mm, with not more than 84 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: <table style="margin-left: 40px; border: none;"> <tr> <td style="padding-right: 20px;">8001</td><td style="padding-right: 20px;">MCM 68590</td><td>82590</td></tr> <tr> <td>8003</td><td>WD 2840</td><td>82592</td></tr> <tr> <td>82586</td><td>WD 80 C 24</td><td></td></tr> <tr> <td>82588</td><td>WD 83 C 503</td><td></td></tr> <tr> <td>AM 7990</td><td>WD 83 C 510</td><td></td></tr> <tr> <td>COM 9026</td><td>WD 83 C 603</td><td></td></tr> <tr> <td>DP 8390</td><td>WD 83 C 690</td><td></td></tr> </table> or — other identification markings relating to devices complying with the abovementioned description	8001	MCM 68590	82590	8003	WD 2840	82592	82586	WD 80 C 24		82588	WD 83 C 503		AM 7990	WD 83 C 510		COM 9026	WD 83 C 603		DP 8390	WD 83 C 690		0
8001	MCM 68590	82590																					
8003	WD 2840	82592																					
82586	WD 80 C 24																						
82588	WD 83 C 503																						
AM 7990	WD 83 C 510																						
COM 9026	WD 83 C 603																						
DP 8390	WD 83 C 690																						
ex 8542 11 91	Control circuit for data block transfer between dynamic memory and peripherals (DMA transfer controller or 'DTC'), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 63 × 35 mm, with not more than 133 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: <table style="margin-left: 40px; border: none;"> <tr> <td style="padding-right: 20px;">Z 8516</td><td style="padding-right: 20px;">82 C 223</td><td>HD 68450</td></tr> <tr> <td>Z 9516</td><td>82307</td><td>WE 32104</td></tr> </table> or — other identification markings relating to devices complying with the abovementioned description	Z 8516	82 C 223	HD 68450	Z 9516	82307	WE 32104	0															
Z 8516	82 C 223	HD 68450																					
Z 9516	82307	WE 32104																					

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Serial communication controllers of MOS technology, with two independent duplex channels with a capacity of 1,6 Mbits/sec or more but not exceeding 4 Mbits/sec, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 62 × 21 mm, with not more than 52 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: Z 80 C 30 PD 72001 Z 85 C 30 SNC 68562 Z 85 C 35 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit, of N-MOS (including H-MOS) technology, for data/address flows from the CPU, inputs/outputs and the main memory, in the form of a monolithic integrated circuit, contained in a housing whose dimensions do not exceed 36 × 36 mm, with not more than 132 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: CIM 1456 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Display controller and character generator (DCCG), of C-MOS technology, for liquid-crystal dot-matrix display system in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 24 × 26 mm, with not more than 80 connecting pins and bearing: — an identification marking consisting of or including one of the following combination of figures and letters: HD 61830 LH 5821 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Interpolation pulse generator, of C-MOS technology, for controlling geometrical functions, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: KM 3701 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Graphics controller of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 100 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: PEGA 82 C 431 82 C 435 82 C 441 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Graphic display controller (GDC) of N-MOS technology (including H-MOS), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 52 × 18 mm, with not more than 44 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: Z 7220 A 82720 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Video controller, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 15 × 52 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 38301-A L 1A 2099 PVC-2 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Monochrome display controller (MDC) of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 25 × 25 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 01-01.00 551 A or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Cathode-ray tube controller (CRTC) of C-MOS technology in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 32 × 62 mm, with not more than 100 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 82 C 434 V 6363 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Cathode-ray tube controller (CRTC) of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 62 × 25 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AM 8052 D 8275 H HD 6845 HD 68 A 45 P 8275 H or — other identification markings relating to devices complying with the abovementioned description	7

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Cathode-ray tube controller (CRTC) of bipolar technology, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 15 × 55 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: SCB 2675 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit for cathode-ray tubes or liquid-crystal displays (CRT and LCD controller) of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm, with not more than 84 connecting pins or contact areas, and bearing: — an identification marking consisting of or including the following combination of letters and figures: V 6355-DJ - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Programmable advanced video display controller (AVDC) of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit, contained in a housing whose external dimensions do not exceed 15 × 55 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: SCN 2674 - or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 91	Video gate arrays programmed to control graphics and memory, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 35 × 35 mm, with not more than 100 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of letters: PVGA - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Colour selection controller of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 19 × 52 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: 82 C 433 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Monolithic integrated circuit with at least 16 analogue switching elements, of C-MOS technology, for controlling signals in the range of 20 to 20 000 Hz, capable of dealing with signals up to 3 V with a distortion of not more than 0,05 % over the whole frequency range at a voltage of 1 V, contained in a housing the exterior dimensions of which do not exceed 16 × 40 mm, with not more than 42 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures and letters: TC 9164 N TC 9177 P TC 9184 P - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Analogue-digital monolithic circuit, capable of controlling brushless motors and keeping their speed constant, contained in a housing the exterior dimensions of which do not exceed 9 × 25 mm, with not more than 20 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: MGA 3015 A SSI 590 UC 1633 UC 1634 UC 3633 UC 3634 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Analogue-digital monolithic integrated circuit of bipolar technology, for damping the oscillations of stepping motors during the positioning phase, contained in a housing the exterior dimensions of which do not exceed 18 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of letters: STEDA - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Controller for servo-devices of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 54 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: KM 3702 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Four-channel control circuit of C-MOS technology, for maintaining a constant electromagnetic traction force with incorporated diodes and a storage capacity of 4 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 7 × 22 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: UCN 5813 - or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Eight-channel control circuit of C-MOS technology, for maintaining a constant electromagnetic traction force with incorporated diodes and a storage capacity of 8 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 9×28 mm, with not more than 22 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: UCN 5801 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit of TTL technology for the firing of magnetic print hammers, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8×23 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 801379-002 810751-001 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	8-bit (octal) dynamic memory bipolar driver, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16×33 mm, with not more than 20 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AM 2965 AM 2966 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Timing control unit (TCU) with two-phase cycle for central processing unit (CPU) and memory management unit (MMU), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16×33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: NS 32201 NS 32 C 201 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Interrupt control unit (ICU) with programmable priority of interrupts of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16×53 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: NS 32202 8259 A - or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Control circuit for bus interface of MOS technology functioning as an adaptor between the central unit and the external control units, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 63 × 26 mm, with not more than 68 connecting pins on contact areas and bearing: — an identification marking consisting of or including one of the following combinations of letters and figures: WD 33 C 93 NCR 5380 NCR 5381 NCR 53 C 80 NCR 53 C 90 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Interface and control circuit for Manchester-coded data, of Schottky technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8 × 14 mm, with not more than 20 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: TMS 38052 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit with a programmable data transfer rate, of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 27 × 27 mm, with not more than 100 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: TMS 38030 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Parallel communications interface of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 64 × 64 mm, with not more than 44 connecting pins or contact areas, and bearing: — an identification marking consisting of or including one of the following combination of figures and letters: PPC-1 82 C 55 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Serial and parallel interface bus circuit for communication between the central processing unit and a peripheral, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 26 × 26 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures: 1820-5022 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Subscriber line interface circuit (SLIC) with a high voltage rating of not less than 200 V, with direct internal relay drive, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: HC 5504 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Programmable communication interface of N-MOS (including H-MOS) technology (N-MOS PCI), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 8251 A - or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 91	Enhanced programmable communications interface (EPCI), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures: 2661 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Interface circuit for the synchronization of data flow from a hard-disk drive, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 35 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: DP 8462 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Analogue-digital monolithic integrated circuit of bipolar technology for interface signals between the peripheral hard-disk, memory unit and the central unit, contained in a housing the exterior dimensions of which do not exceed 15 × 50 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 581 C - or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Interface circuit of C-MOS technology for signals between peripheral hard-disk memory units and central units, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 28 × 53 mm, with not more than 80 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: OMTI 5080 (OMTI 20508) OMTI 5090 (OMTI 20509) WD 11 C 00 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Encoder/decoder serial interface circuit for hard-disk drives, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 37 mm, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AIC 250 AIC 270 DP 8463 B OMTI 5027 (OMTI 20527) OMTI 5070 (OMTI 20507) or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Serial interface, capable of implementing the data stream encoding, decoding and associated control functions for a local area network, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 8002 8023 82501 AM 7991 COM 9032 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Station digital interface circuit for parallel-to-serial or serial-to-parallel conversion of digital signals in telephone sets, of C-MOS technology (C-MOS STID), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins, and bearing: — an identification marking consisting of or including the following combination of figures and letters: WCC 295 G or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit in C-MOS technology, for the control of communication lines comprising a numerical bus, two independent receivers and a transmitter consisting of a first-in first-out (FIFO) memory, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 20 × 52 mm, with not more than 44 connecting pins or contact areas and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91 (cont'd)	— an identification marking consisting of or including the following combination of figures and letters: HS 3282 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus interface for graphic controllers, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of letters: PBI - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit of bipolar technology with 8-, 9- or 10-bit registers, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 9 × 34 mm, with not more than 24 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AM 29821 AM 29822 AM 29823 AM 29824 AM 29825 AM 29826 AM 29843 AM 29844 AM 29845 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Multiple bus interface circuit (multiple bus buffer) of low power Schottky technology for interfacing the error correction and detection unit system data bus and dynamic random-access memory (D-RAM), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 20 × 33 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AM 2961 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit of AS or ALPS technology, for the management of address signals, in the form of a monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 26 × 26 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 82 A 203 82 A 204 82 A 303 82 A 304 - or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Bus interface circuit of AS or ALPS technology, for the management of data flow in the signal lines of the CPU, in the form of a monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 26 × 26 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 82 A 205 82 A 305 82 A 436 82 A 442 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit of C-MOS technology, for the management of address signals, comprising a circuit with 4 × 2-input AND gates, two buffer circuits, two latch circuits, four independent transceivers, a 256 × 4-bit PROM, in the form of a monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 31 × 31 mm, with not more than 84 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: - FE 3020 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit C-MOS technology, for the management of I/O data flow in signal lines, with four independent transceivers, a circuit with 4 × 2-input NAND gates, a circuit with 4 × 2-input AND gates, a separator circuit, a flip-flop circuit, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 84 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: - FE 3030 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Computing unit without an internal programme sequencer for the multiplication or processing of fixed and floating point numbers, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 42 × 42 mm, with not more than 144 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: - ADSP 3210 - ADSP 3220 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	8 × 8-bit multiplier accumulator (MAC) of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 62 × 16 mm, with not more than 48 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 99 (cont'd)	— an identification marking consisting of or including the following combination of figures and letters: ADSP-1008 A - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Floppy-disk data separator (FDDS), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 27×8 mm, with not more than 20 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: FDC 9216 FDC 9216-B FDC 9229 T FDC 9229 BT WD 9216-00 WD 92 C 32 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Hard-disk data separator (HDDS), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16×37 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: DP 8460-2 DP 8460-3 DP 8460-4 DP 8465 HDC 9226 WD 10 C 20 WD 10 C 21 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Six- or eight-channel read/write signal generator for hard-disk drives, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 13×13 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: SSI 117 SSI 501 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Receiver/transmitter of Schottky technology, for Manchester-coded data, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 10×28 mm, with not more than 22 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: TMS 38051 - or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 99	Universal synchronous/asynchronous receiver/transmitter (USART) of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: MSM 82 C 51 - or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 99	Dual universal asynchronous receiver/transmitter (DUART) of MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 53 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: MC 2681 SCN 2681 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Programmable asynchronous communication element circuit of MOS technology, for the asynchronous transmission and reception of data, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 54 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: INS 8250 INS 82 C 50 NS 16450 NS 16550 NS 16 C 450 WD 8250 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Monolithic integrated circuit in N-MOS technology (including H-MOS) for the display of graphic symbols on a cathode-ray tube operating in stroke mode, contained in a housing the exterior dimensions of which do not exceed 28 × 61 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 96 114 898 96 114 899 96 149 135 FCD 28 042 277 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Sequential control and generating circuit of C-MOS technology for the memory display, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 19 × 52 mm, with not more than 44 connecting pins or contact areas and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 99 (cont'd)	— an identification marking consisting of or including the following combination of figures and letters: 82 C 432 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Demodulator/tone-decoder of bipolar technology for frequency decoding, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 10 × 21 mm, with not more than 14 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: XR 2211 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Encoder/decoder circuit of C-MOS technology, using Manchester code (MED) for the transmission of data in continuous flux with a repeater mode, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 33 mm, with not more than 20 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: HD 6409 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Data synchronizer and encoder/decoder of bipolar technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 13 × 13 mm, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures or letters: SSI 532 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Encoder/decoder of N-MOS (including H-MOS) technology, for the conversion of data into serial or parallel signals, consisting of an arithmetic logic unit (ALU) and a read-only memory (ROM) with a storage capacity of 128 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 15 × 60 mm, with not more than 48 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: TMS 38020 TMS 38021 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Pulse code modulation (PCM) codec of N-MOS (including H-MOS) technology, consisting of a sample and hold circuit digital-to-analogue converter, comparator, successive approximation register and logic function to interface to a full duplex PCM link, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 11 × 29 mm, with not more than 22 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 99 (cont'd)	— an identification marking consisting of or including the following combination of figures and letters: 2911 A-1 or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 99	Subscriber line audio-processing circuit (SLAC) with two digital signal processors, an analogue-to-digital converter and a digital-to-analogue converter, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17×39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AM 7901 AM 7905 or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 99	Analogue-to-digital signal converter, containing amplifiers, D/A and A/D converters with a supply voltage of $12 \text{ V} \pm 10\%$ and a digital serial interface with asynchronous receiver/transmitter, in the form of a monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 18×18 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 75002 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Quadruple digital-to-analogue converter, of C-MOS technology, with a capacity of 8 bits per channel, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16×39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: MP 7628 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	16-bit digital-to-analogue converter, of bipolar technology, with 16 parallel inputs, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17×39 mm, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: DAC 700 DAC 701 DAC 702 DAC 703 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Analogue-to-digital converter for the calculation of the average value of variable wave-forms, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18×10 mm, with not more than 14 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 99 (cont'd)	— an identification marking consisting of or including the following combination of figures and letters: AD 536 A - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	8-bit analogue-to-digital parallel converter, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 39 mm, with not more than 28 connecting pins or contact areas, and bearing: — an identification marking consisting of or including the following combinations of figures and letters: MP 7683 MP 7684 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	12-bit analogue-to-digital converter, incorporating a voltage reference and clock, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 36 × 15 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 574 A - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	12-bit analogue-to-digital converter, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 53 mm, with not more than 44 connecting pins or contact areas, and bearing: — an identification marking consisting of or including the following combinations of figures and letters: CS 5012 CSZ 5112 - or — other identification markings relating to devices circuits complying with the abovementioned description	0
ex 8542 11 99	14- or 16-bit analogue-to-digital converter of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 54 mm, with not more than 44 connecting pins or contact areas, and bearing: — an identification marking consisting of or including one the following combinations of figures and letters: CS 5014 CSZ 5114 CSZ 5316 CS 5016 CSZ 5116 CS 5501 CSZ 5126 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	7-channel analogue-to-digital converter with a capacity of 15 bits per channel, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 18 mm, with not more than 44 connecting pins or contact areas, and bearing: — an identification marking consisting of or including the following combination of figures and letters: MAX 133 - or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 99	Pulse code modulation (PCM) transmit/receive filter of N-MOS (including H-MOS) technology, consisting of two filters of a PCM line or trunk termination, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 10 × 21 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: D 2912 A - or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 99	Clock circuit of C-MOS technology, operating from a single 1,5 V power supply, with a liquid crystal display (LCD) driver, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 15 × 21 mm, with not more than 56 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: TC 8219 AF - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Clock/calendar circuit of C-MOS technology, incorporating a quartz crystal oscillator, independent timer recorders and a timer, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: MM 581 74 A MM 58167 58274 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Clock circuit of C-MOS technology, with audio and hour-count output, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: SVM 5530 7910 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Programmable interval timer of MOS technology (MOS PIT), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures: 8253 8254 82 C 54 - or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 99	Clock/calendar circuit of C-MOS technology incorporating a programmable generator for periodic interruptions and square waves, and a static random-access memory with a storage capacity of 400 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17×33 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: MC 146 818 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Clock circuit of C-MOS technology consisting of a 64-bit clock counter, a 64-bit state register, an oscillator and a control logic circuit for the reading and writing cycles, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 59×16 mm, with not more than 48 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: TOD 0815 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Function generator of bipolar technology for the generation of variable wave-forms, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 10×21 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: XR 2206 XR 8038 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Digital signal synthesizer of C-MOS technology with one frequency generator producing one signal and able to output one sound, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8×25 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: UMC 3511 A - or — other identification markings relating to devices complying with the abovementioned description	0
ex 85 42 11 99	Programmable digital signal synthesizer of C-MOS technology with 13 frequency generators each producing up to five sounds and an output capacity of up to 65 sounds, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 15×50 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: DPS 6401 - or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)												
ex 8542 11 99	Programmable digital signal synthesizer of C-MOS technology with 32 frequency generators to generate eight notes each and a simultaneous output of up to 160 notes, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 25 × 25 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of letters: MEG or — other identification markings relating to devices complying with the abovementioned description	0												
ex 8542 11 99	Signal synthesizer of N-MOS (including H-MOS) technology with a frequency generator, a memory of 15 instrumental tones, a digital-to-analogue converter and a quartz oscillator in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8 × 25 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: YM 2413 or — other identification markings relating to devices complying with the abovementioned description	0												
ex 8542 11 99	Phoneme speech synthesizer of C-MOS technology, with a supply current of less than 10 mA, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: <table border="0"> <tr> <td>CD 54121 N2L</td><td>CM 54104</td><td>SC 01</td></tr> <tr> <td>CD 54122 N2L</td><td>CM 54145 N2L</td><td>SSI 263</td></tr> <tr> <td>CD 54123 N2L</td><td>CM 54146 N2L</td><td></td></tr> <tr> <td>CD 54147 N2L</td><td>CM 54166 N2L</td><td></td></tr> </table> or — other identification markings relating to devices complying with the abovementioned description	CD 54121 N2L	CM 54104	SC 01	CD 54122 N2L	CM 54145 N2L	SSI 263	CD 54123 N2L	CM 54146 N2L		CD 54147 N2L	CM 54166 N2L		0
CD 54121 N2L	CM 54104	SC 01												
CD 54122 N2L	CM 54145 N2L	SSI 263												
CD 54123 N2L	CM 54146 N2L													
CD 54147 N2L	CM 54166 N2L													
ex 8542 11 99	Amplifier, of bipolar technology for the amplification of either read or write signals of floppy disk, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 11 × 29 mm, with not more than 22 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: XR 2247 XR 3470 or — other identification markings relating to devices complying with the abovementioned description	0												
ex 8542 11 99	Six-channel monolithic integrated circuit (read/write data processor circuit) for the amplification and conversion of read signals and conversion of write signals for hard-disk drives, contained in a housing the exterior dimensions of which do not exceed 19 × 38 mm, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of letters and figures: SSI 540 SSI 541 or — other identification markings relating to devices complying with the abovementioned description	0												

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 99	Programmable amplifier, of bipolar technology for signals on a digital communications bus, in the form of monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17×21 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: HS 3182 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Repeater circuit, of bipolar technology for the regeneration of pulse-code-modulated signals, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 10×21 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: XR C 240 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Smoke detector operating in a temperature range between at least -20 to $+50$ °C, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 23×9 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CS 235 V 24216 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 20	Amplifier, in the form of a monolithic integrated analogue circuit, the exterior dimensions of which do not exceed 3×3 mm for use in the manufacture of products falling within code 9021 40 00 (a)	0
ex 8542 19 30	Amplifier, in the form of a monolithic integrated analogue circuit, contained in a housing the exterior dimensions of which do not exceed $2 \times 4 \times 4$ mm, with not more than 10 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: C 05 V 35 - or — other identification markings relating to devices complying with the abovementioned description for the manufacture of products falling within code 9021 40 00 (a)	0
ex 8542 19 30	Electronically adjustable differential amplifiers for at least the full range of signals from 0 to not less than 400 MHz, in the form of a monolithic integrated analogue circuit, contained in a housing the exterior dimensions of which do not exceed 11×11 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures: 0078-10 - or — other identification markings relating to devices complying with the abovementioned description	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)
ex 8542 19 30	Amplifier for a full range of signals from 0 to 60 kHz, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed $6 \times 13 \times 26$ mm, with not more than 18 connecting pins and a leakage of not more than $0,3 \mu\text{A}$ and bearing: — an identification marking consisting of or including the following combination of figures and letters: ISO 100 or — other identification markings relating to devices complying with the abovementioned description, for use in the manufacture of telephone exchanges (a)	0
ex 8542 19 30	Read/write amplifier for thin-film magnetic heads, in the form of a monolithic integrated analogue circuit, contained in a housing the exterior dimensions of which do not exceed 8×11 mm, with not more than 24 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: VM 114 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 30	Winchester disk drive amplifier for magnetic heads, in the form of a monolithic integrated analogue circuit, contained in a housing the exterior dimensions of which do not exceed 7×7 mm, with not more than 10 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: A 2480 FC or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 30	Amplifier with a programmable gain factor, in the form of a monolithic integrated analogue circuit, contained in a housing the exterior dimensions of which do not exceed 30×45 mm, with not more than 32 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 3606 G or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 30	Thermocouple amplifier for instrumentation control at temperatures from 0 to 50°C, incorporating an alarm system, in the form of a monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 20×8 mm, with not more than 14 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AD 594 AD 595 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 70	Interface module for pulse code modulated data lines (PCM line interface) for decoding and simultaneous PCM data transmission in both directions (full duplex), of C-MOS technology, in the form of a monolithic integrated analogue circuit, contained in a housing the exterior dimensions of which do not exceed 17×39 mm, with not more than 28 connecting pins and bearing:	

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)
ex 8542 19 70 (cont'd)	— an identification marking consisting of or including the following combination of figures and letters: CS 61534 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Filter unit, of C-MOS technology, for signals with a frequency of 300 Hz or more but not exceeding 3 000 Hz, consisting of a receiver/transmitter, an analogue-to-digital converter, a dual-tone multifrequency generator (DTMF) and interface registers for a central processing unit (CPU), in the form of a monolithic integrated analogue circuit, contained in a housing the exterior dimensions of which do not exceed 14 × 21 mm, with not more than 60 connecting pins, an bearing: — an identification marking consisting of or containing the following combination of figures and letters: STC 9130 F - or — other identification markings relating to circuits complying with the abovementioned description	0
ex 8542 19 90	Four-channel track-and-hold circuit of C-MOS technology, in the form of a monolithic integrated analogue circuit contained in a housing the exterior dimensions of which do not exceed 9 × 25 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: CS 31412 - or: — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Pre-magnetization control circuit for audio frequency magnetic tapes, of bipolar technology, in the form of a monolithic integrated analogue circuit, contained in a housing the exterior dimensions of which do not exceed 26 × 8 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: PC 1297 CA - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Monolithic integrated analogue circuit for the reduction of audio noise by 14 dB, contained in a housing the exterior dimensions of which do not exceed 26 × 7 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: HA 12043 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	AM and FM receiver, of bipolar technology, in the form of a monolithic integrated analogue circuit, contained in a housing the exterior dimensions of which do not exceed 14 × 37 mm, with not more than 28 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 19 90 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures and letters: CXA 1030 P CXA 1240 P or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 19 90	Delay line, of C-MOS technology, for drop-out compensation of video signals, in the form of a monolithic integrated analogue circuit contained in a housing the exterior dimensions of which do not exceed 10 × 7 mm, with not more than eight connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: MSM 6965 RS or — other identification marking relating to devices complying with the abovementioned description	0
ex 8542 19 90	Two-channel monolithic integrated analogue circuit for the demodulation of FM-modulated signals, contained in a housing the dimensions of which do not exceed 28 × 9 mm, with not more than 30 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: HA 12083 NT or — other identification marking to devices complying with the abovementioned description	7
ex 8542 19 90	Monolithic integrated analogue circuit of bipolar technology for the overload protection of telephone exchanges, contained in a housing the exterior dimensions of which do not exceed 11 × 10 mm, with not more than three connecting pins and bearing: — an identification marking consisting of or including the following combination of figures: 1515 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Frequency generator of bipolar technology, with an operating voltage of not less than 40 and not more than 130 V AC, which generates signals oscillating between 512 (± 22 %) and 640 Hz (± 22 %) at a 10 Hz rate, in the form of an analogue monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 9 × 11 mm, with not more than eight connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: QMV 155 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Temperature transducer in the form of a monolithic analogue integrated circuit, contained in a housing the exterior dimensions of which do not exceed 6 × 4 mm, with not more than three connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 19 90 (cont'd)	— an identification marking consisting of or including the following combination of figures and letters: AD 590 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Monolithic integrated analogue circuit of C-MOS technology for controlling the speed of linear or rotary motors and the positioning of magnetic heads, contained in a housing the exterior dimensions of which do not exceed 14 × 38 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: A 2460 A 2461 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Monolithic integrated analogue circuit of bipolar technology for driving linear motors or motors with rotating arms, working at 20 V/2,5 A maximum, contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: EL 2007 EL 2017 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 00	32-bit microprocessor in C-MOS technology, consisting of a single substrate layer on which are mounted two chips, comprising a central processing unit (CPU) and a memory unit, in the form of a hybrid integrated circuit, contained in a housing the exterior dimensions of which do not exceed 33 × 76 mm, with not more than 60 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 57-00000 57-19400 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 00	16-bit digital-to-analogue converter, in the form of a hybrid integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: DAC 705 DAC 706 DAC 707 DAC 708 DAC 709 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 00	Video digital-to-analogue converter (VDAC) with a maximum conversion time of 10 ns, in the form of a hybrid integrated circuit, contained in a housing the exterior dimensions of which do not exceed 20 × 35 mm, with not more than 24 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 20 00 (cont'd)	— an identification marking consisting of or including one of the following combinations of figures and letters: VDAC 0405 H VDAC 0605 H VDAC 0805 H - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 00	Four-channel digital-to-analogue converter, each channel having a capacity of 12 bits, in the form of a hybrid integrated circuit, contained in a housing the external dimensions of which do not exceed 41 × 21 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 390 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 00	Amplifier for the frequency range 20 to 20 000 Hz, in the form of a hybrid integrated circuit, contained in a housing the exterior dimensions of which do not exceed 45 × 80 mm, with not more than 30 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: STK 4041 STK 4151 STK 4201 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 00	Infra-red receiver with a carrier frequency of not less than 36 kHz and not more than 40 kHz, in the form of a hybrid integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 15 mm, with not more than five connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: BX 1317 BX 1323 BX 1387 BX 1407 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 00	Subscriber-connection units (crosspoint switch) with not less than four and not more than 12 switches and an operating voltage of at least 150 V, in the form of a hybrid integrated circuit, contained in a housing the dimensions of which do not exceed 92 × 41 mm, with not more than 94 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 904 719 - or — other identification markings relating to devices complying with the abovementioned description	0
ex 9021 30 90	Vascular prostheses, neither woven nor knitted, of which the largest opening has an internal diameter not exceeding 8 mm	0