

Official Journal of the European Union

L 162



English edition

Legislation

Volume 61

27 June 2018

Contents

I *Legislative acts*

DIRECTIVES

- ★ **Council Directive (EU) 2018/912 of 22 June 2018 amending Directive 2006/112/EC on the common system of value added tax as regards the obligation to respect a minimum standard rate** 1

II *Non-legislative acts*

REGULATIONS

- ★ **Council Regulation (EU) 2018/913 of 25 June 2018 amending Regulation (EU) No 1388/2013 opening and providing for the management of autonomous tariff quotas of the Union for certain agricultural and industrial products** 3
- ★ **Council Regulation (EU) 2018/914 of 25 June 2018 amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products** 8

EN

Acts whose titles are printed in light type are those relating to day-to-day management of agricultural matters, and are generally valid for a limited period.

The titles of all other acts are printed in bold type and preceded by an asterisk.

I

(Legislative acts)

DIRECTIVES

COUNCIL DIRECTIVE (EU) 2018/912

of 22 June 2018

amending Directive 2006/112/EC on the common system of value added tax as regards the obligation to respect a minimum standard rate

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Article 113 thereof,

Having regard to the proposal from the European Commission,

After transmission of the draft legislative act to the national parliaments,

Having regard to the opinion of the European Parliament ⁽¹⁾,Having regard to the opinion of the European Economic and Social Committee ⁽²⁾,

Acting in accordance with a special legislative procedure,

Whereas:

- (1) Article 97 of Council Directive 2006/112/EC ⁽³⁾ provides that, from 1 January 2016 until 31 December 2017, the standard rate may not be lower than 15 %.
- (2) The application of a standard rate of value added tax (VAT) ensures the smooth functioning of the common system of VAT and should therefore be kept in place.
- (3) It is appropriate to maintain the current minimum standard rate at 15 %, and to make it permanent.
- (4) Since the objective of this Directive, namely to set a minimum standard rate of VAT, cannot be sufficiently achieved by the Member States, but can rather, by reason of the scale or effects of the action, be better achieved at Union level, the Union may adopt measures, in accordance with the principle of subsidiarity as set out in Article 5 of the Treaty on European Union. In accordance with the principle of proportionality as set out in that Article, this Directive does not go beyond what is necessary in order to achieve that objective.
- (5) Directive 2006/112/EC should therefore be amended accordingly,

HAS ADOPTED THIS DIRECTIVE:

Article 1

Article 97 of Directive 2006/112/EC is replaced by the following:

'Article 97

The standard rate shall not be lower than 15 %.'

⁽¹⁾ Opinion of the European Parliament of 19 April 2018 (not yet published in the Official Journal).⁽²⁾ Opinion of the European Economic and Social Committee of 23 May 2018 (not yet published in the Official Journal).⁽³⁾ Council Directive 2006/112/EC of 28 November 2006 on the common system of value added tax (OJ L 347, 11.12.2006, p. 1).

Article 2

1. Member States shall bring into force the laws, regulations and administrative provisions necessary to comply with this Directive by 1 September 2018 at the latest. They shall immediately communicate the text of those measures to the Commission.

When Member States adopt those measures, they shall contain a reference to this Directive or be accompanied by such a reference on the occasion of their official publication. Member States shall determine how such a reference is to be made.

2. Member States shall communicate to the Commission the text of the main measures of national law which they adopt in the field covered by this Directive.

Article 3

This Directive shall enter into force on the twentieth day following that of its publication in the *Official Journal of the European Union*.

Article 4

This Directive is addressed to the Member States.

Done at Luxembourg, 22 June 2018.

For the Council

The President

V. GORANOV

II

(Non-legislative acts)

REGULATIONS

COUNCIL REGULATION (EU) 2018/913

of 25 June 2018

amending Regulation (EU) No 1388/2013 opening and providing for the management of autonomous tariff quotas of the Union for certain agricultural and industrial products

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Article 31 thereof,

Having regard to the proposal from the European Commission,

Whereas:

- (1) In order to ensure the sufficient and uninterrupted supply of certain goods insufficiently produced in the Union and to avoid disturbances on the market for certain agricultural and industrial products, autonomous tariff quotas were opened by Council Regulation (EU) No 1388/2013 ⁽¹⁾. Products within those tariff quotas can be imported into the Union at reduced or zero duty rates.
- (2) For those reasons, it is necessary to open, with effect from 1 July 2018, tariff quotas at zero duty rates for an appropriate volume as regards seven new products.
- (3) In the case of eight additional products, the quota volumes should be increased, as an increase is in the interest of economic operators of the Union.
- (4) In the case of three products, the description should be amended.
- (5) Regulation (EU) No 1388/2013 should therefore be amended accordingly.
- (6) In order to avoid any interruption of the application of the quota scheme and to comply with the guidelines set out in the Communication from the Commission concerning autonomous tariff suspensions and quotas ⁽²⁾, the changes provided for in this Regulation regarding the quotas for the products concerned have to apply from 1 July 2018. The Regulation should therefore enter into force as a matter of urgency,

HAS ADOPTED THIS REGULATION:

Article 1

The Annex to Regulation (EU) No 1388/2013 is amended as follows:

- (1) in the table, all asterisks are deleted from the order numbers in the first column;

⁽¹⁾ Council Regulation (EU) No 1388/2013 of 17 December 2013 opening and providing for the management of autonomous tariff quotas of the Union for certain agricultural and industrial products, and repealing Regulation (EU) No 7/2010 (OJ L 354, 28.12.2013, p. 319).

⁽²⁾ OJ C 363, 13.12.2011, p. 6.

- (2) the rows for the tariff quotas with order numbers 09.2726, 09.2728, 09.2684, 09.2730, 09.2732, 09.2734 and 09.2736 set out in Annex I to this Regulation are inserted into the table according to the order of the CN codes indicated in the second column;
- (3) in the table, the rows for the tariff quotas with order numbers 09.2700, 09.2624, 09.2647, 09.2648, 09.2682, 09.2696, 09.2697, 09.2676, 09.2876, 09.2721 and 09.2643 are replaced by the corresponding rows set out in Annex II to this Regulation.

Article 2

This Regulation shall enter into force on the day following that of its publication in the *Official Journal of the European Union*.

It shall apply from 1 July 2018.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Luxembourg, 25 June 2018.

For the Council
The President
N. DIMOV

ANNEX I

In the table in the Annex to Regulation (EU) No 1388/2013, the following rows are inserted according to the order of the CN codes indicated in the second column of that table:

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty (%)
09.2726	ex 2906 11 00	10	Levomethol (INN) (CAS RN 2216-51-5)	1.7.-31.12	185 tonnes	0 %
09.2728	ex 2915 90 70	85	Ethyl trifluoroacetate (CAS RN 383-63-1)	1.7.-31.12	200 tonnes	0 %
09.2684	ex 2916 39 90	28	2,5-dimethylphenylacetyl chloride (CAS RN 55312-97-5)	1.7.-31.12	125 tonnes	0 %
09.2730	ex 2921 59 90	80	4,4'-Methanediyl dianiline (CAS RN 101-77-9) in form of granules, for use in the manufacture of prepolymers ⁽²⁾	1.7.-31.12	100 tonnes	0 %
09.2732	ex 2933 39 99	66	Fluazinam (ISO) (CAS RN 79622-59-6), with a purity by weight of 98,5 % or more	1.7.-31.12	100 tonnes	0 %
09.2734	ex 7409 19 00	20	Plates or sheets consisting of: — a layer of a silicon nitride ceramic with a thickness of 0,32 mm ($\pm$ 0,1 mm) or more, but not more than 1,0 mm ($\pm$ 0,1 mm), — covered on both sides with a foil of refined copper with a thickness of 0,8 mm ($\pm$ 0,1 mm), and — on one side partially covered with a coating of silver	1.7.-31.12	3 500 000 pieces	0 %
09.2736	ex 7607 11 90	83	Aluminium and magnesium alloy strip or foil: — of an alloy conforming to standards 5182-H19 or 5052-H19, — in rolls with an outside diameter of not more than 1 350 mm, — of a thickness (tolerance - 0,006 mm) of 0,15 mm, 0,16 mm, 0,18 mm or 0,20 mm, — a width (tolerance $\pm$ 0,3 mm) of 12,5 mm, 15,0 mm, 16,0 mm, 25,0 mm, 35,0 mm, 50,0 mm or 356 mm, — a camber tolerance of not more than 0,5 mm/750 mm, — a flatness measurement of I-unit $\pm$ 5, — a tensile strength of more than (5182-H19) 365MPa or (5052-H19) 320MPa, and — an elongation at break of more than (5182-H19) 3 % or (5052-H19) 2,5 %, for use in the manufacture of slats for blinds ⁽²⁾	1.7.-31.12.2018	300 tonnes	0 %

⁽²⁾ Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1).'

ANNEX II

In the table in the Annex to Regulation (EU) No 1388/2013, the rows for the tariff quotas with order numbers 09.2700, 09.2624, 09.2647, 09.2648, 09.2682, 09.2696, 09.2697, 09.2676, 09.2876, 09.2721 and 09.2643 are replaced by the following:

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty (%)
09.2700	ex 2905 12 00	10	Propan-1-ol (propyl alcohol) (CAS RN 71-23-8)	1.1.-31.12	15 000 tonnes	0 %
09.2624	2912 42 00		Ethylvanillin (3-ethoxy-4-hydroxybenzaldehyde) (CAS RN 121-32-4)	1.1.-31.12	1 950 tonnes	0 %
09.2647	ex 2918 29 00	80	Pentaerythritol tetrakis(3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate) (CAS RN 6683-19-8): — with a sieve passing fraction at a mesh width of 250 µm of more than 75 % by weight and at a mesh width of 500 µm of more than 99 % by weight, and — a melting point of 110 °C or more, but not more than 125 °C, for use in the manufacture of PVC processing stabiliser-one packs based on powder mixtures (powders or press granulates) ⁽²⁾	1.1.-31.12	140 tonnes	0 %
09.2648	ex 2920 90 10	70	Dimethyl Sulphate (CAS RN 77-78-1)	1.1.-31.12	18 000 tonnes	0 %
09.2682	ex 2921 41 00	10	Aniline with a purity by weight of 99 % or more (CAS RN 62-53-3)	1.1.-31.12	150 000 tonnes	0 %
09.2696	ex 2932 20 90	25	Decan-5-olide (CAS RN 705-86-2)	1.1.-31.12	6 000 kilograms	0 %
09.2697	ex 2932 20 90	30	Dodecan-5-olide (CAS RN 713-95-1)	1.1.-31.12	6 000 kilograms	0 %
09.2676	ex 3204 17 00	14	Preparations based on Colourant C.I. Pigment Red 48:2 (CAS RN 7023-61-2) with a content thereof of 60 % or more, but less than 85 % by weight	1.1.-31.12	50 tonnes	0 %
09.2876	ex 3811 29 00	55	Additives consisting of reaction products of diphenylamine and branched nonenes containing by weight: — 28 % or more, but not more than 55 % of 4-monononyldiphenylamine, — 45 % or more, but not more than 65 % of 4,4'-dinonyldiphenylamine, and — not more than 5 % of 2,4-dinonyldiphenylamine and 2,4'-dinonyldiphenylamine, used for the manufacture of lubricating oils ⁽²⁾	1.1.-31.12	900 tonnes	0 %

Order number	CN code	TARIC	Description	Quota period	Quota volume	Quota duty (%)
09.2721	ex 5906 99 90	20	Woven and laminated rubberised textile fabric with the following characteristics: — with three layers, — one outer layer consists of acrylic fabric, — the other outer layer consists of polyester fabric, — the middle layer consists of chlorobutyl rubber, — the middle layer has a weight of 452 g/m ² or more, but not more than 569 g/m ² , — the textile fabric has a total weight of 952 g/m ² or more, but not more than 1 159 g/m ² , — the textile fabric has a total thickness of 0,8 mm or more, but not more than 4 mm, used for the manufacture of the retractable roof of motor vehicles ⁽²⁾	1.1.-31.12	375 000 square meters	0 %
09.2643	ex 8504 40 82	30	Power supply boards for use in the manufacture of goods falling under heading 8521 and 8528 ⁽²⁾	1.1.-31.12	15 000 000 pieces	0 %

⁽²⁾ Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1).'

COUNCIL REGULATION (EU) 2018/914**of 25 June 2018****amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products**

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Article 31 thereof,

Having regard to the proposal from the European Commission,

Whereas:

- (1) The Union production of 85 products that are not listed in the Annex to Council Regulation (EU) No 1387/2013 ⁽¹⁾ is not sufficient to cover the needs of Union industry. It is therefore in the interest of the Union to suspend the autonomous Common Customs Tariff ('CCT') duties on those products.
- (2) It is necessary to modify the conditions for the suspension of autonomous CCT duties for certain products listed in the Annex to Regulation (EU) No 1387/2013 in order to take into account technical developments in relation to products and economic trends on the market. In particular, for one suspension it is necessary to adapt the end-use requirements, for one other suspension the applicable duty rate should be amended, for 19 suspensions the description should be clarified or aligned, for 14 suspensions it is necessary to change the classification and for 18 suspensions the supplementary unit should be adapted.
- (3) It is no longer in the interest of the Union to maintain the suspension of autonomous CCT duties for five products listed in the Annex to Regulation (EU) No 1387/2013. Suspensions for those products should therefore be deleted from that Annex.
- (4) Regulation (EU) No 1387/2013 should therefore be amended accordingly.
- (5) In order to avoid any interruption of the application of the autonomous suspension scheme and to comply with the guidelines set out in the Communication from the Commission concerning autonomous tariff suspensions and quotas ⁽²⁾, the changes provided for in this Regulation regarding the suspensions for the products concerned have to apply from 1 July 2018. This Regulation should therefore enter into force as a matter of urgency,

HAS ADOPTED THIS REGULATION:

Article 1

The Annex to Regulation (EU) No 1387/2013 is amended as follows:

- (1) all asterisks in the table and the endnote (*), containing the text 'A newly introduced measure or a measure with amended conditions.', are deleted;
- (2) in the table, the rows for the products for which the CN and TARIC codes are set out in Annex I to this Regulation are deleted;
- (3) the rows for the products listed in Annex II to this Regulation are inserted into the table according to the order of the CN and TARIC codes indicated in the first and second columns of that table, respectively.

Article 2

This Regulation shall enter into force on the day following that of its publication in the *Official Journal of the European Union*.

It shall apply from 1 July 2018.

⁽¹⁾ Council Regulation (EU) No 1387/2013 of 17 December 2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products and repealing Regulation (EU) No 1344/2011 (OJ L 354, 28.12.2013, p. 201).

⁽²⁾ OJ C 363, 13.12.2011, p. 6.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Luxembourg, 25 June 2018.

For the Council

The President

N. DIMOV

ANNEX I

In the table set out in the Annex to Regulation (EU) No 1387/2013, the rows relating to suspensions for the products identified by the following CN and TARIC codes are deleted:

CN code	TARIC
ex 2106 90 92	50
ex 2837 20 00	20
ex 2841 90 30	10
ex 2912 29 00	35
ex 2916 14 00	30
ex 2921 59 90	10
ex 2932 20 90	50
ex 2934 20 80	15
ex 2934 99 90	54
ex 3208 90 19	25
ex 3208 90 91	20
ex 3705 00 90	10
ex 3801 90 00	20
ex 3824 99 92	73
ex 3824 99 96	45
ex 3901 90 80	91
ex 3906 90 90	63
ex 3907 20 99	80
ex 3909 40 00	40
ex 3912 90 10	10
ex 3919 90 80	29
ex 3920 99 90	20
ex 3926 30 00	10
ex 3926 90 97	50
ex 3926 90 97	77
ex 7020 00 10	20
ex 8108 20 00	55
ex 8108 20 00	70
ex 8108 90 30	15
ex 8108 90 30	80
ex 8108 90 50	45

CN code	TARIC
ex 8108 90 60	30
ex 8415 90 00	20
ex 8483 30 32	20
ex 8483 30 38	50
ex 8483 40 90	20
ex 8501 31 00	25
ex 8503 00 91	31
ex 8503 00 99	32
ex 8503 00 99	50
ex 8505 11 00	60
ex 8505 19 90	50
ex 8507 60 00	25
ex 8529 90 92	55
ex 8529 90 92	59
ex 8708 29 10	10
ex 8708 29 90	10
ex 8708 95 10	40
ex 8708 95 99	10
ex 8708 99 10	30
ex 8708 99 97	15
ex 9013 80 90	20.

ANNEX II

In the table set out in the Annex to Regulation (EU) No 1387/2013, the following rows are inserted according to the order of the CN and TARIC codes indicated in the first and second columns of that table, respectively:

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
'ex 2106 90 92	50	Casein protein hydrolysate consisting of: — by weight 20 % or more, but not more than 70 % free amino acids, and — peptones of which by weight more than 90 % having a molecular weight of not more than 2 000 Da	0 %	—	31.12.2022
ex 2106 90 98	47	Preparation, having a moisture content of 1 % or more, but not more than 4 %, and containing by weight: — 15 % or more, but not more than 35 % of buttermilk, — 20 % ($\pm$ 10 %) of lactose, — 20 % ($\pm$ 10 %) of whey protein concentrate, — 15 % ($\pm$ 10 %) of cheddar cheese, — 3 % ($\pm$ 2 %) of salt, — 0,1 % or more, but not more than 10 % of lactic acid E270, — 0,1 % or more, but not more than 10 % of gum arabic E414, for use in the manufacture of products of the food and drink industry ⁽²⁾	0 %	—	31.12.2022
ex 2712 90 99	10	Blend of 1-alkenes (alpha-olefins) (CAS RN 131459-42-2) containing by weight 80 % or more of 1-alkenes of a chain length of 24 carbon atoms or more, but not exceeding 64 carbon atoms containing by weight more than 72 % 1-alkenes with more than 28 carbon atoms	0 %	—	31.12.2022
ex 2841 90 30	10	Potassium metavanadate (CAS RN 13769-43-2)	0 %	—	31.12.2022
ex 2842 10 00	50	Fluorophlogopite (CAS RN 12003-38-2)	0 %	—	31.12.2022
ex 2842 90 80	30	Aluminum trititanium dodecachloride (CAS RN 12003-13-3)	0 %	—	31.12.2022
ex 2903 99 80	60	1,1'-methanediylbis(4-fluorobenzene) (CAS RN 457-68-1)	0 %	—	31.12.2022
ex 2905 29 90	10	Cis-hex-3-en-1-ol (CAS RN 928-96-1)	0 %	—	31.12.2022
ex 2906 29 00	50	2,2'-(m-phenylene)dipropan-2-ol (CAS RN 1999-85-5)	0 %	—	31.12.2022
ex 2907 29 00	75	Biphenyl-4,4'-diol (CAS RN 92-88-6)	0 %	—	31.12.2018
ex 2912 29 00	35	Cinnamaldehyde (CAS RN 104-55-2)	0 %	—	31.12.2022
ex 2912 29 00	45	p-Phenylbenzaldehyde (CAS RN 3218-36-8)	0 %	—	31.12.2022
ex 2912 49 00	50	2,6-dihydroxybenzaldehyde (CAS RN 387-46-2)	0 %	—	31.12.2022
ex 2914 29 00	70	2-sec-butylcyclohexanone (CAS RN 14765-30-1)	0 %	—	31.12.2022
ex 2914 29 00	80	1-(cedr-8-en-9-yl)ethanone (CAS RN 32388-55-9)	0 %	—	31.12.2022

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
ex 2915 39 00	10	Cis-3-hexenyl acetate (CAS RN 3681-71-8)	0 %	—	31.12.2022
ex 2915 39 00	30	4-tert-butylcyclohexyl acetate (CAS RN 32210-23-4)	0 %	—	31.12.2022
ex 2915 90 70	20	Methyl (R)-2-fluoropropionate (CAS RN 146805-74-5)	0 %	—	31.12.2022
ex 2916 20 00	20	Mixture of the (1S,2R,6R,7R)-and(1R,2R,6R,7S)-isomers of ethyl tricyclo[5.2.1.0(2,6)]decane-2-carboxylate (CAS RNs 80657-64-3 and 80623-07-0)	0 %	—	31.12.2022
ex 2918 30 00	15	2-fluoro-5-formylbenzoic Acid (CAS RN 550363-85-4)	0 %	—	31.12.2022
ex 2918 99 90	38	Diclofop-methyl (ISO) (CAS RN 51338-27-3)	0 %	—	31.12.2022
ex 2921 59 90	10	Mixture of isomers of 3,5-diethyltoluenediamine (CAS RN 68479-98-1, CAS RN 75389-89-8)	0 %	—	31.12.2018
ex 2922 39 00	15	2-Amino-3,5-dibromobenzaldehyde (CAS RN 50910-55-9)	0 %	—	31.12.2022
ex 2926 90 70	15	2-Cyclohexylidene-2-phenylacetonitrile (CAS RN 10461-98-0)	0 %	—	31.12.2022
ex 2926 90 70	18	Flumethrin (ISO) CAS RN 69770-45-2)	0 %	—	31.12.2022
ex 2926 90 70	33	Deltamethrin (ISO) (CAS RN 52918-63-5)	0 %	—	31.12.2022
ex 2927 00 00	25	2,2'-azobis(4-methoxy-2,4-dimethylvaleronitrile) (CAS RN 15545-97-8)	0 %	—	31.12.2022
ex 2931 90 00	10	(3-fluoro-5-isobutoxyphenyl)boronic acid (CAS RN 850589-57-0)	0 %	—	31.12.2022
ex 2932 13 00	20	Furfuryl Alcohol (CAS RN 98-00-0)	0 %	—	31.12.2022
ex 2932 20 90	50	L-Lactide (CAS RN 4511-42-6) or D-Lactide (CAS RN 13076-17-0) or dilactide (CAS RN 95-96-5)	0 %	—	31.12.2022
ex 2932 99 00	23	2-ethyl-3-hydroxy-4-pyrone (CAS RN 4940-11-8)	0 %	—	31.12.2022
ex 2933 39 99	38	(2-chloropyridin-3-yl) methanol (CAS RN 42330-59-6)	0 %	—	31.12.2022
ex 2933 39 99	39	2,6-dichloropyridine-3-carboxamide (CAS RN 62068-78-4)	0 %	—	31.12.2022
ex 2933 39 99	51	2,5-Dichloro-4,6-dimethylnicotinonitrile (CAS RN 91591-63-8)	0 %	—	31.12.2022
ex 2933 59 95	22	6-chloro-1,3-dimethyluracil (CAS RN 6972-27-6)	0 %	—	31.12.2022
ex 2933 59 95	24	1-(Cyclopropylcarbonyl)piperazine Hydrochloride (CAS RN 1021298-67-8)	0 %	—	31.12.2022
ex 2933 59 95	26	5-Fluoro-4-hydrazino-2-methoxypyrimidine (CAS RN 166524-64-7)	0 %	—	31.12.2022
ex 2933 79 00	25	Methyl 2-oxo-2,3-dihydro-1H-indole-6-carboxylate (CAS RN 14192-26-8)	0 %	—	31.12.2022
ex 2933 99 80	48	5-Amino-6-methyl-2-benzimidazolone (CAS RN 67014-36-2)	0 %	—	31.12.2022
ex 2934 20 80	15	Benthiavalicarb-isopropyl (ISO) (CAS RN 177406-68-7)	0 %	—	31.12.2022
ex 2934 99 90	54	2-benzyl-2-dimethylamino-4'-morpholinobutyrophe- none (CAS RN 119313-12-1)	0 %	—	31.12.2022

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
ex 2934 99 90	59	Dolutegravir (INN) (CAS RN 1051375-16-6) or dolutegravir sodium (CAS RN 1051375-19-9)	0 %	—	31.12.2022
ex 2935 90 90	40	Venetoclax (INN) (CAS 1257044-40-8)	0 %	—	31.12.2022
ex 3204 13 00	15	Colourant C.I. Basic Blue 41 (CAS RN 12270-13-2) and preparations based thereon with a colourant C.I. Basic Blue 41 content of 50 % or more by weight	0 %	—	31.12.2022
ex 3204 13 00	25	Colourant C.I. Basic Red 46 (CAS RN 12221-69-1) and preparations based thereon with a colourant C.I. Basic Red 46 content of 20 % or more by weight	0 %	—	31.12.2022
ex 3204 13 00	35	Colourant C.I. Basic Yellow 28 (CAS RN 54060-92-3) and preparations based thereon with a colourant C.I. Basic Yellow 28 content of 75 % or more by weight	0 %	—	31.12.2022
ex 3204 13 00	45	Mixture of colourant C.I. Basic Blue 3 (CAS RN 33203-82-6) and colourant C.I. Basic Blue 159 (CAS RN 105953-73-9) with a colourant Basic Blue content of 60 % or more by weight	0 %	—	31.12.2022
ex 3204 16 00	40	Aqueous solution of Colourant C.I. Reactive Red 141 (CAS RN 61931-52-0): — with a colourant C.I. Reactive Red 141 content of 13 % or more by weight, and — containing a preservative	0 %	—	31.12.2022
ex 3204 17 00	29	Colourant C.I. Pigment Red 268 (CAS RN 16403-84-2) and preparations based thereon with a Colourant C.I. Pigment Red 268 content of 80 % or more by weight	0 %	—	31.12.2022
ex 3206 49 70	40	Colourant C.I. Pigment Blue 27 (CAS RN 25869-00-5) and preparations thereon with a colourant C.I. Pigment Blue 27 content of 85 % or more by weight	0 %	—	31.12.2022
ex 3208 90 19	25	Tetrafluoroethylene copolymer in butylacetate solution with a content of solvent of 50 % ($\pm$ 2 %) by weight	0 %	—	31.12.2022
ex 3904 69 80	89				
ex 3707 10 00	60	Sensitising emulsion, containing by weight: — not more than 5 % of photoacid generator, — 2 % or more, but not more than 50 % of phenolic resins, and — not more than 7 % of epoxy-containing derivatives, dissolved in heptan-2-one and/or ethyllactate	0 %	—	31.12.2022
ex 3801 90 00	20	Pitch coated graphite based powder with: — an average particle size of 10,8 μ m or more, but not more than 13,0 μ m, — an iron content of less than 40 ppm, — a copper content of less than 5 ppm, — a nickel content of less than 5 ppm,	0 %	—	31.12.2022

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
ex 3802 10 00	20	— an average surface area (N₂ atmosphere) of 3,0 m²/g or more, but not more than 4,36 m²/g, and — a magnetic metal impurity of less than 0,3 ppm Chemically activated carbon in granular form with a Butane Working Capacity of 11 g butane/100 ml or more (as determined by the ASTM D 5228 method) used for vapour absorption and desorption in emission control canisters of motor vehicles ⁽²⁾	0 %	—	31.12.2022
ex 3802 10 00	30	Chemically activated carbon in pellet (cylindrical) form, with: — a diameter of 2 mm or more, but not more than 3 mm, and — a Butane Working Capacity of 5 g butane/100 ml or more (as determined by the ASTM D 5228 method), used for vapour absorption and desorption in emission control canisters of motor vehicles ⁽²⁾	0 %	—	31.12.2021
ex 3808 93 90	60	Preparation in the form of tablets containing by weight: — 0,55 % or more, but not more than 2,50 % of 1-methylcyclopropene (1-MCP) (CAS RN 3100-04-7) with a minimum purity of 96 % or more, and — less than 0,05 % of each of the two impurities, 1-chloro-2-methylpropene (CAS RN 513-37-1) and 3-chloro-2-methylpropene (CAS RN 563-47-3), for coating ⁽²⁾	0 %	—	31.12.2022
ex 3824 99 93	38	Mixture of 4,4'-(perfluoroisopropylidene)diphenol (CAS RN 1478-61-1) and 4,4'-(perfluoroisopropylidene)diphenol benzyl triphenyl phosphonium salt (CAS RN 75768-65-9)	0 %	—	31.12.2022
ex 3824 99 96	30	Rare-earth concentrate containing by weight: — cerium oxide (CAS RN 1306-38-3) of 20 % or more, but not more than 30 %, — lanthanum oxide (CAS RN 1312-81-8) of 2 % or more, but not more than 10 %, — yttrium oxide (CAS RN 1314-36-9) of 10 % or more, but not more than 15 %, and — zirconium oxide (CAS RN 1314-23-4) including natural occurring hafnium oxide of not more than 65 %	0 %	—	31.12.2022
ex 3824 99 96	45	Lithium nickel cobalt aluminum oxide powder (CAS RN 177997-13-6) with: — a particle size of less than 10 µm, — a purity by weight of more than 98 %	0 %	—	31.12.2022
ex 3901 90 80	91	Ionomer resin consisting of a salt of a copolymer of ethylene with methacrylic acid	0 %	—	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
ex 3903 90 90	38	Polytetrafluoroethylene (CAS RN 9002-84-0) encapsulated with an acrylonitrile-styrene copolymer (CAS RN 9003-54-7), with a content by weight of each polymer of 50 % ($\pm$ 1)	0 %	—	31.12.2022
ex 3904 69 80	88				
ex 3906 90 90	23	Copolymer of methylmethacrylate, butylacrylate, glycidylmethacrylate and styrene (CAS RN 37953-21-2), with an epoxy equivalent weight of not more than 500, in form of ground flakes with a particle size of not more than 1 cm	0 %	—	31.12.2022
ex 3906 90 90	43	Copolymer of methacrylic esters, butylacrylate and cyclic dimethylsiloxanes (CAS RN 143106-82-5)	0 %	—	31.12.2021
ex 3907 20 99	80	Isoamyl alcohol polyoxyethylene ether (CAS RN 62601-60-9)	0 %	—	31.12.2022
ex 3907 30 00	70	Preparation of epoxy resin (CAS RN 29690-82-2) and phenolic resin (CAS RN 9003-35-4) containing by weight: — 65 % or more, but not more than 75 % of silicon dioxide (CAS RN 60676-86-0), and — none or not more than 0,5 % of carbon black (CAS RN 1333-86-4)	0 %	—	31.12.2022
ex 3907 40 00	45	α -(2,4,6-Tribromophenyl)- ω -(2,4,6-tribromophenoxy) poly[oxy(2,6-dibromo-1,4-phenylene)isopropylidene (3,5-dibromo-1,4-phenylene)oxycarbonyl] (CAS RN 71342-77-3)	0 %	—	31.12.2018
ex 3909 20 00	10	Polymer mixture, containing by weight: — 60 % or more, but not more than 75 % of melamine resin (CAS RN 9003-08-1), — 15 % or more, but not more than 25 % of silica (CAS RN 14808-60-7 or 60676-86-0), — 5 % or more, but not more than 15 % of cellulose (CAS RN 9004-34-6), and — 1 % or more, but not more than 15 % of phenolic resin (CAS RN 25917-04-8)	0 %	—	31.12.2022
ex 3912 90 10	10	Cellulose acetate propionate, non-plasticised, in the form of powder: — containing by weight 25 % or more of propionyl (as determined by the ASTM D 817-72 method), and — of a viscosity of not more than 120 poise (as determined by the ASTM D 817-72 method)	0 %	—	31.12.2018
ex 3919 90 80	21	Polytetrafluoroethylene film: — with a thickness of 50 μ m or more, but not more than 155 μ m, — with a width of 6,30 mm or more, but not more than 585 mm, — an elongation at break of not more than 200 %, and — coated on one side with a pressure sensitive silicon adhesive with a thickness of not more than 40 μ m	0 %	—	31.12.2022

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
ex 3919 90 80	22	Polyester, polyethylene or polypropylene film coated on one or both sides with an acrylic and/or rubber pressure sensitive adhesive, whether or not supplied with a release liner, put up in rolls of a width of 45,7 cm or more, but not more than 160 cm	0 %	—	31.12.2019
ex 3920 62 19	05	Poly(ethylene terephthalate) film in rolls:	0 %	—	31.12.2022
ex 3920 62 90	10	— with a thickness of 0,335 mm or more, but not more than 0,365 mm, and — coated with a gold layer with a thickness of 0,03 µm or more, but not more than 0,06 µm			
ex 3920 99 90	20	Anisotropic conductive film, in rolls, of a width of 1,2 mm or more, but not more than 3,15 mm and a maximum length of 300 m, used for joining electronic components in the production of LCD or plasma displays	0 %	—	31.12.2018
ex 3921 19 00	35	Multilayer film consisting of: — 30 % or more, but not more than 60 % of a micro-porous polypropylene layer (CAS RN 9003 07-0), — 20 % or more, but not more than 40 % of a micro-porous polyethylene layer (CAS RN 9002-88-4), and — 20 % or more, but not more than 40 % of a boehmite layer/coating (CAS RN 1318-23-6), for use in the manufacture of lithium-ion batteries ⁽²⁾	0 %	—	31.12.2022
ex 3926 30 00	10	Plastic cover with clips for the exterior rear-view mirror of motor vehicles	0 %	p/st	31.12.2020
ex 3926 90 97	23				
ex 8708 29 10	10				
ex 8708 29 90	10				
ex 3926 90 97	50	Knob of car radio front panel, made of Bisphenol A-based polycarbonate, in immediate packings of not less than 300 pieces	0 %	p/st	31.12.2018
ex 3926 90 97	77	Silicone decoupling ring, with an inner diameter of 15,4 mm (+ 0,0 mm/– 0,1 mm), in immediate packings of 2 500 pieces or more, of a kind used in car parking aid sensor systems	0 %	p/st	31.12.2021
ex 4016 99 57	30	Pin boot of a brake calliper made of vulcanised rubber with: — an inner diameter of not less than 5 mm and an outer diameter of not more than 35 mm, — a height of 15 mm or more, but not more than 40 mm, and — a ribbed design, for use in the manufacture of goods of Chapter 87 ⁽²⁾	0 %	—	31.12.2022

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
ex 5311 00 90	10	Plain-woven fabric of paper yarns glued on a tissue paper layer: — with a weight of 230 g/m ² or more, but not more than 280 g/m ² , and — cut into rectangles with a side length of 40 cm or more, but not more than 140 cm	0 %	—	31.12.2022
ex 5603 14 90	50	Non-woven fabric of microfibres, composed of polyester fibres with a uniform cross section with: — a weight of more than 150 g/m ² , — a denier of 0,06 or more, but not more than 0,50 den, — containing by weight 74 % or more of polyethylene terephthalate	0 %	m ²	31.12.2022
ex 5911 90 99	50	Loudspeaker vibration damper, made from round, corrugated, flexible and cut-to-size tissue of textile fibres of polyester, cotton or aramid or a combination hereof, of a kind used in car loudspeakers	0 %	—	31.12.2022
ex 7020 00 10	20	Raw material for optical elements of fused silicon dioxide with: — a thickness of 10 cm or more, but not more than 40 cm, and — a weight of 100 kg or more	0 %	p/st	31.12.2022
ex 7326 90 92	40	Steel nozzle shell with integral flange in one piece open-die forged from 4 castings, worked and machined, with: — a diameter of 5 752 mm or more, but not more than 5 758 mm, — a height of 3 452 mm or more, but not more than 3 454 mm, — a total weight 167 875 kg or more, but not more than 168 125 kg, of a kind used for the fabrication of a nuclear reactor vessel	0 %	p/st	31.12.2022
ex 7326 90 98	50	Surface-hardened, steel piston rod for a hydraulic or dropneumatic shock absorber of motor vehicles: — with a chrome coating, — of a diameter of 11 mm or more, but not more than 28 mm, — of a length of 80 mm or more, but not more than 600 mm, with a threaded end or a mandrel for resistance welding	0 %	—	31.12.2022
ex 7409 19 00	10	Plates or sheets:	0 %	—	31.12.2022
ex 7410 21 00	70	— with at least one layer of woven glass fibre, impregnated with a fire-retardant artificial or synthetic resin with a glass transition temperature (T _g) of more than 130 °C as measured according to IPC-TM-650, method 2.4.25,			

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
		— coated on one or both sides with a copper film with a thickness of not more than 3,2 mm, - and containing at least one of the following: — poly(tetrafluoroethylene) (CAS RN 9002-84-0), — poly(oxy-(2,6-dimethyl)-1,4-phenylene) (CAS RN 25134-01-4), — epoxy resin having a thermal expansion of not more than 10 ppm in length and width and not more than 25 ppm in height, for use in the manufacture of circuit boards ⁽²⁾			
ex 7413 00 00	20	Loudspeaker centering ring, consisting of one or more vibration dampers and minimum 2 non-insulated copper cables, therein woven or pressed of the kind used in car loudspeakers	0 %	—	31.12.2022
ex 8518 90 00	45				
ex 7606 12 20	20	Sign-plates composed of a polyethylene cellular core and outer layers of aluminium, with a total thickness of 1,8 mm or more, but not more than 4,2 mm	0 %	—	31.12.2022
ex 8108 20 00	55	Titanium alloy ingot: — with a height of 17,8 cm or more, a length of 180 cm or more, a width of 48,3 cm or more, — a weight of 680 kg or more, containing alloy elements by weight of: — 3 % or more, but not more than 7 % of aluminium, — 1 % or more, but not more than 5 % of tin, — 3 % or more, but not more than 5 % of zirconium, — 4 % or more, but not more than 8 % of molybdenum	0 %	p/st	31.12.2020
ex 8108 20 00	70	Titanium alloy slab, with: — a height of 20,3 cm or more, but not more than 23,3 cm, — a length of 246,1 cm or more, but not more than 289,6 cm, — a width of 40,6 cm or more, but not more than 46,7 cm, — a weight of 820 kg or more, but not more than 965 kg, containing alloy elements by weight of: — 5,2 % or more, but not more than 6,2 % of aluminium, — 2,5 % or more, but not more than 4,8 % of vanadium	0 %	p/st	31.12.2022

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
ex 8108 90 30	15	Rods and wire of an alloy of titanium with: — a uniform solid cross-section in the form of a cylinder, — with a diameter of 0,8 mm or more, but not more than 5 mm, — an aluminium content by weight of 0,3 % or more, but not more than 0,7 %, — a silicon content by weight of 0,3 % or more, but not more than 0,6 %, — a niobium content by weight of 0,1 or more, but not more than 0,3 %, and — an iron content by weight of not more than 0,2 %	0 %	—	31.12.2022
ex 8108 90 30	25	Titanium-aluminium-vanadium alloy (TiAl ₆ V ₄) bars, rods and wire, complying with AMS standards 4928, 4965 or 4967	0 %	—	31.12.2020
ex 8108 90 50	45	Cold or hot rolled plates, sheets and strips of non-alloyed titanium with: — a thickness of 0,4 mm or more, but not more than 100 mm, — a length of not more than 14 m, and — a width of not more than 4 m	0 %	—	31.12.2022
ex 8108 90 60	30	Seamless tubes and pipes of titanium or an alloy of titanium with: — a diameter of 19 mm or more, but not more than 159 mm, — a wall thickness of 0,4 mm or more, but not more than 8 mm, and — a maximum length of 18 m	0 %	—	31.12.2022
ex 8418 99 10	70	Evaporator made of aluminium for use in the manufacture of air conditioning machines for automobiles (?)	0 %	p/st	31.12.2021
ex 8481 10 99	20	Electromagnetic pressure reducing valve with: — a plunger, — at least 275 mPa internal tightness, — a plastic connector with 2 silver or tin pins	0 %	—	31.12.2022
ex 8481 10 99	30	Pressure reducing valves in a brass case with: — a length of not more than 18 mm (± 1 mm), — a width of not more than 30 mm (± 1 mm), of a kind used for incorporation in fuel delivery modules of motor vehicles	0 %	—	31.12.2022
ex 8481 80 59	30	Two-way flow control valve with housing, with: — at least 5, but not more than 9 outlet holes with at least 0,110 mm, but not more than 0,134 mm diameter,	0 %	—	31.12.2022

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
ex 8481 80 59	40	— at least 640 cm³/minute, but not more than 805 cm³/minute flow rate, — at least 19, but not more than 300 MPa operating pressure Flow-control valve: — made of steel, — with an outlet hole with a diameter of at least 0,175 mm, but not more than 0,185 mm, — with an inlet hole with a diameter of at least 0,255 mm, but not more than 0,265 mm, — with chromium nitride coating, — with a surface roughness of Rp 0,4	0 %	—	31.12.2022
ex 8481 80 59	50	Electromagnetic valve for quantity control with: — a plunger, — DLC (Diamond-like carbon) coating, — a solenoid with a of coil resistance of at least 2,6 Ohm, but not more than 3 Ohm, — a supply voltage of 12 V	0 %	—	31.12.2022
ex 8481 80 59	60	Electromagnetic valve for quantity control: — with a solenoid with a coil resistance of at least 0,19 Ohm, but not more than 0,52 Ohm, and with an inductance of at least 0,083 mH, but not more than 0,172 mH, — with a supply voltage of 24 V, — operating at a DC of at least 15,5 A, but not more than 16,5 A	0 %	—	31.12.2022
ex 8483 30 32	30	Bearing housing of a kind used in turbochargers: — of precision-cast grey cast iron complying with standard DIN EN 1561 or precision-cast ductile cast iron complying with DIN EN 1560,	0 %	p/st	31.12.2022
ex 8483 30 38	60	— with oil chambers, — without bearings, — with a diameter of 50 mm or more, but not more than 250 mm, — with a height of 40 mm or more, but not more than 150 mm, — whether or not with water chambers and connectors			
ex 8483 40 90	20	Hydrostatic transmission with: — measurements (without shafts) of not more than 154 mm × 115 mm × 108 mm, — a weight of not more than 3,3 kg, — a maximum rotation speed of the input shaft of 2 700 rpm or more, but not more than 3 200 rpm,	0 %	p/st	31.12.2022

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
ex 8501 31 00	50	— a torque of the output shaft of not more than 10,4 Nm, — a rotation speed of the output shaft of not more than 930 rpm at 2 800 rpm input speed, and — an operating temperature range of – 5 °C or more, but not more than + 40 °C, for use in the manufacture of hand-operated lawn mowers of subheading 8433 11 90 (?) DC motors, brushless, with: — an external diameter of 80 mm or more, but not more than 200 mm, — a supply voltage of 9 V or more, but not more than 16 V, — an output at 20 °C of 300 W or more, but not more than 750 W, — a torque at 20 °C of 2,00 Nm or more, but not more than 7,00 Nm, — a rated speed at 20 °C of 600 rpm or more, but not more than 3 100 rpm, — with or without the rotor angle position sensor of resolver type or Hall effect type, of the kind used in power steering systems for cars	0 %	—	31.12.2022
ex 8503 00 91	31	Rotor, at the inner side provided with one or two magnetic rings (uniform or sectional) whether or not incorporated in a steel ring	0 %	p/st	31.12.2018
ex 8503 00 99	32				
ex 8503 00 99	55	Stator for brushless motor, with: — an internal diameter of 206,6 mm (± 0,5), — an external diameter of 265,0 mm (± 0,2), and — a width of 37,2 mm or more, but not more than 47,8 mm, of a kind used in the manufacture of washing machines, washer-dryers or dryers equipped with direct drive drums	0 %	p/st	31.12.2018
ex 8504 50 95	80	Self-induction coil: — with one or more windings, with an inductivity per winding of no more than 62 mH, attached to one or more carrier materials, — with ferrites, — with one or more Negative Temperature Coefficient resistors as a temperature sensor, — whether or not with insulation covers, spacers and connection cables	0 %	—	31.12.2022

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
ex 8505 11 00	63	Rings, tubes, bushings or collars made from an alloy of neodymium, iron and boron, with: — an external diameter of not more than 45 mm, — a height of not more than 45 mm, of a kind used in the manufacture of permanent magnets after magnetisation	0 %	p/st	31.12.2022
ex 8505 19 90	50	Article of agglomerated ferrite in the shape of a rectangular prism to become a permanent magnet after magnetisation: — whether or not with bevelled edges, — of a length of 27 mm or more, but not more than 32 mm ($\pm 0,15$ mm), — of a width of 8,5 mm or more, but not more than 9,5 mm (+ 0,05 mm/– 0,09 mm), — of a thickness of 5,5 mm or more, but not more than 5,8 mm (+ 0/– 0,2 mm), and — of a weight of 6,1 g or more, but not more than 8,3 g	0 %	p/st	31.12.2022
ex 8506 50 30	10	Lithium manganese dioxide cell, with: — a diameter of 20 mm or more, but not more than 25 mm, — a length of 3 mm or more, but not more than 6 mm, — a voltage of 3 V or more, but not more than 3,4 V, — a capacity of 200 mAh or more, but not more than 600 mAh, — an automotive test temperature range from – 40 °C to + 125 °C, for use as a component within the manufacture of Tyre Pressure Measuring Systems (TPMS) ⁽²⁾	0 %	—	31.12.2022
ex 8507 50 00	40	Nickel-metal Hydride (NiMH) battery assembly, with: — a voltage of 190 V or more, but not more than 210 V, — a length of 220 mm or more, but not more than 280 mm, — a width of 500 mm or more, but not more than 600 mm, — a height of 100 mm or more, but not more than 150 mm, for use in the manufacture of motor vehicles of Chapter 87 ⁽²⁾	0 %	—	31.12.2022
ex 8507 60 00	25	Rectangular modules for incorporation in lithium-ion rechargeable batteries, with: — a width of 352,5 mm (± 1 mm) or 367,1 mm (± 1 mm), — a depth of 300 mm (± 2 mm) or 272,6 mm (± 1 mm),	0 %	p/st	31.12.2022

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
ex 8512 20 00	50	— a height of 268,9 mm ($\pm 1,4$ mm) or 229,5 mm (± 1 mm), — a weight of 45,9 kg or 46,3 kg, — a rating of 75 Ah, and — a nominal voltage of 60 V Cabin overhead lamp in a plastic housing whether or not with a storage box, with an operating voltage of 8 V or more, but not more than 16 V, containing: — at least two light sources, — light switch, — whether or not emergency call button (E-Call), — whether or not panoramic roof slide switch, — whether or not microphone, — whether or not ultrasonic sensor (UIP sensor), for use in the manufacture of motor vehicles ⁽²⁾	0 %	—	31.12.2022
ex 8512 30 90	30	Sound alarm device for protection against burglary into the vehicle: — with an operating temperature of -45 °C or more, but not more than $+95$ °C, — with a voltage of 9 V or more, but not more than 16 V, — in a plastic housing, — whether or not with a metal holder, for use in the manufacture of motor vehicles ⁽²⁾	0 %	—	31.12.2022
ex 8526 10 00	30	Radar sensor equipment with a control unit of blind spot detection system: — with a voltage of 8 V or more, but not more than 16 V, — in a plastic housing, — with cable and connector, for use in the manufacture of motor vehicles ⁽²⁾	0 %	—	31.12.2022
ex 8529 90 92	33	LCD modules combined with touch screen facilities: — solely consisting of one or more TFT cells, — with a diagonal measurement of the screen of 10,7 cm or more, but not more than 36 cm, — with or without LED backlight, — with control electronics for pixel addressing only, — without an EPROM memory (Erasable Programmable Read-only Memory), — with digital RGB Interface (Red, Green, Blue Interface), Touch-Screen Interface, used solely for installation in motor vehicles of Chapter 87 ⁽²⁾	0 %	—	31.12.2022

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
ex 8529 90 92	39	LCD modules with: — a diagonal measurement of the screen of 14,5 cm or more, but not more than 25,5 cm, — an LED backlight, — a printed circuit board with EPROM (Erasable Programmable Read-only Memory), microcontroller, timing controller, LIN (Local Interconnect Network) bus or APIX2 (Automotive Pixel Link) driver module and other active and passive components, — a 6 to 8 pin connector for power supply and a 2 to 4-pin connector for LVDS (Low-voltage differential signalling)/LIN signals or an APIX2 interface or an LVDS/LIN interface for signals and power supply, — whether or not in a housing, for permanent incorporation or permanent mounting into motor vehicles of Chapter 87 ⁽²⁾	0 %	p/st	31.12.2020
ex 8529 90 92	55	OLED modules, consisting of: — one or more TFT glass or plastic cells, containing organic material, — with or without combined touch screen facilities, and — one or more printed circuit boards with control electronics for pixel addressing, for use in the manufacture of TV sets and monitors or for use in the manufacture of vehicles of Chapter 87 ⁽²⁾	0 %	p/st	31.12.2019
ex 8537 10 91	55	Electronic control unit of automatic parking system with the ability to evaluate the surroundings of the car and control automatic parking: — of a voltage of 5 V or more, but not more than 16 V, — with programmable memory, — with at least one connector, — in a plastic housing, — whether or not with a metal holder, for use in the manufacture of goods of Chapter 87 ⁽²⁾	0 %	—	31.12.2022
ex 8537 10 91	65	Electronic control unit for optimal engine performance: — with a programmable memory, — with a voltage of 8 V or more, but not more than 16 V, — with at least one composite connector,	0 %	—	31.12.2022

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
ex 8537 10 98	85	— in a metal housing, — whether or not with metal holders, for use in the manufacture of motor vehicles ⁽²⁾ Electronic airbag control unit: — with an operating temperature of – 45 °C or more, but not more than 90 °C, — with a voltage of 8 V or more, but not more than 16 V, — with two connectors, — in a metal housing, for use in the manufacture of motor vehicles ⁽²⁾	0 %	—	31.12.2022
ex 8540 91 00	20	Thermionic electron source (emitter point) of lanthanum hexaboride (CAS RN 12008-21-8) or cerium hexaboride (CAS RN 12008-02-5), in a metal housing with electric connectors having: — a graphite carbon shield mounted in a mini-Vogel type system, — separate pyrolytic carbon blocks used as heating elements, and — a cathode temperature of less than 1 800 K at a filament current of 1,26 A	0 %	—	31.12.2022
ex 8708 40 20	50	Transmission assembly which houses 3 other shafts inside it and offers a rotating switch for shift position, consisting of:	0 %	—	31.12.2022
ex 8708 40 50	40	— cast aluminium body, — differential gear, — 2 electrical motors and gears, with the dimensions of: — a width of 300 mm or more, but not more than 350 mm, — a height of 420 mm or more, but not more than 500 mm, — a length of 500 mm or more, but not more than 600 mm, for use in the manufacture of motor vehicles of Chapter 87 ⁽²⁾			
ex 8708 50 20	50	Double flange bearing of 3rd generation, for motor vehicles:	0 %	—	31.12.2022
ex 8708 50 55	20	— with double-row ball bearing,			
ex 8708 50 91	10	— whether or not with impulse (encoder) ring,			
ex 8708 50 99	40	— whether or not with antilock brake system (ABS) sensor, — whether or not with mounted screws, for use in the manufacture of goods of Chapter 87 ⁽²⁾			
ex 8708 99 10	35	Holder of front radiator or intercooler whether or not with rubber cushioning for use in the manufacture of goods of Chapter 87 ⁽²⁾	0 %	p/st	31.12.2021
ex 8708 99 97	35				

CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
ex 8714 99 10	20	Bicycle handlebars:	0 %	—	31.12.2022
ex 8714 99 10	89	— with or without integrated stem, — made out of carbon fibres and synthetic resin, for use in the manufacture of bicycles ⁽²⁾			
ex 9013 80 90	30	Electronic semiconductor micro-mirror in a housing suitable for the automatic printing of conductor boards, mainly consisting of: — one or more microelectromechanical mirrors (MEMS) manufactured with semiconductor technology, with a drive arranged in three-dimensional structures on the semiconductor material, — whether or not in a combination with one or more monolithic application-specific integrated circuits (ASIC), of a kind used for incorporation into products of Chapters 84-90 and 95	0 %	p/st	31.12.2019

⁽²⁾ Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1).'

